

DIODE(THREE PHASES BRIDGE TYPE)

DF40AA120/160

TOP





UL;E76102 (M)

Power Diode Module **DF40AA** is designed for three phase full wave rectification, which has six diodes connected in a three phase bridge configuration. The mounting base of the module is electrically isolated from semiconductor elements for simple heatsink construction output DC current is 40Amp ($T_c=116^{\circ}\text{C}$) Repetitive peak reverse voltage is up to 1,600V.

- $T_{j\text{Max}}=150^{\circ}\text{C}$
- Isolated Mounting Base
- High reliability by unique glass passivation

(Applications)

AC. DC Motor Drive/AVR/Switching
—for three phase rectification



Maximum Ratings

(T_j=25°C)

Symbol	Item	Ratings		Unit
		DF40AA120	DF40AA160	
V _{RRM}	Repetitive Peak Reverse Voltage	1200	1600	V
V _{RSM}	Non-Repetitive Peak Reverse Voltage	1300	1700	V

Symbol	Item		Conditions	Ratings	Unit
I _D	Output current (D.C.)		Three phase. full wave. T _c =116°C	40	A
I _{FSM}	Surge Forward Current		1 cycle, 50/60Hz, peak value, non-repetitive	640/700	A
T _j	Junction Temperature			-40~+150	°C
T _{stg}	Storage Temperature			-40~+125	°C
V _{ISO}	Isolation Breakdown Voltage (R.M.S.)		Main Terminal to case 1minute	2500	V
	Mounting Torque	Mounting (M6)	Recommended Value 2.5~3.9 (25~40)	4.7 (48)	N·m (kgf·cm)
		Terminal (M5)	Recommended Value 1.5~2.5 (15~25)	2.7 (28)	
	Mass		Typical Value	200	g


Electrical Characteristics

Symbol	Item	Conditions	Ratings	Unit
I _{RRM}	Repetitive Peak Reverse Current, max.	T _j =150°C at V _{RRM}	8.0	mA
V _{FM}	Forward Voltage Drop, max.	I _{FM} =40A, T _j =25°C Inst. measurement	1.3	V
R _{th(j-c)}	Thermal Impedance, max.	Junction to case	0.32	°C/W


DF40AA120/160

[TOP](#)


Forward Voltage Drop max.




Output Current vs. Power Dissipation, max. (Three phase, full wave)



Output Current vs. Allowable case Temp



Cycle Surge Forward Current Rating (Non-Repetitive)



Transient Thermal Impedance (max)

