



DS017LS

Length 13"/330mm
Weight 3.5oz/99g

Static-Safe Deluxe SOLDAPULLT

Molded from conductive material
High efficiency and durable construction
Retractable shaft guide for portability and easy storage



SS350

Length 8.5"/216mm
Weight 1.5oz/43g

Static-Safe Standard Metric SOLDAPULLT Challenger

High quality, low cost
Designed for single-handed operation
Aluminum barrel for easy cleaning



PT409

Length 11.5"/292mm
Weight 2.0 oz/57g

Static-Safe SOLDAPULLT III Desoldering Tool

Light weight, petite barrel for smaller hands
Static-safe conductive material
Retractable shaft guide for portability and easy storage



SS750LS

Length 8.5"/216mm
Weight 1.5oz/43g

Static-Safe Standard Metric SOLDAPULLT Challenger

Molded from conductive material
High quality, low cost
Designed for single-handed operation

Replacement Tip

SOLDAPULLT

	DS017	US140	PT109	DS017LS	SS350	SS750LS	PT409
LS197 i.d. = .125"/3.2mm L = .536"/13.6mm				⊙			⊙
LS363 i.d. = .125"/3.2mm L = .536"/13.6mm					⊙		
LS751 i.d. = .100"/2.5mm L = .875"/22.2mm						⊙	
SRT12 i.d. = .125"/3.2mm L = .536"/13.6mm	⊙	⊙	⊙				

O-Ring

Use OL111 O-Ring Lube for lubrication

	DS017	US140	PT109	DS017LS	SS350	SS750LS	PT409
ODS31	⊙	⊙		⊙			
OSB32			⊙				⊙
OS130					⊙	⊙	