


DWP-125-1/8-0-STK Product Details



DWP-125-1/8-0-STK

TE Internal Number: 4429522003



[Active](#)

Heat Shrink Tubing

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = DWP-125
- Product Source = U.S.
- Flexible
- Medium Wall Style

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [DWP-125 Flame Retardant, Dual Wall Polyolefin, Heat-...](#) (PDF, English)

Catalog Pages/Data Sheets:

- [RAYCHEM TUBING CATALOG SECT1 PRODUCTS A-H](#) (PDF, English)
- [Flexible, Flame-Retardant, Adhesive-lined, Polyolefi...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Heat Shrinkable Tubing
- Material = Crosslinked Polyolefin
- Color = Black

Electrical Characteristics:

- Product Source = U.S.
- [Expanded ID, Min. \(mm \[in\]\)](#) = 3.20 [0.126]
- [Recovered ID, Max. \(mm \[in\]\)](#) = 1.00 [0.039]
- Product Use = Cable Breakouts, Connector-to-Cable Transitions, Wire Splices
- [Cut Length \(mm \[in\]\)](#) = 1220.00 [48.068]

Body Related Features:

- [Product Name](#) = DWP-125
- Pliancy = Flexible
- [Wall Style](#) = Medium
- [Wall Type](#) = Dual
- [Lining Type](#) = Adhesive
- [Shrink Ratio](#) = 3:1
- Fluid Resistance = Splash Protection
- Fluid Type = Brake Fluid, Hydraulic Fluid, Lubricating Oil, Water
- Resistant To = Fluids, Mechanical Damage
- Wall Thickness - Full Recovery (Nominal) (mm [in]) = 1.02 [0.040]

Housing Related Features:

- Material Systems = No
- Flammability Rating Type = Flame-Retardant

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- UL Rating = Recognized
- CSA Certified = Yes
- Approved Standards = CSA LR31929, UL E35586
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Full Recovery Temperature (°C) = 125
- Shrink Temperature, Min. (°C) = 80
- [Operating Temperature \(°C\)](#) = -40 - +110
- High Temperature Compatible = No

Operation/Application:

- Application = Insulation and Protection, Sealing
- Emission Free = No

Packaging Related Features:

- Packaging Method = Stick

Other:

- Brand = Raychem