



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE6154 thru NTE6165 Silicon Industrial Rectifier, 150 Amp, General Purpose

Description:

The NTE6154 through NTE6165 power rectifiers are stud mounted DO8 type packages. Because the silicon junction is carefully fitted within a glass-to-metal hermetically sealed case, reliable operation is assured even with extreme humidity and under other severe environmental conditions.

These power rectifiers are ideal for a broad range of commercial uses including power supplies, ultrasonic systems, inverters, welders, emergency generators, battery chargers, DC motors, and motor controls.

Features:

- Standard DO8 Type Package
- Available in Standard (Cathode to Case) and Reverse (Anode to Case) Polarity
- Recommended Stud Mounting Torque: 120in. lbs. Lubricated.

Electrical Ratings:

Peak Reverse Voltage, P_{RV}

NTE6154, NTE6155*	400V
NTE6156, NTE6157*	600V
NTE6158, NTE6159*	1000V
NTE6162, NTE6163*	1400V
NTE6164, NTE6165*	1600V

Maximum Forward Current Single Phase Half Wave ($T_C = +125^\circ C$), I_O 150A

Maximum Surge Current, Single Cycle, I_{FSM} 2100A

Maximum Forward Voltage Drop ($T_C = +25^\circ C$, $I_O = 200A$), V_F 1.1V

Maximum Reverse Current (FCA @ $+150^\circ C$), I_R 5mA

Maximum I^2t for Fusing (less than 8ms) 18200A²Sec

Reverse Power for Bulk Available 1.0Joules

Storage Temperature Range, T_{stg} -65° to $+200^\circ C$

Operating Temperature Range, T_{opr} -65° to $+190^\circ C$

Maximum Thermal Impedance (Junction-to-Case) $0.35^\circ C/W$ Max

