

Medium Power Differential Line Driver

The EL1507 is a very low power dual operational amplifier designed for central office and customer premise line driving for DMT ADSL solutions. This device features a high drive capability of 400mA while consuming only 7.5mA of supply current per amplifier from $\pm 12V$ supplies. This driver achieves a typical distortion of less than -75dBc, at 1MHz into a 50 Ω load. The EL1507 is available in the thermally-enhanced 16-pin SO package, as well as a 16-pin QFN package. Both are specified for operation over the full -40°C to +85°C temperature range.

The EL1507 has two control pins, C₀ and C₁. With the selection of C₀ and C₁, the device can be set into full-I_S power, $\frac{3}{4}$ -I_S power, $\frac{1}{2}$ -I_S power, and power down disable modes. The EL1507 maintains excellent distortion and load driving capabilities even in the lowest power settings.

Features

- Drives 360mA at 16V_{P-P} on $\pm 12V$ supplies
- 40V_{P-P} differential output drive into 100 Ω
- -75dBc typical driver output distortion driving 50 Ω at 1MHz and $\frac{1}{2}$ -I_S bias current
- Low quiescent current of 3.5mA per amplifier in $\frac{1}{2}$ -I_S mode
- Power down disable mode
- Pb-Free available (RoHS compliant)

Applications

- ADSL G.DMT and G.lite CO line driving
- G.SHDSL, HDSL2 line driver
- ADSL CPE line driving
- Video distribution amplifier
- Video twisted-pair line driver

Ordering Information

PART NUMBER	PACKAGE	TAPE & REEL	PKG. DWG. #
EL1507CS	16-Pin SO	-	MDP0027
EL1507CS-T7	16-Pin SO	7"	MDP0027
EL1507CS-T13	16-Pin SO	13"	MDP0027
EL1507CSZ (See Note)	16-Pin SO (Pb-free)	-	MDP0027
EL1507CSZ-T7 (See Note)	16-Pin SO (Pb-free)	7"	MDP0027
EL1507CSZ-T13 (See Note)	16-Pin SO (Pb-free)	13"	MDP0027
EL1507CL	16-Pin QFN	-	MDP0046
EL1507CL-T7	16-Pin QFN	7"	MDP0046
EL1507CL-T13	16-Pin QFN	13"	MDP0046

NOTE: Intersil Pb-free products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

Get FULL DATASHEET

EL1507

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.
Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com