



義隆電子股份有限公司

ELAN MICROELECTRONICS CORP.

EM78870

8-BIT MICRO-CONTROLLER

Version 1.4

ELAN MICROELECTRONICS CORP.
No. 12, Innovation 1st RD., Science-Based Industrial Park
Hsin Chu City, Taiwan, R.O.C.
TEL: (03) 5639977
FAX: (03)5782037(SL) 5780617 (SA2)



User Application Note

1. ROM, OTP, ICE

ROM	OTP	ICE
EM78870	EM78P870	EM78808 ICE

2. Main Function Difference

	EM78870	EM78P870
RAM	2.5K x 8	8K x 8



I. General Description

The EM78870 is an 8-bit RISC type microprocessor with low power, high speed CMOS technology. Integrated onto a single chip are on_chip watchdog (WDT), RAM, ROM, programmable real time clock /counter, internal interrupt, power down mode, LCD driver, build-in KEY TONE clock generation, Programming Tone generators, Serial Peripheral Interface(SPI), comparator and tri-state I/O. The EM78870 provides a single chip solution to design a message_display.

II. Feature

CPU

- Operating voltage range : 2.2V~5.5V(Normal mode), 2.0V~5.5V(Green mode)
- 32Kx 13 on chip Program ROM
- 2.5Kx 8 on chip data RAM
- 144 byte working register
- Up to 51 bi-directional tri-state I/O ports (32 shared with LCD Segment pins)
- IO with internal Pull high, wake-up and interrupt functions
- STACK: 32 level stack for subroutine nesting
- TCC: 8-bit real time clock/counter (TCC) with 8-bit prescaler
- COUNTER1: 8-bit counter with 8-bit prescaler can be an interrupt source
- COUNTER2: 8-bit counter with 8-bit prescaler can be an interrupt source
- Watch Dog : Programmable free running on chip watchdog timer
- CPU modes:

Mode	CPU status	Main clock	32.768kHz clock status
Sleep mode	Turn off	Turn off	Turn off
Idle mode	Turn off	Turn off	Turn on
Green mode	Turn on	Turn off	Turn on
Normal mode	Turn on	Turn on	Turn on

- 12 interrupt source : 8 external , 4 internal
- Key Scan : Port key scan function up to 16x4 keys
- Sub-Clock: 32.768kHz crystal
- Main-clock: 3.5826MHz multiplied by 0.25, 0.5, 1 or 3 generated by internal PLL
- Key tone output (shared with IO) : 4kHz, 2kHz, 1kHz
- Comparator: 3-channel comparators, internal (16 level) or external reference voltage (shared with IO)
- Serial Peripheral Interface (SPI) : Interrupt flag available for the read buffer full, Programmable baud rates of communication, Three-wire synchronous communication. (shared with IO)

Programmable Tone Generators

- Operation Voltage 2.2V~5.5V
- Programmable Tone1 and Tone2 generators
- Independent single tone generation for Tone1 and Tone2
- Mixed dual tone generation by Tone1 and Tone2 with 2dB difference

LCD (8x80, 9x80, 16x80, 24x72)

- Maximum common driver pins : 16/24
- Maximum segment driver pins : 80(SEG0..SEG79)/72(SEG8..SEG79)
- Shared COM16 ~ COM23 pins with SEG0 ~ SEG7 pins
- 1/4 bias for 8, 9 and 16 common mode and 1/5 bias for 24 common mode
- 1/8, 1/9, 1/16, 1/24 duty
- 16 Level LCD contrast control (software)
- Internal resistor circuit for LCD bias
- Internal voltage follower for better display

Package type

- 128-pin QFP or chip : EM78870AQ (POVD disable), EM78870BQ (POVD enable), EM78870H



III. Application

Cordless phones or any telephone product with large LCD needed

IV. Pin Configuration

			COM9	1	104	SEG18
			COM8	2	103	SEG19
			COM7	3	102	SEG20
			COM6	4	101	SEG21
			COM5	5	100	SEG22
			COM4	6	99	SEG23
			COM3	7	98	SEG24
			COM2	8	97	SEG25
			COM1	9	96	SEG26
			COM0	10	95	SEG27
			VC5	11	94	SEG28
			VC4	12	93	SEG29
			VC3	13	92	SEG30
			VC2	14	91	SEG31
			VC1	15	90	SEG32
			XIN	16	89	SEG33
			XOUT	17	88	SEG34
			VDD	18	87	SEG35
			AVDD	18	86	SEG36
			PLL	19	85	SEG37
			TONE	20	88	SEG38
			AVSS	21	83	SEG39
			GND	21	82	SEG40
			TEST	22	81	SEG41
			/RESET	23	80	SEG42
			P70/INT0	24	79	SEG43
			P71/INT0	25	78	SEG44
			P72/INT0	26	77	SEG45
			P73/INT0	27	76	SEG46
			P74/INT1	28	75	SEG47
			P75/INT1	29	74	SEG48/PB0
			P76/INT1	30	73	SEG49/PB1
			P77/INT2	31	72	SEG50/PB2
			P60/SCK	32	71	SEG51/PB3
			P61/SDO	33	70	SEG52/PB4
			P62/SDI	34	69	SEG53/PB5
			P63/CMP1	35	68	SEG54/PB6
			P64/CMP2	36	67	SEG55/PB7
			P65/CMP3	37	66	SEG56/PC0
			P66	38	65	SEG57/PC1
			P67/KTONE	39	64	SEG58/PC2
				40		SEG59/PC3
				41		
				42		
				43		
				44		
				45		
				46		
				47		
				48		
				49		
				50		
				51		
				52		
				53		
				54		
				55		
				56		
				57		
				58		
				59		
				60		
				61		
				62		
				63		
				64		
				65		
				66		
				67		
				68		
				69		
				70		
				71		
				72		
				73		
				74		
				75		
				76		
				77		
				78		
				79		
				80		
				81		
				82		
				83		
				84		
				85		
				86		
				87		
				88		
				89		
				90		
				91		
				92		
				93		
				94		
				95		
				96		
				97		
				98		
				99		
				100		
				101		
				102		
				103		
				104		
				105		
				106		
				107		
				108		
				109		
				110		
				111		
				112		
				113		
				114		
				115		
				116		
				117		
				118		
				119		
				120		
				121		
				122		
				123		
				124		
				125		
				126		
				127		
				128		

Fig.1 Pin assignment (128-pin QFP or chip)

* This specification are subject to be changed without notice.