

CHEMTRONICS®

Technical Data Sheet

TDS # 805

Label Adhesive Remover

PRODUCT DESCRIPTION

Label Adhesive Remover effectively removes adhesive residue left by tape, stickers, and labels. The foaming formula concentrates cleaning action where required without a drippy or runny mess, making it ideal for cleaning vertical surfaces. Label Adhesive Remover is safe for use on metals, glass, ceramics, and most plastic surfaces.

- Quickly removes sticker and adhesive residue
- No drip foaming formulation
- Clings to vertical surfaces
- Safe for use on metals, glass, ceramics, and most plastics
- Contains no CFCs or HCFCs

TYPICAL APPLICATIONS

Label Adhesive Remover effectively removes label and adhesive residue from:

- Computer Housings
- Printer Housings
- Film Cameras
- Video Cameras
- Mirror and Glass Surfaces
- File Cabinets
- Telephones

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

| | |
|-------------------------------------|---|
| Vapor Density (air = 1) | >1 |
| @ 100°F | |
| Solubility in Water | Miscible |
| Specific Gravity (water = 1) | 0.85 |
| Evaporative Rate (Ether = 1) | <1 |
| Appearance | Opaque, White Foam |
| Odor | Mild Orange |
| Flash Point TCC | 113°F |
| Shelflife | 5 years |
| RoHS/WEEE Status |  |

COMPATIBILITY

Label Adhesive Remover is generally compatible with most materials used in commercial/industrial systems, film/video cameras, VCRs, computer housings. As with any chemical product, component compatibility must be determined on a non-critical area prior to use. **Not** recommended for use on polystyrenes.

| <u>Material</u> | <u>Compatibility</u> |
|-----------------|----------------------|
| Aluminum | Excellent |
| Buna-N | Fair |
| CPVC | Excellent |
| Epoxy | Excellent |
| Neoprene | Fair |
| Noryl® | Excellent |
| Phenolic | Good |
| Polycarbonate | Good |
| Cross-Linked PE | Good |
| Polypropylene | Good |
| Polystyrene | Poor |
| PVC | Fair |
| Teflon™ | Excellent |
| Tygon™ | Good |
| Viton™ | Good |

ENVIRONMENTAL IMPACT DATA

| ENVIRONMENTAL IMPACT DATA | | | |
|---------------------------|------|-----|-------|
| CFC | 0.0% | VOC | 54.7% |
| HCFC | 0.0% | HFC | 0.0% |
| Cl. Solv. | 0.0% | ODP | 0.00 |

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is 0.0. It is the sum of the ODP of the substances that may contribute to the depletion of stratospheric ozone, based upon the weight of each substance in the product's formulation.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

MANUFACTURED BY:

ITW CHEMTRONICS
8125 COBB CENTER DRIVE
KENNESAW, GA 30152

1-770-424-4888

REV. E (06/06)

DISTRIBUTED BY:

USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

Use a label scraper to peel off top layer of label or tape. Shake can well prior to use. Hold can 2-3 inches from label to be removed. Spray foam, completely covering label. When foam collapses, peel off remaining label paper and wipe away residue.

AVAILABILITY

ES805

6 oz. Foaming Aerosol

TECHNICAL & APPLICATION

ASSISTANCE

Chemtronics® provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**