

MAXIM**2.5Ω, Dual, SPST,
CMOS Analog Switches****General Description**

The MAX4607/MAX4608/MAX4609 dual analog switches feature low on-resistance of 2.5Ω max. On-resistance is matched between switches to 0.5Ω max and is flat (0.5Ω max) over the specified signal range. Each switch can handle Rail-to-Rail® analog signals. The off-leakage current is only 2.5nA max at $+85^\circ\text{C}$. These analog switches are ideal in low-distortion applications and are the preferred solution over mechanical relays in automatic test equipment or applications where current switching is required. They have low power requirements, require less board space, and are more reliable than mechanical relays.

The MAX4607 has two normally closed (NC) switches, the MAX4608 has two normally open (NO) switches, and the MAX4609 has one NC and one NO switch.

These switches operate from a single supply of $+4.5\text{V}$ to $+36\text{V}$ or from dual supplies of $\pm 4.5\text{V}$ to $\pm 20\text{V}$. All digital inputs have $+0.8\text{V}$ and $+2.4\text{V}$ logic thresholds, ensuring TTL/CMOS-logic compatibility when using dual $\pm 15\text{V}$ or a single $+12\text{V}$ supply.

Applications

Reed Relay Replacement	PBX, PABX Systems
Test Equipment	Audio-Signal Routing
Communication Systems	Avionics


Features

- ◆ Low On-Resistance (2.5Ω max)
- ◆ Guaranteed RON Match Between Channels (0.5Ω max)
- ◆ Guaranteed RON Flatness over Specified Signal Range (0.5Ω max)
- ◆ Rail-to-Rail Signal Handling
- ◆ Guaranteed ESD Protection $> 2\text{kV}$ per Method 3015.7
- ◆ Single-Supply Operation: $+4.5\text{V}$ to $+36\text{V}$
Dual-Supply Operation: $\pm 4.5\text{V}$ to $\pm 20\text{V}$
- ◆ TTL/CMOS-Compatible Control Inputs

MAX4607/MAX4608/MAX4609**Ordering Information**

PART	TEMP. RANGE	PIN-PACKAGE
MAX4607CSE	0°C to $+70^\circ\text{C}$	16 Narrow SO
MAX4607CPE	0°C to $+70^\circ\text{C}$	16 Plastic DIP
MAX4607ESE	-40°C to $+85^\circ\text{C}$	16 Narrow SO
MAX4607EPE	-40°C to $+85^\circ\text{C}$	16 Plastic DIP

Ordering Information continued at end of data sheet.

Pin Configurations/Functional Diagrams/Truth Tables

Rail-to-Rail is a registered trademark of Nippon Motorola, Ltd.

Maxim Integrated Products 1

For free samples & the latest literature: <http://www.maxim-ic.com>, or phone 1-800-998-8800.

For small orders, phone 1-800-835-8760.



2.5Ω, Dual, SPST, CMOS Analog Switches

ABSOLUTE MAXIMUM RATINGS

V+ to GND	-0.3V to +44V
V- to GND	+0.3V to -44V
V+ to V-.....	-0.3V to +44V
V _L to GND	(GND - 0.3V) to (V+ + 0.3V)
All Other Pins to GND (Note 1)	(V- - 0.3V) to (V+ + 0.3V)
Continuous Current (COM __ , NO __ , NC __)	±100mA
Peak Current (COM __ , NO __ , NC __) (pulsed at 1ms, 10% duty cycle).....	±300mA

Continuous Power Dissipation (T _A = +70°C)	
Narrow SO (derate 8.70mW/°C above +70°C)	696mW
Plastic DIP (derate 10.53mW/°C above +70°C)	842mW
Operating Temperature Ranges	
MAX460_C_E	0°C to +70°C
MAX460_E_E	-40°C to +85°C
Storage Temperature Range	-65°C to +160°C
Lead Temperature (soldering, 10sec)	+300°C

Note 1: Signals on NC_{_}, NO_{_}, COM_{_}, or IN_{_}, exceeding V+ or V- will be clamped by internal diodes. Limit forward diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—Dual Supplies

(V₊ = +15V, V₋ = -15V, V_L = +5V, V_{IN_H} = +2.4V, V_{IN_L} = +0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Input Voltage Range (Note 3)	V _{COM_} , V _{NO_} , V _{NC_}			V-		V+	V
COM __ to NO __ , COM __ to NC __ On-Resistance	R _{ON}	I _{COM_} = 10mA, V _{NO_} or V _{NC_} = ±10V	T _A = +25°C	1.6	2.5		Ω
			T _A = T _{MIN} to T _{MAX}		3		
COM __ to NO __ , COM __ to NC __ On-Resistance Match Between Channels (Note 4)	ΔR _{ON}	I _{COM_} = 10mA, V _{NO_} or V _{NC_} = -5V, 0, 5V	T _A = +25°C	0.05	0.4		Ω
			T _A = T _{MIN} to T _{MAX}		0.5		
COM __ to NO __ , COM __ to NC __ On-Resistance Flatness (Note 5)	R _{FLAT(ON)}	I _{COM_} = 10mA, V _{NO_} or V _{NC_} = ±10V	T _A = +25°C	0.1	0.4		Ω
			T _A = T _{MIN} to T _{MAX}		0.5		
Off-Leakage Current (NO __ or NC __) (Note 6)	I _{NO_} , I _{NC_}	V _{COM_} = ±10V, V _{NO_} or V _{NC_} = ±10V	T _A = +25°C	-0.5	0.01	0.5	nA
			T _A = T _{MIN} to T _{MAX}	-2.5		2.5	
COM Off-Leakage Current (Note 6)	I _{COM_(OFF)}	V _{COM_} = ±10V, V _{NO_} or V _{NC_} = ±10V	T _A = +25°C	-0.5	0.01	0.5	nA
			T _A = T _{MIN} to T _{MAX}	-2.5		2.5	
COM On-Leakage Current (Note 6)	I _{COM_(ON)}	V _{COM_} = ±10V, V _{NO_} or V _{NC_} = ±10V, or floating	T _A = +25°C	-1	0.02	1	nA
			T _A = T _{MIN} to T _{MAX}	-10		10	
LOGIC INPUT							
Input Current with Input Voltage High	I _{IN_H}	IN __ = 2.4V, all others = 0.8V		-0.500	0.001	0.500	μA
Input Current with Input Voltage Low	I _{IN_L}	IN __ = 0.8V, all others = 2.4V		-0.500	0.001	0.500	μA
Logic Input High Voltage	V _{IN_H}			2.4	1.7		V
Logic Input Low Voltage	V _{IN_L}				1.7	0.8	V

2.5Ω, Dual, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Dual Supplies (continued)

($V_+ = +15V$, $V_- = -15V$, $V_L = +5V$, $V_{IN_H} = +2.4V$, $V_{IN_L} = +0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS	
POWER SUPPLY								
Power-Supply Range				± 4.5		± 20.0	V	
Positive Supply Current	I_+	$V_{IN} = 0$ or $5V$	$T_A = +25^\circ C$	-0.5	0.001	0.5	μA	
			$T_A = T_{MIN}$ to T_{MAX}	5		5		
Negative Supply Current	I_-	$V_{IN} = 0$ or $5V$	$T_A = +25^\circ C$	-0.5	0.001	0.5	μA	
			$T_A = T_{MIN}$ to T_{MAX}	5		5		
Logic Supply Current	I_L	$V_{IN} = 0$ or $5V$	$T_A = +25^\circ C$	-0.5	0.001	0.5	μA	
			$T_A = T_{MIN}$ to T_{MAX}	5		5		
Ground Current	I_{GND}	$V_{IN} = 0$ or $5V$	$T_A = +25^\circ C$	-0.5	0.001	0.5	μA	
			$T_A = T_{MIN}$ to T_{MAX}	5		5		
SWITCH DYNAMIC CHARACTERISTICS								
Turn-On Time	t_{ON}	$V_{COM_} = \pm 10V$, Figure 2, $T_A = +25^\circ C$		110		ns		
Turn-Off Time	t_{OFF}	$V_{COM_} = \pm 10V$, Figure 2, $T_A = +25^\circ C$		150		ns		
Charge Injection	Q	$C_L = 1.0nF$, $V_{GEN} = 0$, $R_{GEN} = 0$, Figure 3, $T_A = +25^\circ C$		450		pC		
Off-Isolation (Note 7)	V_{ISO}	$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, Figure 4, $T_A = +25^\circ C$		-60		dB		
Crosstalk (Note 8)	V_{CT}	$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, Figure 5, $T_A = +25^\circ C$		-66		dB		
NC_ or NO_ Capacitance	C_{OFF}	$f = 1MHz$, Figure 6, $T_A = +25^\circ C$		65		pF		
COM_ Off-Capacitance	C_{COM}	$f = 1MHz$, Figure 6, $T_A = +25^\circ C$		65		pF		
On-Capacitance	C_{COM}	$f = 1MHz$, Figure 7, $T_A = +25^\circ C$		290		pF		

2.5Ω, Dual, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single Supply

($V_+ = +12V$, $V_- = 0$, $V_L = +5V$, $V_{IN_H} = +2.4V$, $V_{IN_L} = +0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Input Voltage Range (Note 3)	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$			GND		V_+	V
COM_ to NO_, COM_ to NC_ On-Resistance	R_{ON}	$I_{COM_} = 10mA$, $V_{NO_}$ or $V_{NC_} = 10V$	$T_A = +25^\circ C$	3	6		Ω
			$T_A = T_{MIN}$ to T_{MAX}		7		
COM_ to NO_, COM_ to NC_ On-Resistance Match Between Channels (Note 4)	ΔR_{ON}	$I_{COM_} = 10mA$, $V_{NO_}$ or $V_{NC_} = 10V$	$T_A = +25^\circ C$	0.05	0.4		Ω
			$T_A = T_{MIN}$ to T_{MAX}		0.5		
COM_ to NO_, COM_ to NC_ On-Resistance Flatness (Note 5)	$R_{FLAT(ON)}$	$I_{COM_} = 10mA$, $V_{NO_}$ or $V_{NC_} = 3V$, 6V, 0V	$T_A = +25^\circ C$	0.05	0.5		Ω
			$T_A = T_{MIN}$ to T_{MAX}		0.5		
Off-Leakage Current (NO_ or NC_) (Notes 6, 9)	$I_{NO_}$ $I_{NC_}$	$V_{COM_} = 1V$, 10V, $V_{NO_}$ or $V_{NC_} = 1V$, 10V	$T_A = +25^\circ C$	-0.5	0.01	0.5	nA
			$T_A = T_{MIN}$ to T_{MAX}	-2.5		2.5	
COM Off-Leakage Current (Notes 6, 9)	I_{COM_OFF}	$V_{COM_} = 10V$, 1V $V_{NO_}$ or $V_{NC_} = 1V$, 10V	$T_A = +25^\circ C$	-0.5	0.01	0.5	nA
			$T_A = T_{MIN}$ to T_{MAX}	-2.5		2.5	
COM On-Leakage Current (Notes 6, 9)	I_{COM_ON}	$V_{COM_} = 1V$, 10V, $V_{NO_}$ or $V_{NC_} = 1V$, 10V, or floating	$T_A = +25^\circ C$	-1	0.01	1	nA
			$T_A = T_{MIN}$ to T_{MAX}	-10		10	
LOGIC INPUT							
Input Current with Input Voltage High	I_{IN_H}	$IN_ = 2.4V$, all others = 0.8V		-0.500	0.001	0.500	μA
Input Current with Input Voltage Low	I_{IN_L}	$IN_ = 0.8V$, all others = 2.4V		-0.500	0.001	0.500	μA
Logic Input High Voltage	V_{IN_H}			2.4	1.7		V
Logic Input Low Voltage	V_{IN_L}				1.7	0.8	V

2.5Ω, Dual, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single Supply (continued)

(V₊ = +12V, V₋ = 0, V_L = +5V, V_{IN_H} = +2.4V, V_{IN_L} = +0.8V, TA = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at TA = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
POWER SUPPLY						
Power-Supply Range			+4.5		+36.0	V
Positive Supply Current	I ₊	V _{IN} = 0 or 5V	T _A = +25°C	-0.5	0.001	0.5
			T _A = T _{MIN} to T _{MAX}	5		5
Logic Supply Current	I _L	V _{IN} = 0 or 5V	T _A = +25°C	-0.5	0.001	0.5
			T _A = T _{MIN} to T _{MAX}	5		5
Ground Current	I _{GND}	V _{IN} = 0 or 5V	T _A = +25°C	-0.5	0.001	0.5
			T _A = T _{MIN} to T _{MAX}	5		5
SWITCH DYNAMIC CHARACTERISTICS						
Turn-On Time	t _{ON}	V _{COM} = 10V, Figure 2, T _A = +25°C	110			ns
Turn-Off Time	t _{OFF}	V _{COM} = 10V, Figure 2, T _A = +25°C	130			ns
Charge Injection	Q	C _L = 1.0nF, V _{GEN} = 0, R _{GEN} = 0, Figure 3, T _A = +25°C	50			pC
Crosstalk (Note 8)	V _{CT}	R _L = 50Ω, C _L = 5pF, f = 1MHz, Figure 5, T _A = +25°C	66			dB
NC or NO Capacitance	C _(OFF)	f = 1MHz, Figure 6, T _A = +25°C	105			pF
COM Off-Capacitance	C _(COM)	f = 1MHz, Figure 6, T _A = +25°C	105			pF
On-Capacitance	C _(COM)	f = 1MHz, Figure 7, T _A = +25°C	185			pF

Note 2: The algebraic convention, where the most negative value is a minimum and the most positive value a maximum, is used in this data sheet.

Note 3: Guaranteed by design.

Note 4: $\Delta R_{ON} = R_{ON(MAX)} - R_{ON(MIN)}$

Note 5: Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal range.

Note 6: Leakage parameters are 100% tested at maximum-rated hot temperature and guaranteed by correlation at +25°C.

Note 7: Off-isolation = $20\log_{10} [V_{COM} / (V_{NC} \text{ or } V_{NO})]$, V_{COM} = output, V_{NC} or V_{NO} = input to off switch.










Note 8: Between any two switches.

Note 9: Leakage testing at single supply is guaranteed by testing with dual supplies.

2.5Ω, Dual, SPST, CMOS Analog Switches

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



Typical Operating Characteristics



2.5Ω, Dual, SPST, CMOS Analog Switches

Typical Operating Characteristics (continued)

(TA = +25°C, unless otherwise noted.)



Pin Description

PIN			NAME	FUNCTION
MAX4607	MAX4608	MAX4609		
2, 7	2, 7	2, 7	IN2, IN2	Logic-Control Digital Inputs
14, 11	14, 11	14, 11	COM1, COM2	Analog Switch, Common Terminals
16, 9	—	—	NC1, NC2	Analog Switch, Normally Closed Terminals
—	16, 9	—	NO1, NO2	Analog Switch, Normally Open Terminals
—	—	9	NC1	Analog Switch, Normally Closed Terminal
—	—	16	NO1	Analog Switch, Normally Open Terminal
4	4	4	V-	Negative Analog Supply-Voltage Input. Connect to DGND for single-supply operation.
5	5	5	GND	Ground
1, 3, 6, 8, 10, 15	1, 3, 6, 8, 10, 15	1, 3, 6, 8, 10, 15	N.C.	No Connection. Not internally connected. Connect to GND as low impedance to improve on/off-isolation.
12	12	12	V _L	Logic-Supply Input
13	13	13	V ₊	Positive Analog-Supply Input

2.5Ω, Dual, SPST, CMOS Analog Switches

Applications Information

Overvoltage Protection

Proper power-supply sequencing is recommended for all CMOS devices. Do not exceed the absolute maximum ratings, because stresses beyond the listed ratings can cause permanent damage to the devices. Always sequence V₊ on first, then V₋, followed by the logic inputs, NO, or COM. If power-supply sequencing is not possible, add two small signal diodes (D1, D2) in series with supply pins for overvoltage protection (Figure 1). Adding diodes reduces the analog signal range to one diode drop below V₊ and one diode drop above V₋, but does not affect the devices' low switch resistance and low leakage characteristics. Device operation is unchanged, and the difference between V₊ and V₋ should not exceed 44V. These protection diodes are not recommended when using a single supply.

Off-Isolation at High Frequencies

With the N.C. pins connected to GND, the high-frequency on-response of these parts extends from DC to above 100MHz with a typical loss of -2dB. When the switch is turned off, however, it behaves like a capacitor, and off-isolation decreases with increasing frequency. (Above 300MHz, the switch actually passes more signal turned off than turned on.) This effect is more pronounced with higher source and load impedances.

Above 5MHz, circuit-board layout becomes critical, and it becomes difficult to characterize the response of the switch independent of the circuit. The graphs shown in the *Typical Operating Characteristics* were taken using a 50Ω source and load connected with BNC connectors to a circuit board deemed "average;" that is, designed with isolation in mind, but not using strip-line or other special RF circuit techniques. For critical applications above 5MHz, use the MAX440, MAX441, and MAX442, which are fully characterized up to 160MHz.




Figure 1. Overvoltage Protection Using External Blocking Diodes

Test Circuits/Timing Diagrams




Figure 2. Switching-Time Test Circuit

2.5Ω, Dual, SPST, CMOS Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 3. Charge-Injection Test Circuit




Figure 4. Off-Isolation Test Circuit




Figure 5. Crosstalk Test Circuit

2.5Ω, Dual, SPST, CMOS Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 6. Switch Off-Capacitance Test Circuit




Figure 7. Switch On-Capacitance Test Circuit

Ordering Information (continued)

PART	TEMP. RANGE	PIN-PACKAGE
MAX4608CSE	0°C to +70°C	16 Narrow SO
MAX4608CPE	0°C to +70°C	16 Plastic DIP
MAX4608ESE	-40°C to +85°C	16 Narrow SO
MAX4608EPE	-40°C to +85°C	16 Plastic DIP
MAX4609CSE	0°C to +70°C	16 Narrow SO
MAX4609CPE	0°C to +70°C	16 Plastic DIP
MAX4609ESE	-40°C to +85°C	16 Narrow SO
MAX4609EPE	-40°C to +85°C	16 Plastic DIP


Chip Information

TRANSISTOR COUNT: 100

2.5Ω, Dual, SPST, CMOS Analog Switches

Package Information

MAX4607/MAX4608/MAX4609



INCHES		MILLIMETERS		
MIN	MAX	MIN	MAX	
A	0.053	0.069	1.35	1.75
A1	0.004	0.010	0.10	0.25
B	0.014	0.019	0.35	0.49
C	0.007	0.010	0.19	0.25
e	0.050		1.27	
E	0.150	0.157	3.80	4.00
H	0.228	0.244	5.80	6.20
h	0.010	0.020	0.25	0.50
L	0.016	0.050	0.40	1.27

INCHES		MILLIMETERS		N	MS012
MIN	MAX	MIN	MAX		
D	0.189	0.197	4.80	5.00	8 A
D	0.337	0.344	8.55	8.75	14 B
D	0.386	0.394	9.80	10.00	16 C

NOTES:

1. D&E DO NOT INCLUDE MOLD FLASH
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15mm (.006")
3. LEADS TO BE COPLANAR WITHIN .102mm (.004")
4. CONTROLLING DIMENSION: MILLIMETER
5. MEETS JEDEC MS012-XX AS SHOWN IN ABOVE TABLE
6. N = NUMBER OF PINS



129 SAN GABRIEL DR. SANTA CLARA, CA 95051 FAX (408) 737-7794
PROPRIETARY INFORMATION

PACKAGE FAMILY OUTLINE: SOIC .150"

TITLE


1/1

21-0041 A

DOCUMENT CONTROL NUMBER REV

2.5Ω, Dual, SPST, CMOS Analog Switches

Package Information (continued)



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

12 Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600