



E-Series 2-Way 0° Power Divider

5 - 1000 MHz

ESSM-2-2-75

V3.00


Features

- 2 Way
- 0°
- Surface Mount

Specifications @ 25°C

Frequency Range	5 - 1000 MHz	
Insertion Loss	Typical	Maximum
	5 - 50 MHz	0.6 dB / 1.2 dB
	50 - 500 MHz	0.5 dB / 0.9 dB
500 - 1000 MHz	0.8 dB / 1.5 dB	
Isolation	Typical	Minimum
	5 - 50 MHz	33 dB / 20 dB
	50 - 500 MHz	30 dB / 17 dB
500 - 1000 MHz	18 dB / 11 dB	
Amplitude Unbalance	Maximum	
	5 - 50 MHz	0.6 dB
	50 - 500 MHz	0.5 dB
500 - 1000 MHz	0.5 dB	
Phase Unbalance	Maximum	
	5 - 50 MHz	5°
	50 - 500 MHz	3°
500 - 1000 MHz	6°	
Return Loss	Typical	Minimum
	I/P	30 dB / 14 dB
	O/P	20 dB / 11 dB

SM-55



Pin Configuration

Function	Pin No.
Not Connected	5,2
Ground	1
Input	6
Port 1	4
Port 2	3

Operating Characteristics

Impedance	75 Ohms Nominal
-----------	-----------------

Ordering Information

Part No.	ESSM-2-2-75	Packaging	Tube
----------	-------------	-----------	------

Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C