#### 查询MAX1682EUK-T供应商

19-1305; Rev 1; 8/98

### 捷多邦,专业PCB打样工厂,24小时加急出货

# Switched-Capacitor Voltage Doublers

### **General Description**

Applications

The ultra-small MAX1682/MAX1683 monolithic, CMOS charge-pump voltage doublers accept input voltages ranging from +2.0V to +5.5V. Their high voltage-conversion efficiency (over 98%) and low operating current (110µA for MAX1682) make these devices ideal for both battery-powered and board-level voltage-doubler applications.

Oscillator control circuitry and four power MOSFET switches are included on-chip. The MAX1682 operates at 12kHz and the MAX1683 operates at 35kHz. A typical application includes generating a 6V supply to power an LCD display in a hand-held PDA. Both parts are available in a 5-pin SOT23 package and can deliver 30mA with a typical voltage drop of 600mV.

\_Features

- 5-Pin SOT23 Package
- + +2.0V to +5.5V Input Voltage Range
- 98% Voltage-Conversion Efficiency
- 110µA Quiescent Current (MAX1682)
- Requires Only Two Capacitors
- Up to 45mA Output Current

## Small LCD Panels Cell Phones Handy-Terminals PDAs



### Typical Operating Circuit

ent

### **Ordering Information**

PART	TEMP. RANGE	PIN- PACKAGE	SOT TOP MARK	
<b>MAX1682</b> C/D	$0^{\circ}C$ to $+70^{\circ}C$	Dice*	-	
MAX1682EUK-T	-40°C to +85°C	5 SOT23-5	ACLL	
MAX1683C/D	0°C to +70°C	Dice*	C.CO.M	
MAX1683EUK-T	-40°C to +85°C	5 SOT23-5	ACCM	

**Note:** These parts are available in tape-and-reel only. Minimum order quantity is 2500 pieces. \*Dice are tested at  $T_A = +25^{\circ}C$ .

Pin Configuration



Maxim Integrated Products 1

For free samples & the latest literature: http://www.maxim-ic.com, or phone 1-800-998-8800. For small orders, phone 408-737-7600 ext, 3468.

### **ABSOLUTE MAXIMUM RATINGS**

IN to GND	+6V to -0.3V
OUT to GND	+12V, VIN - 0.3V
OUT Output Current	50mA
Output Short-Circuit Duration	1sec (Note 1)
Continuous Power Dissipation ( $T_A = +70^{\circ}C$ )	
SOT23-5 (derate 7.1mW/°C above +70°C)	571mW

Operating Temperature Range	
MAX1682EUK/MAX1683EUK	40°C to +85°C
Junction Temperature	+150°C
Storage Temperature Range	65°C to +160°C
Lead Temperature (soldering, 10sec)	+300°C

Note 1: Avoid shorting OUT to GND, as it may damage the device. For temperatures above +85°C, shorting OUT to GND even instantaneously will damage the device.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### **ELECTRICAL CHARACTERISTICS**

 $(V_{IN} = +5.0V, capacitor values from Table 2, T_A = 0^{\circ}C to +85^{\circ}C, unless otherwise noted. Typical values are at T_A = +25^{\circ}C.)$ 

PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
No Load Supply Current		MAX1682		110	145	
	IA = +25 C	MAX1683		230	310	- μΑ
Supply Voltage Dange	$R_{LOAD} = 10k\Omega$	$T_A = +25^{\circ}C$	2.0	1.7	5.5	V
Supply vollage Range		$T_A = 0^{\circ}C \text{ to } +85^{\circ}C$	2.1	1.8	5.5	
Minimum Operating Voltage	(Note 2)			1		V
Oscillator Fraguancy	T <sub>A</sub> = +25°C	MAX1682	8.4	12	15.6	- kHz
Oscillator Frequency		MAX1683	24.5	35	45.5	
Output Decistance	Iout = 5mA	$T_A = +25^{\circ}C$		20	50	
		$T_A = 0^{\circ}C \text{ to } +85^{\circ}C$			65	52
Voltage Conversion Efficiency	$I_{OUT} = 0mA, T_A = +25^{\circ}C$		98	99.9		%

Note 2: Once started, the MAX1682/MAX1683 typically operate down to 1V.

### **ELECTRICAL CHARACTERISTICS**

( $V_{IN} = +5.0V$ , capacitor values from Table 2,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ , unless otherwise noted.) (Note 3)

PARAMETER	CONDITIONS	MIN	ТҮР	MAX	UNITS	
No Load Supply Current	MAX1682			160		
	MAX1683			350	μΑ	
Supply-Voltage Range	$R_{LOAD} = 10k\Omega$	2.3		5.5	V	
Oscillator Fraguancy	MAX1682	6.6		18.6	- kHz	
Oscillator frequency	MAX1683	17.5		57.8		
Output Resistance	I <sub>OUT</sub> = 5mA			65	Ω	
Voltage Conversion Efficiency	I <sub>OUT</sub> = 0mA	97			%	

Note 3: Specifications at -40°C to +85°C are guaranteed by design.



# Typical Operating Characteristics

(Typical Operating Circuit,  $V_{IN} = +5V$ , C1 = C2 = 10 $\mu$ F for the MAX1682 and 3.3 $\mu$ F for the MAX1683, T<sub>A</sub> = +25°C, unless otherwise

3



M/X/W

#### Pin Description

PIN	NAME	FUNCTION	
1	GND	Ground	
2	OUT	Doubled Output Voltage. Connect C2 between OUT and GND.	
3	C1-	Negative Terminal of the Flying Capacitor	
4	IN	Input Supply	
5	C1+	Positive Terminal of the Flying Capacitor	

#### Detailed Description

The MAX1682/MAX1683 capacitive charge pumps double the voltage applied to their input. Figure 1 shows a simplified functional diagram of an ideal voltage doubler. During the first half-cycle, switches S1 and S2 close, and capacitor C1 charges to V<sub>IN</sub>. During the second half cycle, S1 and S2 open, S3 and S4 close, and C1 is level shifted upward by V<sub>IN</sub> volts. This connects C1 to the reservoir capacitor C2, allowing energy to be delivered to the output as necessary. The actual voltage is slightly lower than 2 x V<sub>IN</sub>, since switches S1–S4 have resistance and the load drains charge from C2.

#### **Charge-Pump Output**

The MAX1682/MAX1683 have a finite output resistance of about 20 $\Omega$  (Table 2). As the load current increases, the devices' output voltage (V<sub>OUT</sub>) droops. The droop equals the current drawn from V<sub>OUT</sub> times the circuit's output impedance (R<sub>S</sub>), as follows:

VDROOP = IOUT X RS VOUT = 2 X VIN - VDROOP



Figure 1. Simplified Functional Diagram of Ideal Voltage Doubler

#### **Efficiency Considerations**

The power efficiency of a switched-capacitor voltage converter is affected by three factors: the internal losses in the converter IC, the resistive losses of the capacitors, and the conversion losses during charge transfer between the capacitors. The total power loss is:

$$\Sigma P_{LOSS} = P_{INTERNAL LOSSES}$$

- + PPUMP CAPACITOR LOSSES
- + PCONVERSION LOSSES

The internal losses are associated with the IC's internal functions, such as driving the switches, oscillator, etc. These losses are affected by operating conditions such as input voltage, temperature, and frequency.

The next two losses are associated with the voltage converter circuit's output resistance. Switch losses occur because of the on-resistance of the MOSFET switches in the IC. Charge-pump capacitor losses occur because of their ESR. The relationship between these losses and the output resistance is as follows:

#### PPUMP CAPACITOR LOSSES + PSWITCH LOSSES =

$$R_{OUT} \cong \frac{1}{(f_{OSC}) \times C1} + 2R_{SWITCHES} + 4ESR_{C1} + ESR_{C2}$$

where fOSC is the oscillator frequency. The first term is the effective resistance from an ideal switched-capacitor circuit (Figures 2a and 2b).



Figure 2a. Switched-Capacitor Model



Figure 2b. Equivalent Circuit

Conversion losses occur during the charge transfer between C1 and C2 when there is a voltage difference between them. The power loss is:

$$P_{\text{CONVERSION LOSS}} = \left[ \frac{1}{2}C1 \left( 4V_{\text{IN}}^{2} - V_{\text{OUT}}^{2} \right) + \frac{1}{2}C2 \left( 2V_{\text{OUT}}V_{\text{RIPPLE}} - V^{2}_{\text{RIPPLE}} \right) \right] x f_{\text{OSC}}$$

where VRIPPLE is the peak-to-peak output voltage ripple determined by the output capacitor and load current (see *Output Capacitor* section). Choose capacitor values that decrease the output resistance (see *Flying Capacitor* section).

### Applications Information

#### Flying Capacitor (C1)

To maintain the lowest output resistance, use capacitors with low ESR. Suitable capacitor manufacturers are listed in Table 1. The charge-pump output resistance is a function of C1 and C2's ESR and the internal switch resistance, as shown in the equation for R<sub>OUT</sub> in the *Efficiency Considerations* section.

Minimizing the charge-pump capacitor's ESR minimizes the total resistance. Suggested values are listed in Tables 2 and 3. Using a larger flying capacitor reduces the output impedance and improves efficiency (see the *Efficiency Considerations* section). Above a certain point, increasing C1's capacitance has a negligible effect because the output resistance becomes dominated by the internal switch resistance and capacitor ESR (see the Output Resistance vs. Capacitance graph in the *Typical Operating Characteristics*). Table 2 lists the most desirable capacitor values—those that produce a low output resistance. But when space is a constraint, it may be necessary to sacrifice low output resistance for the sake of small capacitor size. Table 3 demonstrates how the capacitor affects output resistance.

#### **Output Capacitor (C2)**

Increasing the output capacitance reduces the output ripple voltage. Decreasing its ESR reduces both output resistance and ripple. Smaller capacitance values can be used with light loads. Use the following equation to calculate the peak-to-peak ripple:

VRIPPLE = IOUT / (fOSC x C2) + 2 x IOUT x ESRC2

#### Input Bypass Capacitor

Bypass the incoming supply to reduce its AC impedance and the impact of the MAX1682/MAX1683's switching noise. When loaded, the circuit draws a continuous current of 2 x IOUT. A 0.1µF bypass capacitor is sufficient.

PRODUCTION METHOD	MANUFACTURER	SERIES	PHONE	FAX
	AVX	TPS	803-946-0690	803-448-2170
Surface-Mount Tantalum	Matsuo	267	714-969-2491	714-960-6492
	Sprague	593D, 595D	603-224-1961	603-224-1430
Surface Mount Coramic	AVX	X7R	803-946-0590	803-626-3123
	Matsuo	X7R	714-969-2491	714-960-6492

#### **Table 1. Recommended Capacitor Manufacturers**

# Table 2. Suggested Capacitor Values forLow Output Resistance

PART	FREQUENCY (kHz)	CAPACITOR VALUE (µF)	TYPICAL Rout (Ω)	
MAX1682	12	10	20	
MAX1683	35	3.3	20	

# Table 3. Suggested Capacitor Values forMinimum Size

PART	FREQUENCY (kHz)	CAPACITOR VALUE (µF)	TYPICAL Rout (Ω)
MAX1682	12	3.3	35
MAX1683	35	1	35

#### **Cascading Devices**

Devices can be cascaded to produce an even larger voltage (Figure 3). The unloaded output voltage is nominally (n + 1) x V<sub>IN</sub>, where n is the number of voltage doublers used. This voltage is reduced by the output resistance of the first device multiplied by the quiescent current of the second. The output resistance increases when devices are cascaded. Using a two-stage doubler as an example, output resistance can be approximated as ROUT = 2 x ROUT1 + ROUT2, where ROUT1 is the output resistance of the first stage and ROUT2 is the output resistance of the second stage. A typical value for a two-stage voltage doubler is  $60\Omega$  (with C1 at 10µF for MAX1682 and  $3.3\mu$ F for MAX1683). For n stages with the same C1 value, ROUT =  $(2^n - 1) \times ROUT1$ .

#### **Paralleling Devices**

Paralleling multiple MAX1682 or MAX1683s reduces the output resistance. Each device requires its own pump capacitor (C1), but the reservoir capacitor (C2) serves all devices (Figure 4). Increase C2's value by a factor of n, where n is the number of parallel devices. Figure 4 shows the equation for calculating output resistance.

#### Layout and Grounding

Good layout is important, primarily for good noise performance. To ensure good layout, mount all components as close together as possible, keep traces short to minimize parasitic inductance and capacitance, and use a ground plane.



Figure 3. Cascading Devices



Figure 4. Paralleling Devices

Chip Information

TRANSISTOR COUNT: 97 SUBSTRATE CONNECTED TO OUT

### Package Information



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Printed USA

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600

© 1998 Maxim Integrated Products

8

is a registered trademark of Maxim Integrated Products.