

19-1092 Rev 0; 6/96

EVALUATION KIT  
AVAILABLE

### General Description

The MAX4135/MAX4136 are 1-input/6-output voltage-feedback amplifiers that combine high speed with fast switching for video distribution applications. The MAX4135 is internally set for a closed-loop gain of 2V/V, while the MAX4136 can be externally set for gains of 2V/V or greater.

The MAX4135 achieves a -3dB bandwidth of 185MHz, with 0.1dB gain flatness to 40MHz. The MAX4136's -3dB bandwidth is 140MHz. Both devices deliver a 1000V/μs slew rate, as well as exceptional full-power bandwidths of 185MHz and 140MHz, respectively.

A 25ns channel switching time enables rapid multiplexing for picture-in-picture applications, yet maintains a high off-isolation of 75dB and all-hostile crosstalk of -50dB (f = 30MHz). The MAX4135/MAX4136's on-board logic selects any combination of the six signal outputs. Each output is capable of swinging  $\pm 2V$  and delivering 65mA.

For applications that require a 1-input/4-output distribution amplifier, see the MAX4137/MAX4138 data sheet.

### Selector Guide

PART	NO. OF OUTPUTS	GAIN (V/V)	-3dB BANDWIDTH (MHz)
MAX4135	6	Fixed 2	185
MAX4136	6	$\geq 2$	140
MAX4137	4	Fixed 2	185
MAX4138	4	$\geq 2$	140

### Applications

Video Switching and Distribution  
High-Resolution RGB CRT Monitors  
High-Speed Analog Bus Drivers  
RF Signal Processing  
Composite Video Preamplifiers

**MAXIM**

## 1-Input/6-Output Video Distribution Amplifiers

### Features


- ♦ Fixed Gain of 2V/V (MAX4135)  
External Gain Set (MAX4136)
- ♦ High Speed:  
185MHz -3dB Bandwidth (MAX4135)  
140MHz -3dB Bandwidth (MAX4136)  
1000V/μs Slew Rate
- ♦ High Full-Power Bandwidths (V<sub>OUT</sub> = 2Vp-p):  
185MHz (MAX4135)  
140MHz (MAX4136)
- ♦ 0.1dB Gain Flatness to 40MHz
- ♦ Low Differential Gain/Phase Error: 0.10%/0.02°
- ♦ High-Impedance Output Disable

**MAX4135/MAX4136**

### Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
MAX4135EWG	-40°C to +85°C	24 Wide SO
MAX4136EWG	-40°C to +85°C	24 Wide SO

### Pin Configurations



# 1-Input/6-Output Video Distribution Amplifiers

## ABSOLUTE MAXIMUM RATINGS

Power-Supply Voltage ( $V_{CC}$  to  $V_{EE}$ ) ..... 12V  
 Voltage on Any Input Pin to GND ..... ( $V_{EE}$  + 0.3V) to ( $V_{EE}$  - 0.3V)  
 Short-Circuit Duration to GND ..... Continuous  
 Continuous Power Dissipation ( $TA = +70^\circ C$ ) ..... Wide SO (derate 19.3mW/ $^\circ C$  above  $+70^\circ C$ ) ..... 1.54W

Operating Temperature Range  
 MAX4135EWG/MAX4136EWG .....  $-40^\circ C$  to  $+85^\circ C$   
 Storage Temperature Range .....  $-65^\circ C$  to  $+160^\circ C$   
 Lead Temperature (soldering, 10sec) .....  $+300^\circ C$

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS

( $V_{CC} = +5V$ ,  $V_{EE} = -5V$ ,  $TA = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $TA = +25^\circ C$ .)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Input Offset Voltage	$V_{OS}$	$V_{OUT} = 0V$ , $R_L = \infty$	1	8		mV
Input Offset Voltage Match Between Channels		$V_{OUT} = 0V$ , $R_L = \infty$	1	6		mV
Input Offset Voltage Drift	$TCV_{OS}$	$V_{OUT} = 0V$ , $R_L = 150\Omega$	30			$\mu V/^\circ C$
Input Bias Current	$I_B$	$V_{OUT} = 0V$ , $R_L = 150\Omega$ , $V_{CM} = 0V$	4.5	10		$\mu A$
Common-Mode Input Resistance	$R_{IN(CM)}$	MAX4136, either input	5			$M\Omega$
Common-Mode Input Capacitance	$C_{IN(CM)}$	MAX4136, either input	2			pF
Input Voltage Noise	$e_n$	$f = 1MHz$ $f = 1MHz$ to $100MHz$	7			$nV/\sqrt{Hz}$
Input Current Noise	$i_n$	$f = 1MHz$ $f = 1MHz$ to $100MHz$	2.4			$\mu A/\sqrt{Hz}$
Input Capacitance	$C_{IN}$		2			pF
Common-Mode Input Voltage Range	$V_{CM}$	MAX4136		$\pm 2.5$		V
Common-Mode Rejection Ratio	$CMRR$	MAX4136, $V_{CM} = \pm 2.5V$	60			dB
Power-Supply Rejection Ratio	$PSRR$	$V_S = \pm 4.75V$ to $\pm 5.25V$	55	65		dB
Quiescent Supply Current	$I_{SY}$	$V_{IN} = 0V$ All channels off All channels on	45	55		mA
Output Voltage Swing	$V_{OUT}$	$R_L = 150\Omega$ Positive Negative	+2.2	+2.6		V
Output Current Drive	$I_{OUT}$	$R_L = 30\Omega$	45	65		mA
SEL High Threshold	$V_{IH}$				2.0	V
SEL Low Threshold	$V_{IL}$			0.8		V
SEL Input Current	$I_{SEL}$		1	5		$\mu A$

# 1-Input/6-Output Video Distribution Amplifiers

## AC ELECTRICAL CHARACTERISTICS


( $V_{CC} = +5V$ ,  $V_{EE} = -5V$ ,  $AVCL = 2V/V$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
-3dB Bandwidth	BW-3dB	$V_{OUT} \leq 0.1V_{RMS}$ , $AVCL = 2V/V$	MAX4135	185	140	MHz
			MAX4136	140		
Full-Power Bandwidth	FPBW	$V_{OUT} = 2V_{p-p}$ , $AVCL = 2V/V$	MAX4135	185	140	MHz
			MAX4136	140		
0.1dB Bandwidth		$AVCL = 2V/V$		40		MHz
Slew Rate	SR	$-2V \leq V_{OUT} \leq 2V$		1000		V/ $\mu$ s
Settling Time	ts	$-1V \leq V_{OUT} \leq 1V/V$ , $R_L = 150\Omega$ , $AVCL = 2V/V$	to 0.1%	17	40	ns
			to 0.01%	40		
Differential Gain	DG	$f = 3.58MHz$ , $AVCL = 2V/V$	MAX4135	0.10	0.10	%
			MAX4136	0.10		
Differential Phase	DP	$f = 3.58MHz$ , $AVCL = 2V/V$	MAX4135	0.02	0.02	degrees
			MAX4136	0.02		
All-Hostile Crosstalk		$V_{IN} = 1V_{p-p}$ , $f = 30MHz$		-50		dB
Off Isolation		$V_{IN} = 1V_{p-p}$ , $f = 30MHz$		75		dB
Channel Switching Off Time	tOFF			25		ns
Channel Switching On Time	tON			25		ns
Digital Switching Feedthrough		$V_{IN} = 0V_{DC}$		$\pm 1$		mV
Spurious-Free Dynamic Range	SFDR	$f_C = 5MHz$ , $AVCL = 2V/V$ , $V_{OUT} = 2V_{p-p}$ , $R_L = 100\Omega$		-72		dBc
Output On-Resistance	ROUT	$f = DC$ , $AVCL = 2V/V$		1		$\Omega$
Output Off-Resistance	ROUT	$f = DC$ , $AVCL = 2V/V$		200		k $\Omega$
Output On-Capacitance	COUT(ON)			2		pF
Output Off-Capacitance	COUT(OFF)			3.5		pF

## 1-Input/6-Output Video Distribution Amplifiers

### Typical Operating Characteristics


( $V_{CC} = +5V$ ,  $V_{EE} = -5V$ ,  $R_L = 150\Omega$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



## 1-Input/6-Output Video Distribution Amplifiers

### Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = -5V$ ,  $R_L = 150\Omega$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)












# MAX4135/MAX4136

## 1-Input/6-Output Video Distribution Amplifiers

### Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = -5V$ ,  $R_L = 150\Omega$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



# 1-Input/6-Output Video Distribution Amplifiers

## Pin Description

PIN		NAME	FUNCTION
MAX4135	MAX4136		
1	1	OUT1	Output 1
2, 11	2, 11	VCCO	Positive Supply for Output Amplifiers. Connect to +5V.
3	3	OUT2	Output 2
4, 9, 18, 21	4, 9, 21	AGND	Analog Ground
5	5	OUT3	Output 3
6, 7	6, 7	VEEO	Negative Supply for Output Amplifiers. Connect to -5V.
8	8	OUT4	Output 4
10	10	OUT5	Output 5
12	12	OUT6	Output 6
13	13	SEL6	When low, enables output channel OUT6. When high, disables output channel OUT6.
14	14	SEL5	When low, enables output channel OUT5. When high, disables output channel OUT5.
15	15	SEL4	When low, enables output channel OUT4. When high, disables output channel OUT4.
16	16	VCCI	Positive Supply for Input Amplifier. Connect to +5V.
17	—	N.C.	No Connect. Not internally connected.
—	17	RF	Output of Input Amplifier
—	18	RG	Inverting Input
19	19	VEEI	Negative Supply for Input Amplifier. Connect to -5V.
20	20	IN+	Noninverting Input
22	22	SEL3	When low, enables output channel OUT3. When high, disables output channel OUT3.
23	23	SEL2	When low, enables output channel OUT2. When high, disables output channel OUT2.
24	24	SEL1	When low, enables output channel OUT1. When high, disables output channel OUT1.

## Detailed Description

The MAX4135/MAX4136 are 1-input/6-output video distribution amplifiers. The MAX4135 is configured for a fixed gain of +2, while the MAX4136 features external gain control (feedback) for closed-loop gains of 2V/V or greater.

Each output provides sufficient current to drive five  $150\Omega$  loads. However, distortion will increase when driving multiple loads. The TTL/CMOS-compatible digital control (SEL<sub>n</sub>) enables or disables each output amplifier. When the SEL<sub>n</sub> control input is low, the amplifier is enabled; when it is high, the amplifier is disabled and presents a high-impedance output. The enable/disable

or disable/enable time is under 25ns, which is useful in multiplexing, pixel switching, or picture-in-picture applications.

Each device has an input amplifier, which buffers the input from any switching glitches that may occur at the output stage, and provides a high-impedance, low-capacitance input. The separate input buffer allows a true high output impedance when an amplifier is disabled.

The outputs are protected against short circuits to ground. However, power-dissipation limits preclude shorting all output channels to ground. See the *Power-Dissipation Considerations* section for details.

## 1-Input/6-Output Video Distribution Amplifiers




Figure 1. MAX4135 Typical Operating Circuit

### Applications Information

#### Grounding, Bypassing, and PC Board Layout

To obtain the MAX4135/MAX4136's full 185MHz bandwidth, Microstrip and Stripline techniques are recommended in most cases. To ensure that the PC board does not degrade the amplifier's performance, design the board for a frequency greater than 1GHz. Even with very short traces, use these techniques at critical points, such as inputs and outputs. Whether you use a constant-impedance board or not, observe the following guidelines when designing the board:

- Do not use wire-wrap boards. They are too inductive.
- Do not use IC sockets. They increase parasitic capacitance and inductance.
- In general, surface-mount components have shorter leads and lower parasitic reactance, giving better high-frequency performance than through-hole components.
- The PC board should have at least two layers, with one side a signal layer and the other a ground plane.
- Keep signal lines as short and straight as possible. Do not make 90° turns; round all corners.
- The ground plane should be as free from voids as possible.

## 1-Input/6-Output Video Distribution Amplifiers

MAX4135/MAX4136




Figure 2. MAX4136 Typical Operating Circuit

## *Driving Capacitive Loads*

The MAX4135/MAX4136 provide maximum AC performance with no output load capacitance. This is the case when they are driving a correctly terminated transmission line (i.e., a back-terminated  $75\Omega$  cable). However, the MAX4135/MAX4136 are capable of driving capacitive loads up to  $10\text{pF}$  without oscillations, but with reduced AC performance.

Driving large capacitive loads increases the chance of oscillations in most amplifier circuits. This is especially true for circuits with high loop gain, such as voltage followers. The amplifier's output resistance and the load capacitor combine to add a pole and excess phase to

the loop response. If the frequency of this pole is low enough and phase margin is degraded sufficiently, oscillations may occur.

A second problem when driving capacitive loads results from the amplifier's output impedance, which looks inductive at high frequencies. This inductance forms an L-C resonant circuit with the capacitive load, which causes peaking in the frequency response and degrades the amplifier's gain margin.

The MAX4135/MAX4136 drive capacitive loads up to 10pF without oscillation. However, some peaking (in the frequency domain) or ringing (in the time domain) may occur (Figure 3).

## 1-Input/6-Output Video Distribution Amplifiers




Figure 3. Effect of  $C_{LOAD}$  on Frequency Response (without  $R_{ISO}$ )




Figure 4. Capacitive-Load Driving Circuit

To drive larger-capacitance loads or to reduce ringing, add an isolation resistor between the amplifier's output and the load, as shown in Figure 4.

The value of  $R_{ISO}$  depends on the circuit's gain and the capacitive load. Figure 5 shows the optimal isolation resistor ( $R_{ISO}$ ) vs. capacitive load ( $C_L$ ). At the higher capacitor values, the bandwidth is dominated by the RC network, formed by  $R_{ISO}$  and  $C_L$ .

### Power-Dissipation Considerations

The MAX4135/MAX4136 can drive up to six outputs simultaneously. Quiescent power dissipation is typically 750mW and 800mW maximum, respectively, with all channels enabled. The maximum package power dissipation is rated at 1540mW.

In a typical application, six outputs drive a standard video signal into a  $150\Omega$  load. The amount of power added to the quiescent dissipation is minimal and no special precautions are necessary.

However, each output driving the maximum 65mA into  $30\Omega$  will cause a power-dissipation increase of approximately 200mW. Therefore, you should not allow more than three outputs to deliver that load simultaneously. Similarly, one output shorted to ground will cause a power-dissipation increase of 650mW. Only one output can be shorted to ground without violating the package power rating.




Figure 5. Optimal Isolation Resistor ( $R_{ISO}$ ) vs.  $C_{LOAD}$

In conclusion, during normal operation in a matched-load environment, the total power dissipation is well within the package's dissipation rating. The maximum power dissipation is violated only if multiple channels are driving the maximum current into minimum loads at the same time.

1-Input/6-Output  
Video Distribution Amplifiers





Figure 6. Two Cameras to Six Monitors Distribution Amplifier

# 1-Input/6-Output Video Distribution Amplifiers

## Chip Information

TRANSISTOR COUNT: 901  
SUBSTRATE CONNECTED TO VEE

## Package Information



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

12 Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 (408) 737-7600

© 1996 Maxim Integrated Products

Printed USA

**MAXIM**

is a registered trademark of Maxim Integrated Products.