查询IRF6614供应商 捷多邦，专业PCB打样工厂，24小时加急出货

International
IOR Rectifier

PD -96907A

IRF6614

DirectFET™ Power MOSFET ②

- Application Specific MOSFETs
- Lead and Bromide Free ①
- Low Profile (<0.7 mm)
- Dual Sided Cooling Compatible ①
- Ultra Low Package Inductance
- Optimized for High Frequency Switching above 1MHz ①
- Ideal for CPU Core and Telecom Synchronous Rectification in DC-DC Converters
- Optimized for Control FET socket of Sync. Buck Converter①
- Low Conduction Losses
- Compatible with existing Surface Mount Techniques ①

Typical values (unless otherwise specified)

V_{DSS}	V_{GS}	$R_{DS(on)}$	$R_{DS(on)}$
40V max	±20V max	5.9mΩ@ 10V	7.1mΩ@ 4.5V

$Q_{g\ tot}$	Q_{gd}	Q_{gs2}	Q_{rr}	Q_{oss}	$V_{gs(th)}$
19nC	6.0nC	1.4nC	5.5nC	9.5nC	1.8V



Applicable DirectFET Outline and Substrate Outline (see p.7,8 for details)①

SQ	SX	ST		MQ	MX	MT				

Description

The IRF6614 combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest on-state resistance in a package that has the footprint of a MICRO-8 and only 0.7 mm profile. The DirectFET package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques, when application note AN-1035 is followed regarding the manufacturing methods and processes. The DirectFET package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6614 balances both low resistance and low charge along with ultra low package inductance to reduce both conduction and switching losses. The reduced total losses make this product ideal for high efficiency DC-DC converters that power the latest generation of processors operating at higher frequencies. The IRF6614 has been optimized for parameters that are critical in synchronous buck operating from 12 volt buss converters including Rds(on) and gate charge to minimize losses in the control FET socket.

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{DS}	Drain-to-Source Voltage	40	V
V_{GS}	Gate-to-Source Voltage	±20	
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ 10V ⑥	12.7	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ 10V ⑥	10.1	
I_D @ T_C = 25°C	Continuous Drain Current, V_{GS} @ 10V ⑨	55	
I_{DM}	Pulsed Drain Current ③	102	
E_{AS}	Single Pulse Avalanche Energy ④	22	mJ
I_{AR}	Avalanche Current ③	10.2	A



Fig 1. Typical On-Resistance Vs. Gate Voltage



Fig 2. Typical Total Gate Charge vs Gate-to-Source Voltage

Notes:
① Click on this section to link to the appropriate technical paper.
② Click on this section to link to the DirectFET MOSFETs
③ Repetitive rating; pulse width limited by max. junction temperature.
④ Starting T_J = 25°C, L = 0.43mH, R_G = 25Ω, I_{AS} = 10.2A.
⑥ Surface mounted on 1 in. square Cu board, steady state.
⑨ T_C measured with thermocouple mounted to top (Drain) of part.

Static @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	40	—	—	V	V_{GS} = 0V, I_D = 250μA
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	38	—	mV/°C	Reference to 25°C, I_D = 1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	5.9	8.3	mΩ	V_{GS} = 10V, I_D = 12.7A ⑤
		—	7.1	9.9		V_{GS} = 4.5V, I_D = 10.2A ⑤
$V_{GS(th)}$	Gate Threshold Voltage	1.35	1.80	2.25	V	V_{DS} = V_{GS}, I_D = 250μA
$\Delta V_{GS(th)}/\Delta T_J$	Gate Threshold Voltage Coefficient	—	-5.5	—	mV/°C	
I_{DSS}	Drain-to-Source Leakage Current	—	—	1.0	μA	V_{DS} = 32V, V_{GS} = 0V
		—	—	150		V_{DS} = 32V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	V_{GS} = 20V
	Gate-to-Source Reverse Leakage	—	—	-100		V_{GS} = -20V
gfs	Forward Transconductance	71	—	—	S	V_{DS} = 10V, I_D = 10.2A
Q_g	Total Gate Charge	—	19	29	nC	
Q_{gs1}	Pre-Vth Gate-to-Source Charge	—	5.9	—		V_{DS} = 20V
Q_{gs2}	Post-Vth Gate-to-Source Charge	—	1.4	—		V_{GS} = 4.5V
Q_{gd}	Gate-to-Drain Charge	—	6.0	—		I_D = 10.2A
Q_{godr}	Gate Charge Overdrive	—	5.7	—		See Fig. 17
Q_{sw}	Switch Charge (Q_{gs2} + Q_{gd})	—	7.4	—		
Q_{oss}	Output Charge	—	9.5	—	nC	V_{DS} = 16V, V_{GS} = 0V
R_G	Gate Resistance	—	1.0	1.5	Ω	
$t_{d(on)}$	Turn-On Delay Time	—	13	—	ns	V_{DD} = 20V, V_{GS} = 4.5V ⑤
t_r	Rise Time	—	27	—		I_D = 10.2A
$t_{d(off)}$	Turn-Off Delay Time	—	18	—		Clamped Inductive Load
t_f	Fall Time	—	3.6	—		
C_{iss}	Input Capacitance	—	2560	—	pF	V_{GS} = 0V
C_{oss}	Output Capacitance	—	370	—		V_{DS} = 20V
C_{rss}	Reverse Transfer Capacitance	—	200	—		f = 1.0MHz

Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	2.6	A	MOSFET symbol showing the integral reverse p-n junction diode. 
I_{SM}	Pulsed Source Current (Body Diode) ③	—	—	102		
V_{SD}	Diode Forward Voltage	—	—	1.0	V	T_J = 25°C, I_S = 10.2A, V_{GS} = 0V ⑤
t_{rr}	Reverse Recovery Time	—	15	23	ns	T_J = 25°C, I_F = 10.2A
Q_{rr}	Reverse Recovery Charge	—	5.5	8.3	nC	di/dt = 100A/μs ⑤

Notes:

③ Repetitive rating; pulse width limited by max. junction temperature.

⑤ Pulse width ≤ 400μs; duty cycle ≤ 2%.

Absolute Maximum Ratings

	Parameter	Max.	Units
P_D @T_A = 25°C	Power Dissipation ⑥	2.1	W
P_D @T_A = 70°C	Power Dissipation ⑥	1.4	
P_D @T_C = 25°C	Power Dissipation ⑨	42	
T_P	Peak Soldering Temperature	270	°C
T_J T_{STG}	Operating Junction and Storage Temperature Range	-40 to + 150	

Thermal Resistance

	Parameter	Typ.	Max.	Units
$R_{\theta JA}$	Junction-to-Ambient ⑥⑩	——	58	°C/W
$R_{\theta JA}$	Junction-to-Ambient ⑦⑩	12.5	——	
$R_{\theta JA}$	Junction-to-Ambient ⑧⑩	20	——	
$R_{\theta JC}$	Junction-to-Case ⑨⑩	——	3.0	
$R_{\theta J\text{-}PCB}$	Junction-to-PCB Mounted	1.0	——	
	Linear Derating Factor ⑤	0.017		W/°C



Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Notes:

⑥ Surface mounted on 1 in. square Cu board, steady state.

⑦ Used double sided cooling , mounting pad.

⑧ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.

⑨ T_C measured with thermocouple incontact with top (Drain) of part.

⑩ R_θ is measured at T_J of approximately 90°C.



⑥ Surface mounted on 1 in. square Cu board (still air).



⑦ Mounted to a PCB with a thin gap filler and heat sink. (still air)



⑧ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)



Fig 4. Typical Output Characteristics



Fig 5. Typical Output Characteristics



Fig 6. Typical Transfer Characteristics



Fig 7. Normalized On-Resistance vs. Temperature



Fig 8. Typical Capacitance vs.Drain-to-Source Voltage



Fig 9. Typical On-Resistance Vs. Drain Current and Gate Voltage



Fig 10. Typical Source-Drain Diode Forward Voltage



Fig11. Maximum Safe Operating Area



Fig 12. Maximum Drain Current vs. Case Temperature



Fig 13. Typical Threshold Voltage vs. Junction Temperature



Fig 14. Maximum Avalanche Energy Vs. Drain Current



Fig 15a. Gate Charge Test Circuit



Fig 15b. Gate Charge Waveform



Fig 16b. Unclamped Inductive Test Circuit



Fig 16c. Unclamped Inductive Waveforms



Fig 17a. Switching Time Test Circuit



Fig 17b. Switching Time Waveforms



Fig 18. Diode Reverse Recovery Test Circuit for N-Channel HEXFET® Power MOSFETs

DirectFET™ Substrate and PCB Layout, ST Outline (Small Size Can, T-Designation).

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET. This includes all recommendations for stencil and substrate designs.



1- Drain
2- Drain
3- Source
4- Source
5- Gate
6- Drain
7- Drain

IRF6614

International
IOR Rectifier

DirectFET™ Outline Dimension, ST Outline (Small Size Can, T-Designation).

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.
This includes all recommendations for stencil and substrate designs.



DIMENSIONS				
	METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX
A	4.75	4.85	0.187	0.191
B	3.70	3.95	0.146	0.156
C	2.75	2.85	0.108	0.112
D	0.35	0.45	0.014	0.018
E	0.58	0.62	0.023	0.024
F	0.58	0.62	0.023	0.024
G	0.75	0.79	0.030	0.031
H	0.53	0.57	0.021	0.022
J	0.26	0.30	0.010	0.012
K	O.88	0.98	0.035	0.039
L	2.18	2.28	0.086	0.090
M	0.59	0.70	0.023	0.028
N	0.03	0.08	0.001	0.003

Note: Controlling dimensions are in mm

DirectFET™ Part Marking



DirectFET™ Tape & Reel Dimension (Showing component orientation).



NOTE: Controlling dimensions in mm
Std reel quantity is 4800 parts. (ordered as IRF6614). For 1000 parts on 7" reel, order IRF6614TR1

REEL DIMENSIONS								
STANDARD OPTION **(QTY 4800)**					TR1 OPTION **(QTY 1000)**			
	METRIC		IMPERIAL		METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
A	330.0	N.C	12.992	N.C	177.77	N.C	6.9	N.C
B	20.2	N.C	0.795	N.C	19.06	N.C	0.75	N.C
C	12.8	13.2	0.504	0.520	13.5	12.8	0.53	0.50
D	1.5	N.C	0.059	N.C	1.5	N.C	0.059	N.C
E	100.0	N.C	3.937	N.C	58.72	N.C	2.31	N.C
F	N.C	18.4	N.C	0.724	N.C	13.50	N.C	0.53
G	12.4	14.4	0.488	0.567	11.9	12.01	0.47	N.C
H	11.9	15.4	0.469	0.606	11.9	12.01	0.47	N.C

Loaded Tape Feed Direction



NOTE: CONTROLLING DIMENSIONS IN MM

DIMENSIONS				
	METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX
A	7.90	8.10	0.311	0.319
B	3.90	4.10	0.154	0.161
C	11.90	12.30	0.469	0.484
D	5.45	5.55	0.215	0.219
E	5.10	5.30	0.201	0.209
F	6.50	6.70	0.256	0.264
G	1.50	N.C	0.059	N.C
H	1.50	1.60	0.059	0.063

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier
IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.11/04