查询IRF7306供应商 捷多邦，专业PCB打样工厂，24小时加急出货

International
IOR Rectifier

PD - 9.1241C

IRF7306

HEXFET® Power MOSFET

- Generation V Technology
- Ultra Low On-Resistance
- Dual P-Channel Mosfet
- Surface Mount
- Available in Tape & Reel
- Dynamic dv/dt Rating
- Fast Switching



Top View

V_{DSS} = -30V

$R_{DS(on)}$ = 0.10Ω


SO-8

Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve the lowest possible on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient device for use in a wide variety of applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infra red, or wave soldering techniques. Power dissipation of greater than 0.8W is possible in a typical PCB mount application.

Absolute Maximum Ratings

	Parameter	Max.	Units
I_D @ T_A = 25°C	10 Sec. Pulsed Drain Current, V_{GS} @ -10V	-4.0	A
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ -10V	-3.6	
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ -10V	-2.9	
I_{DM}	Pulsed Drain Current ①	-14	
P_D @T_A = 25°C	Power Dissipation	2.0	W
	Linear Derating Factor	0.016	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
dv/dt	Peak Diode Recovery dv/dt ②	-5.0	V/ns
T_J, T_{STG}	Junction and Storage Temperature Range	-55 to + 150	°C

Thermal Resistance Ratings

	Parameter	Typ.	Max.	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient④	——	62.5	°C/W

找PDF 维库一下 pdf.dzsc.com

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)DSS}$	Drain-to-Source Breakdown Voltage	-30	——	——	V	V_{GS} = 0V, ID = -250µA
$\Delta V_{(BR)DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	——	-0.037	——	V/°C	Reference to 25°C, I_D = -1mA
$R_{DS(ON)}$	Static Drain-to-Source On-Resistance	——	——	0.10	Ω	V_{GS} = -10V, I_D = -1.8A ③
		——	——	0.16		V_{GS} = -4.5V, I_D = -1.5A ③
$V_{GS(th)}$	Gate Threshold Voltage	-1.0	——	——	V	V_{DS} = V_{GS}, I_D = -250µA
g_{fs}	Forward Transconductance	2.5	——	——	S	V_{DS} = -24V, I_D = -1.8A
I_{DSS}	Drain-to-Source Leakage Current	——	——	-1.0	µA	V_{DS} = -24V, V_{GS} = 0V
		——	——	-25		V_{DS} = -24V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	——	——	-100	nA	V_{GS} = -20V
	Gate-to-Source Reverse Leakage	——	——	100		V_{GS} = 20V
Q_g	Total Gate Charge	——	——	25	nC	I_D = -1.8A
Q_{gs}	Gate-to-Source Charge	——	——	2.9		V_{DS} = -24V
Q_{gd}	Gate-to-Drain ("Miller") Charge	——	——	9.0		V_{GS} = -10V, See Fig. 6 and 12 ③
$t_{d(on)}$	Turn-On Delay Time	——	11	——	ns	V_{DD} = -15V
t_r	Rise Time	——	17	——		I_D = -1.8A
$t_{d(off)}$	Turn-Off Delay Time	——	25	——		R_G = 6.0Ω
t_f	Fall Time	——	18	——		R_D = 8.2Ω, See Fig. 10 ③
L_D	Internal Drain Inductance	——	4.0	——	nH	Between lead tip and center of die contact 
L_S	Internal Source Inductance	——	6.0	——		
C_{iss}	Input Capacitance	——	440	——	pF	V_{GS} = 0V
C_{oss}	Output Capacitance	——	200	——		V_{DS} = -25V
C_{rss}	Reverse Transfer Capacitance	——	93	——		ƒ = 1.0MHz, See Fig. 5

Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	——	——	-2.5	A	MOSFET symbol showing the integral reverse p-n junction diode. 
I_{SM}	Pulsed Source Current (Body Diode) ①	——	——	-14		
V_{SD}	Diode Forward Voltage	——	——	-1.0	V	T_J = 25°C, I_S = -1.8A, V_{GS} = 0V ③
t_{rr}	Reverse Recovery Time	——	53	80	ns	T_J = 25°C, I_F = -1.8A
Q_{rr}	Reverse RecoveryCharge	——	66	99	µC	di/dt = 100A/µs ③
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible (turn-on is dominated by L_S+L_D)				

Notes:

① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 11)

② I_{SD} ≤ -1.8A, di/dt ≤ 90A/µs, V_{DD} ≤ $V_{(BR)DSS}$, T_J ≤150°C

③ Pulse width ≤ 300µs; duty cycle ≤ 2%.

④ Surface mounted on FR-4 board, t ≤ 10sec.



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance Vs. Temperature



Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Maximum Drain Current Vs. Ambient Temperature



Fig 10a. Switching Time Test Circuit



Fig 10b. Switching Time Waveforms



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Fig 12a. Basic Gate Charge Waveform



Fig 12b. Gate Charge Test Circuit

Peak Diode Recovery dv/dt Test Circuit



* Reverse Polarity for P-Channel
** Use P-Channel Driver for P-Channel Measurements



*** V_{GS} = 5.0V for Logic Level and 3V Drive Devices

Fig 13. For P-Channel HEXFETS

Package Outline

SO-8 Outline

Dimensions are shown in millimeters (inches)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.0532	.0688	1.35	1.75
A1	.0040	.0098	0.10	0.25
B	.014	.018	0.36	0.46
C	.0075	.0098	0.19	0.25
D	.189	.196	4.80	4.98
E	.150	.157	3.81	3.99
e	.050 BASIC		1.27 BASIC	
e1	.025 BASIC		0.635 BASIC	
H	.2284	.2440	5.80	6.20
K	.011	.019	0.28	0.48
L	0.16	.050	0.41	1.27
θ	0°	8°	0°	8°

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
2. CONTROLLING DIMENSION : INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.006).
6. DIMENSIONS IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE..

RECOMMENDED FOOTPRINT



Part Marking Information

SO-8

EXAMPLE : THIS IS AN IRF7101



Tape & Reel Information

SO-8

Dimensions are shown in millimeters (inches)





NOTES:

1 CONFORMS TO EIA-481-1

2 INCLUDES FLANGE DISTORTION @ OUTER EDGE

3 DIMENSIONS MEASURED @ HUB

4 CONTROLLING DIMENSION : METRIC

International
IOR Rectifier

WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, Tel: (310) 322 3331
EUROPEAN HEADQUARTERS: Hurst Green, Oxted, Surrey RH8 9BB, UK Tel: ++ 44 1883 732020
IR CANADA: 7321 Victoria Park Ave., Suite 201, Markham, Ontario L3R 2Z8, Tel: (905) 475 1897
IR GERMANY: Saalburgstrasse 157, 61350 Bad Homburg Tel: ++ 49 6172 96590
IR ITALY: Via Liguria 49, 10071 Borgaro, Torino Tel: ++ 39 11 451 0111
IR FAR EAST: K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo Japan 171 Tel: 81 3 3983 0086
IR SOUTHEAST ASIA: 315 Outram Road, #10-02 Tan Boon Liat Building, Singapore 0316 Tel: 65 221 8371