

FAIRCHILD SEMICONDUCTOR

84 DE 3469674 0027336 0

**FAIRCHILD**

A Schlumberger Company

# FD700/FDLL700

# FD777/FDLL777

## Ultra Fast Diodes

T-03-09

- C... 1.0 pF (MAX) @  $V_R = 0$ , f = 1.0 MHz (FD 700)
- $t_{rr}$ ... 700 ps (MAX) @  $I_F = I_r = 10$  mA,  $R_L = 100 \Omega$  (FD 700)
- CONTROLLED FORWARD CONDUCTANCE

PACKAGES
FD700
DO-7
FD777
DO-7
FDLL700
LL-34
FDLL777
LL-34

## ABSOLUTE MAXIMUM RATINGS (Note 1)

	FD700	FD777	
Storage Temperature Range	-65°C to +200°C	-65°C to +200°C	
Max Junction Operating Temperature	+175°C	+175°C	
Lead Temperature	+260°C	+260°C	
<b>Power Dissipation</b>			
Maximum Total Dissipation at 25°C			
Ambient	250 mW	250 mW	
Linear Derating Factor (from 25°C)	1.67 mW/°C	1.67 mW/°C	
<b>Maximum Voltages and Currents</b>			
WIV	Working Inverse Voltage	20 V	8.0 V
$I_O$	Average Rectified Current	50 mA	50 mA
$I_F$	Forward Current Steady State dc	150 mA	150 mA
$I_r$	Recurrent Peak Forward Current	150 mA	150 mA
$I_F$ (surge)	Peak Forward Surge Current Pulse Width = 1.0 s	250 mA	250 mA

If you need this device in the SOT package, an electrical equivalent is available. See FDSO1700 family.

3

## ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	FD700		FD777		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
$V_F$	Forward Voltage	0.89	1.10	0.89	1.35	V	$I_F = 50$ mA
		0.81	0.95	0.81	1.00	V	$I_F = 20$ mA
		0.76	0.88	0.76	0.94	V	$I_F = 10$ mA
		0.64	0.74	0.64	0.79	V	$I_F = 1.0$ mA
		0.52	0.61	0.52	0.64	V	$I_F = 0.1$ mA
		0.42	0.50	0.42	0.53	V	$I_F = 0.01$ mA
$BV$	Breakdown Voltage	30		15		V	$I_R = 5.0$ $\mu$ A
$I_R$	Reverse Current		50		100	nA	$V_R = 20$ V
					50	nA	$V_R = 8.0$ V
						$\mu$ A	$V_R = 20$ V, $T_A = 150^\circ\text{C}$
						$\mu$ A	$V_R = 8.0$ V, $T_A = 150^\circ\text{C}$
$\tau$	Minority Carrier Lifetime		450		450	ps	(see Note 2)
$t_{rr}$	Reverse Recovery Time (Note 3)		700		750	ps	$I_F = I_r = 10$ mA, $R_L = 100 \Omega$
C	Capacitance		1.0		1.3	pF	$V_R = 0$ , f = 1.0 MHz

## NOTES:

- The maximum ratings are limiting values above which life or satisfactory performance may be impaired.
- Measured as suggested by S. M. Krakauer, IRE Proceedings, Volume 60, July 1982, pp. 1674 - 1675.
- Recovery to 0.1  $I_F$ .
- For product family characteristic curves, refer to Chapter 4, D3.