


SBD Type : FSH04A06

OUTLINE DRAWING

FEATURES

- *Similar to TO-220AC Case
- *Fully Molded Isolation
- *Low Forward Voltage Drop
- *Low Power Loss,High Efficiency
- *High Surge Capability
- *Tj=150 °C operation



Maximum Ratings



Approx Net Weight: 1.7g

Rating	Symbol	FSH04A06		Unit
Repetitive Peak Reverse Voltage	V_{RRM}	60		V
Repetitive Peak Surge Reverse Voltage	V_{RRSM}	65(pulse width $\leq 1\mu s$ duty $\leq 1/50$)		V
Average Rectified Output Current	I_O	4	Tc=129°C 50 Hz half Sine Wave Resistive Load	A
RMS Forward Current	$I_{F(RMS)}$	6.28		A
Surge Forward Current	I_{FSM}	100	50Hz Half Sine Wave ,1cycle Non-repetitive	A
Operating JunctionTemperature Range	T_{jw}	-40 to +150		°C
Storage Temperature Range	T_{stg}	-40 to +150		°C
Mounting torque	F_{tor}	recommended torque = 0.5		N•m


Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I_{RM}	Tj= 25°C, $V_{RM} = V_{RRM}$	-	-	1	mA
Peak Forward Voltage	V_{FM}	Tj= 25°C, $I_{FM} = 4 A$	-	-	0.69	V
Thermal Resistance	$R_{th(j-c)}$	Junction to Case	-	-	6	°C/W
	$R_{th(c-f)}$	Cace to Fin	-	-	1.5	°C/W


FSH_A_ OUTLINE DRAWING (Dimensions in mm)



FORWARD CURRENT VS. VOLTAGE




AVERAGE FORWARD POWER DISSIPATION



PEAK REVERSE CURRENT VS. PEAK REVERSE VOLTAGE


T_j = 150 °C

FSH04A06



AVERAGE REVERSE POWER DISSIPATION

FSH04A06






AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE

$V_{RM}=60V$


FSH04A06



SURGE CURRENT RATINGS

$f=50Hz$, Sine Wave, Non-Repetitive, No Load

FSH04A06



JUNCTION CAPACITANCE VS. REVERSE VOLTAGE

$T_j=25^\circ\text{C}$, $V_m=20\text{mV}_{\text{RMS}}$, $f=100\text{kHz}$, Typical Value

FSH04A06

