

# FU-319SPP-CV6

InGaAs PD PREAMP MODULE FOR THE 1.31  $\mu\text{m}$  AND 1.55  $\mu\text{m}$  WAVELENGTH RANGE

## DESCRIPTION

FU-319SPP-CV6 is InGaAs pin photodiode module with GaAs preamplifier, designed for use in high-speed, long haul optical communication systems. The coaxial package contains an InGaAs pin photodiode coupled with single-mode fiber pigtail and GaAs preamplifier.

## FEATURES

- High-sensitivity (-23dBm typ)
- 5pin coaxial package
- Selectable single power supply voltage (+5V or -5.2V). (InGaAs pin photodiode and GaAs preamplifier are isolated from the case.)
- GaAs preamplifier with AGC function
- Differential output (50 $\Omega$ )

## APPLICATION

2.5Gbps optical receiver (OC-48, STM-16)  
Extended reach datacom and telecom applications  
Long haul optical communication systems

## ABSOLUTE MAXIMUM RATINGS (T<sub>c</sub>=25°C)

Parameter	Symbol	Conditions	Rating	Unit
PD Reverse voltage	VPD	VSS=0V	20	V
PD Reverse current (CW)	I <sub>r</sub>	-	4	mA
PD Forward current (CW)	I <sub>f</sub>	-	2	mA
Power supply voltage	VDD	VSS=0V	0~7	V
Operating case temperature	T <sub>c</sub>	-	-40~+85	°C
Storage temperature	T <sub>stg</sub>	-	-40~+85	°C

**FU-319SPP-CV6****InGaAs PD PREAMP MODULE FOR THE 1.31  $\mu\text{m}$  AND 1.55  $\mu\text{m}$  WAVELENGTH RANGE****ELECTRICAL/OPTICAL CHARACTERISTICS** ( $T_c=25^\circ\text{C}$ ,  $\lambda=1.3\mu\text{m}$ ,  $V_{DD}=5\text{V}$ ,  $V_{SS}=0\text{V}$  unless otherwise noted)

Parameter	Symbol	Test Conditions	Limits			Unit
			Min.	Typ.	Max.	
Detection range	-	-	1000	-	1600	nm
Responsivity(Note 1)	R	CW	0.7	0.8	-	A/W
Transimpedance	Zt(off)	AC, f=100MHz, RL=High AGC_off (Note 1)	-	1.7	-	k $\Omega$
	Zt(on)	AC, f=100MHz, RL=High AGC_on	-	0.5	-	
Cutoff frequency(-3dB)	fc_High	AC, RL=50 $\Omega$	1.8	-	-	GHz
	fc_Low	AC, RL=50 $\Omega$	-	-	100	kHz
Average input equivalent noise current density	in	AC, RL=50 $\Omega$ , 1MHz~1.8GHz	-	6.5	-	pA/ $\sqrt{\text{Hz}}$
Output impedance	Zo	(Differential output)	-	50	-	$\Omega$
Sensitivity	Pr	AC, RL=50 $\Omega$ , NRZ, 2.48832Gbps., PRBS=2 <sup>23</sup> -1, BER=10 <sup>-10</sup> , VPD=5V (Note 2)	-	-23	-21	dBm
Over load power	Po		1	3	-	
Power supply voltage	VDD	VSS=0V	4.75	5	5.46	V
Power supply current	IDD	VDD=5V	-	35	60	mA
Optical return loss	Prtn	-	27	-	-	dB

Note 1. Transimpedance value apply when AGC(Bit by bit) function is fully off.

Note 2. Used post-amp bandwidth is 1.86GHz, Laser source extinction ratio is 10dB.

**OPTICAL FIBER SPECIFICATION**

Parameter	Limits	Unit
Type	SM	-
Mode field dia.	9.5 $\pm$ 1	$\mu\text{m}$
Cladding dia.	125 $\pm$ 2	$\mu\text{m}$
Jacket dia.	0.9 typ.	mm
Connector return loss	40(min)	dB

**BLOCK DIAGRAM**

