


SOT223 NPN SILICON PLANAR MEDIUM POWER TRANSISTOR

ISSUE 3 – NOVEMBER, 1995

FZT493



COMPLEMENTARY TYPE – FZT593

PARTMARKING DETAIL – FZT493

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	120	V
Collector-Emitter Voltage	V_{CEO}	100	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	2	A
Continuous Collector Current	I_C	1	A
Base Current	I_B	200	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	2	W
Operating and Storage Temperature Range	T_j, T_{stg}	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Breakdown Voltages	$V_{(BR)CBO}$	120			V	$I_C=100\mu\text{A}$
	$V_{(BR)CEO}$	100			V	$I_C=10\text{mA}^*$
	$V_{(BR)EBO}$	5			V	$I_E=100\mu\text{A}$
Cut-Off Currents	I_{CBO}			100	nA	$V_{CE}=100\text{V}$
	I_{EBO}			100	nA	$V_{EB}=4\text{V}$
	I_{CES}			100	nA	$V_{CES}=100\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		0.3		V	$I_C=500\text{mA}, I_B=50\text{mA}^*$
			0.6		V	$I_C=1\text{A}, I_B=100\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		1.15		V	$I_C=1\text{A}, I_B=100\text{mA}^*$
Base-Emitter Turn-On Voltage	$V_{BE(on)}$		1.0		V	$I_C=1\text{A}, V_{CE}=10\text{V}^*$
Static Forward Current	I_{FE}	100				$I_C=1\text{mA}, V_{CE}=10\text{V}$
		100		300		$I_C=250\text{mA}, V_{CE}=10\text{V}^*$
		80				$I_C=500\text{mA}, V_{CE}=10\text{V}^*$
		30				$I_C=1\text{A}, V_{CE}=10\text{V}^*$
Transition Frequency	f_T	150			MHz	$I_C=50\text{mA}, V_{CE}=10\text{V}, f=100\text{MHz}$
Output Capacitance	C_{obo}			10	pF	$V_{CE}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$
For typical Characteristics graphs see FMMT493 datasheet

查询FZT493供应商

捷多邦, 专业PCB打样工厂, 24小时加急出货

