


Surface Mount

Monolithic Amplifiers

NEW!

Gali-19 • Gali-29 • Gali-39
Gali-49 • Gali-59

50Ω, Broadband, DC to 7 GHz



CASE STYLE : DF782

Features

- miniature SOT-89 package
- frequency range, DC to 7 GHz
- up to 17.6 dBm typ. output power
- excellent package for heat dissipation, exposed metal bottom

Applications

- cellular
- PCS
- communication receivers & transmitters

Electrical Specifications @ 25°C

	MODEL NO.	FREQ. [▲] (GHz)	GAIN, dB Typical									MAXIMUM POWER, dBm at 7 GHz*			DYNAMIC RANGE at 2 GHz*		VSWR (:1) Typ.				MAXIMUM CURRENT RATING**		DC OPERATING POWER @ Pin 3***				THERMAL RESISTANCE θ _{jc} , typ. °C/W	PRICE \$ Qty. (25)							
			over frequency, GHz									Min. @ 2 GHz		Output (1 dB Comp.)		NF dB		IP3 dBm		DC-3		3-f _U		DC-3		3-f _U			I		Current		Device		
			0.1	1	2	3	4	5	7	10		Typ.	Min.	Typ.	Min.	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.	mA	(mA)	Typ	Min			Max	Typ	Min	Max			
LOW POWER	Gal ₁₉	DC-7	12.1	11.7	11.6	10.7	10.8	10.1	11.0	14.5	9.6	10.6	9.0	15	6.5	23.7	1.6	1.7	1.5	2.3	55	40	3.6	3.2	4.0	311	1.19								
	Gal ₂₉	DC-7	15.4	15.1	14.7	13.7	13.6	12.9	14.2	12.5	12.7	11.2	10.0	15	6.0	24.7	1.5	1.6	1.5	2.3	55	40	3.6	3.2	4.0	340	1.19								
	Gal ₃₉	DC-7	20.8	21.1	19.7	17.7	17.0	16.1	17.6	9.8	17.7	10.5	9.0	13	4.9	22.9	1.6	1.8	1.5	2.3	55	35	3.5	3.1	3.9	350	1.19								
MEDIUM POWER	Gal ₄₉	DC-5	14.0	13.7	13.6	13.7	13.3	13.1	10.7	—	11.5	16.4	15.0	20	5.5	33.3	1.7	1.2	1.5	1.4	85	65	5.0	4.5	5.4	171	1.79								
	Gal ₅₉	DC-5	20.6	19.7	18.3	16.7	15.4	14.0	10.2	—	16.3	17.6	16.5	13.0	4.3	33.3	1.6	1.5	1.5	1.7	85	65	4.8	4.3	5.2	209	1.79								

▲ Low frequency cutoff determined by external coupling capacitors.

* For Pout @ 1dB compression, Gali-49, -59 at 2 GHz.
For IP3, Gali-49, -59 at 1 GHz.

** Permanent damage may occur if any of these limits are exceeded.
These ratings are not intended for continuous normal operation.

***Reliability predictions and normal operating conditions are applicable at current specified.

f_u is the upper frequency limit for each model as shown in the table.

Maximum Ratings

Operating Temperature -45°C to 85°C
Storage Temperature -65°C to 150°C


Pin Configuration

RF IN	1
RF OUT	3
DC	3
GND EXT.	2


Model Identification

Model	Marking [†]
Gali-19	19
Gali-29	29
Gali-39	39
Gali-49	49
Gali-59	59


[†] Prefix letter (optional) designates assembly location. Suffix letters (optional) are for wafer identification.



Suggested Layout for PCB Pattern




Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
.102	.090	.181	.173	.063	.167	.155	.059
2.59	2.29	4.60	4.39	1.60	4.24	3.94	1.50
J	K	L	M	N	P	wt.	
.118	.015	.041	.016	.019	.065	grams	
3.00	0.38	1.04	0.41	0.48	1.65	.2	

Typical Biasing Configuration



Test Board includes case, connectors, and components (in bold) soldered to PCB

R BIAS

"1%" Resistor Values (ohms) for Optimum Biasing of Gali Models

Vcc	Gali-19	Gali-29	Gali-39	Gali-49	Gali-59
7	88.7	88.7	107	34.0	36.5
8	113	113	133	48.7	51.1
9	137	137	162	64.9	64.9
10	162	162	191	80.6	80.6
11	187	187	221	95.3	97.6
12	215	215	249	110	113
13	237	237	280	127	127
14	261	261	309	143	143
15	287	287	340	158	158
16	309	316	365	174	174
17	332	340	392	187	191
18	357	365	422	205	205
19	383	392	453	221	221
20	412	412	475	237	237