




GBU801 THRU GBU807

Single Phase 8.0 AMPS. Glass Passivated Bridge Rectifiers



Voltage Range
50 to 1000 Volts
Current
8.0 Amperes


Features

- ✦ UL Recognized File # E-96005
- ✦ Ideal for printed circuit board
- ✦ Reliable low cost construction
- ✦ Plastic material has Underwriters Laboratory Flammability Classification 94V-0
- ✦ Surge overload rating to 200 amperes peak
- ✦ High temperature soldering guaranteed: 260°C / 10 seconds / .375", (9.5mm) lead lengths.

Mechanical Data

- ✦ Case: Molded plastic body.
- ✦ Terminals: Plated leads solderable per MIL-STD-750, Method 2026.
- ✦ Weight: 0.3 ounce, 8.0 grams
- ✦ Mounting torque: 5 in. lb. Max.

GBU



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	GBU	GBU	GBU	GBU	GBU	GBU	GBU	Units
		801	802	803	804	805	806	807	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_C = 100^\circ\text{C}$	$I_{(AV)}$	8.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	200							A
Maximum Instantaneous Forward Voltage @ 8.0A	V_F	1.0							V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=125^\circ\text{C}$	I_R	5.0 500							μA μA
Rating for fusing ($t < 8.3\text{ms}$)	I^2t	166							A^2sec
Typical Thermal Resistance Per Leg (Note 1) (Note 2)	$R_{\theta JA}$ $R_{\theta JC}$	21.0 2.0							$^\circ\text{C}/\text{W}$
Typical Junction Capacitance (Note 3)	C_j	211				94			pF
Operating Temperature Range	T_J	-55 to +150							$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150							$^\circ\text{C}$

Notes 1: Units Mounted in Free Air No Heat Sink On PCB 0.5x0.5" (12x12mm) Copper Pads, 0.375"(9.5mm) Lead Length.

2: Units Case Mounted On 4" x 6" x 0.25" AL. Plate Heat Sink.

3: Measured at 1.0 MHz and applied Reverse Voltage of 4.0V.



RATINGS AND CHARACTERISTIC CURVES (GBU801 THRU GBU807)

FIG.1- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER BRIDGE ELEMENT




FIG.2-MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT

