

# HD74ALVC16836

20-bit Universal Bus Driver with 3-state Outputs

**HITACHI**

ADE-205-209 (Z)  
Preliminary  
1st. Edition  
January 1998

## Description

This 20-bit universal bus driver is designed for 2.3 V to 3.6 V  $V_{CC}$  operation.

Data flow from A to Y is controlled by the output enable ( $\overline{OE}$ ) input. The device operates in the transparent mode when the latch enable ( $\overline{LE}$ ) input is low. When  $\overline{LE}$  is high, the A data is latched if the clock (CLK) input is held at a high or low logic level. If  $\overline{LE}$  is high, the A data is stored in the latch flip flop on the low to high transition of CLK. When  $\overline{OE}$  is high, the outputs are in the high impedance state.

To ensure the high impedance state during power up or power down,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current sinking capability of the driver.

## Features

- $V_{CC} = 2.3$  V to 3.6 V
- Typical  $V_{OL}$  ground bounce < 0.8 V (@ $V_{CC} = 3.3$  V,  $T_a = 25^\circ C$ )
- Typical  $V_{OH}$  undershoot > 2.0 V (@ $V_{CC} = 3.3$  V,  $T_a = 25^\circ C$ )
- High output current  $\pm 24$  mA (@ $V_{CC} = 3.0$  V)

---

## HD74ALVC16836

---

### Function Table

Inputs				Output Y
OE	LE	CLK	A	
H	X	X	X	Z
L	L	X	L	L
L	L	X	H	H
L	H	↑	L	L
L	H	↑	H	H
L	H	H	X	$Y_0^{-1}$
L	H	L	X	$Y_0^{-2}$

H : High level

L : Low level

X : Immaterial

Z : High impedance

↑ : Low to high transition

Notes: 1. Output level before the indicated steady state input conditions were established, provided that CLK is high before LE goes low.

2. Output level before the indicated steady state input conditions were established.


---

---

## HD74ALVC16836

---

### Pin Arrangement



---

## HD74ALVC16836

---

### Absolute Maximum Ratings

Item	Symbol	Ratings	Unit	Conditions
Supply voltage	$V_{CC}$	−0.5 to 4.6	V	
Input voltage <sup>1</sup>	$V_I$	−0.5 to 4.6	V	
Output voltage <sup>1,2</sup>	$V_O$	−0.5 to $V_{CC}$ +0.5	V	
Input clamp current	$I_{IK}$	−50	mA	$V_I < 0$
Output clamp current	$I_{OK}$	±50	mA	$V_O < 0$ or $V_O > V_{CC}$
Continuous output current	$I_O$	±50	mA	$V_O = 0$ to $V_{CC}$
$V_{CC}$ , GND current / pin	$I_{CC}$ or $I_{GND}$	±100	mA	
Maximum power dissipation at $T_a = 55^\circ C$ (in still air) <sup>3</sup>	$P_T$	1	W	TSSOP
Storage temperature	Tstg	−65 to 150	°C	

Notes: Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute maximum rated conditions for extended periods may affect device reliability.

1. The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.
2. This value is limited to 4.6 V maximum.
3. The maximum package power dissipation is calculated using a junction temperature of 150°C and a board trace length of 750 mils.

### Recommended Operating Conditions

Item	Symbol	Min	Max	Unit	Conditions
Supply voltage	$V_{CC}$	2.3	3.6	V	
Input voltage	$V_I$	0	$V_{CC}$	V	
Output voltage	$V_O$	0	$V_{CC}$	V	
High level output current	$I_{OH}$	—	−12	mA	$V_{CC} = 2.3$ V
		—	−12		$V_{CC} = 2.7$ V
		—	−24		$V_{CC} = 3.0$ V
Low level output current	$I_{OL}$	—	12	mA	$V_{CC} = 2.3$ V
		—	12		$V_{CC} = 2.7$ V
		—	24		$V_{CC} = 3.0$ V
Input transition rise or fall rate	$\Delta t / \Delta v$	0	10	ns / V	
Operating temperature	$T_a$	−40	85	°C	

Note: Unused control inputs must be held high or low to prevent them from floating.


---

---

## HD74ALVC16836

---

### Logic Diagram



---

## HD74ALVC16836

---

### Electrical Characteristics (Ta = -40 to 85°C)

Item	Symbol	V <sub>cc</sub> (V)	Min	Max	Unit	Test Conditions
Input voltage	V <sub>IH</sub>	2.3 to 2.7	1.7	—	V	
		2.7 to 3.6	2.0	—		
	V <sub>IL</sub>	2.3 to 2.7	—	0.7		
		2.7 to 3.6	—	0.8		
Output voltage	V <sub>OH</sub>	2.3 to 3.6	V <sub>cc</sub> - 0.2	—	V	I <sub>OH</sub> = -100 µA
		2.3	2.0	—		I <sub>OH</sub> = -6 mA, V <sub>IH</sub> = 1.7 V
		2.3	1.7	—		I <sub>OH</sub> = -12 mA, V <sub>IH</sub> = 1.7 V
		2.7	2.2	—		I <sub>OH</sub> = -12 mA, V <sub>IH</sub> = 2.0 V
		3.0	2.4	—		I <sub>OH</sub> = -12 mA, V <sub>IH</sub> = 2.0 V
		3.0	2.0	—		I <sub>OH</sub> = -24 mA, V <sub>IH</sub> = 2.0 V
	V <sub>OL</sub>	2.3 to 3.6	—	0.2		I <sub>OL</sub> = 100 µA
		2.3	—	0.4		I <sub>OL</sub> = 6 mA, V <sub>IL</sub> = 0.7 V
		2.3	—	0.7		I <sub>OL</sub> = 12 mA, V <sub>IL</sub> = 0.7 V
		2.7	—	0.4		I <sub>OL</sub> = 12 mA, V <sub>IL</sub> = 0.8 V
		3.0	—	0.55		I <sub>OL</sub> = 24 mA, V <sub>IL</sub> = 0.8 V
Input current	I <sub>IN</sub>	3.6	—	±5	µA	V <sub>IN</sub> = V <sub>cc</sub> or GND
Off state output current	I <sub>OZ</sub>	3.6	—	±10	µA	V <sub>OUT</sub> = V <sub>cc</sub> or GND
Quiescent supply current	I <sub>CC</sub>	3.6	—	40	µA	V <sub>IN</sub> = V <sub>cc</sub> or GND
	ΔI <sub>CC</sub>	3.0 to 3.6	—	750	µA	V <sub>IN</sub> = one input at (V <sub>cc</sub> - 0.6) V, other inputs at V <sub>cc</sub> or GND

---



---

## HD74ALVC16836

---

### Switching Characteristics (Ta = -40 to 85°C)

Item	Symbol	V <sub>cc</sub> (V)	Min	Typ	Max	Unit	FROM (Input)	TO (Output)	
Maximum clock frequency	f <sub>max</sub>	2.5±0.2	150	—	—	MHz	A	Y	
		2.7	150	—	—				
		3.3±0.3	150	—	—				
Propagation delay time	t <sub>PLH</sub>	2.5±0.2	1.0	—	4.2	ns	A	Y	
	t <sub>PLH</sub>	2.7	—	—	4.2				
	t <sub>PLH</sub>	3.3±0.3	1.0	—	3.6				
	t <sub>PLH</sub>	2.5±0.2	1.3	—	5.0		LE	Y	
	t <sub>PLH</sub>	2.7	—	—	4.9				
	t <sub>PLH</sub>	3.3±0.3	1.3	—	4.2				
	t <sub>PLH</sub>	2.5±0.2	1.4	—	5.5				
	t <sub>PLH</sub>	2.7	—	—	5.2				
	t <sub>PLH</sub>	3.3±0.3	1.4	—	4.5				
Output enable time	t <sub>ZH</sub>	2.5±0.2	1.4	—	5.5	ns	OE	Y	
	t <sub>ZL</sub>	2.7	—	—	5.6				
	t <sub>ZL</sub>	3.3±0.3	1.1	—	4.6				
Output disable time	t <sub>HZ</sub>	2.5±0.2	1.0	—	4.5	ns	OE	Y	
	t <sub>HZ</sub>	2.7	—	—	4.3				
	t <sub>HZ</sub>	3.3±0.3	1.3	—	3.9				
Input capacitance	C <sub>IN</sub>	3.3	—	3.5	—	pF	Control inputs		
		3.3	—	6.0	—		Data inputs		
Output capacitance	C <sub>O</sub>	3.3	—	7.0	—	pF	Outputs		

---

## HD74ALVC16836

---

### Switching Characteristics (Ta = -40 to 85°C) (cont)

Item	Symbol	V <sub>cc</sub> (V)	Min	Typ	Max	Unit	FROM (Input)
Setup time	t <sub>su</sub>	2.5±0.2	1.4	—	—	ns	Data before CLK↑
		2.7	1.7	—	—		
		3.3±0.3	1.5	—	—		
		2.5±0.2	1.2	—	—		Data before $\overline{LE} \uparrow$
		2.7	1.6	—	—		CLK "H"
		3.3±0.3	1.3	—	—		
		2.5±0.2	1.4	—	—		Data before $\overline{LE} \uparrow$
		2.7	1.5	—	—		CLK "L"
		3.3±0.3	1.2	—	—		
Hold time	t <sub>h</sub>	2.5±0.2	0.9	—	—	ns	Data after CLK↑
		2.7	0.9	—	—		
		3.3±0.3	0.9	—	—		
		2.5±0.2	1.1	—	—		Data after $\overline{LE} \uparrow$
		2.7	1.1	—	—		CLK "H" or "L"
		3.3±0.3	1.1	—	—		
Pulse width	t <sub>w</sub>	2.5±0.2	3.3	—	—	ns	$\overline{LE}$ "L"
		2.7	3.3	—	—		
		3.3±0.3	3.3	—	—		
		2.5±0.2	3.3	—	—		CLK "H" or "L"
		2.7	3.3	—	—		
		3.3±0.3	3.3	—	—		


---

---

## HD74ALVC16836

---

### Test Circuit




---


## HD74ALVC16836

---

### Waveforms – 1




### Waveforms – 2



## HD74ALVC16836

### Waveforms – 3




---

## HD74ALVC16836

---

### Package Dimensions

Unit : mm



---

---

## Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

**Hitachi, Ltd.**

Semiconductor & Integrated Circuits.

Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL	NorthAmerica	: <a href="http://semiconductor.hitachi.com/">http://semiconductor.hitachi.com/</a>
	Europe	: <a href="http://www.hitachi-eu.com/hel/ecg">http://www.hitachi-eu.com/hel/ecg</a>
	Asia (Singapore)	: <a href="http://www.has.hitachi.com.sg/grp3/sicd/index.htm">http://www.has.hitachi.com.sg/grp3/sicd/index.htm</a>
	Asia (Taiwan)	: <a href="http://www.hitachi.com.tw/E/Product/SICD_Frame.htm">http://www.hitachi.com.tw/E/Product/SICD_Frame.htm</a>
	Asia (HongKong)	: <a href="http://www.hitachi.com.hk/eng/bo/grp3/index.htm">http://www.hitachi.com.hk/eng/bo/grp3/index.htm</a>
	Japan	: <a href="http://www.hitachi.co.jp/Sicd/idx.htm">http://www.hitachi.co.jp/Sicd/idx.htm</a>

**For further information write to:**

Hitachi Semiconductor (America) Inc. 179 East Tasman Drive, San Jose, CA 95134 Tel: <1> (408) 433-1990 Fax: <1>(408) 433-0223	Hitachi Europe GmbH Electronic components Group Dornacher Straße 3 D-85622 Feldkirchen, Munich Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00 Hitachi Europe Ltd. Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 778322	Hitachi Asia Pte. Ltd. 16 Collyer Quay #20-00 Hitachi Tower Singapore 049318 Tel: 535-2100 Fax: 535-1533 Hitachi Asia Ltd. Taipei Branch Office 3F, Hung Kuo Building, No.167, Tun-Hwa North Road, Taipei (105) Tel: <886> (2) 2718-3666 Fax: <886> (2) 2718-8180	Hitachi Asia (Hong Kong) Ltd. Group III (Electronic Components) 7/F., North Tower, World Finance Centre, Harbour City, Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong Tel: <852> (2) 735 9218 Fax: <852> (2) 730 0281 Telex: 40815 HITEC HX
--	---	--	--