

TOSHIBA

HN3G01J

TOSHIBA TRANSISTOR SILICON N CHANNEL JUNCTION TYPE FET SILICON NPN EPITAXIAL TYPE TRANSISTOR

HN3G01J

HIGH FREQUENCY AMPLIFIER APPLICATIONS

AM HIGH FREQUENCY AMPLIFIER APPLICATIONS

AUDIO FREQUENCY AMPLIFIER APPLICATIONS

MAXIMUM RATINGS (Ta = 25°C)
Q1

CHARACTERISTIC	SYMBOL	RATING	UNIT
Gate-Drain Voltage	V _{GDS}	-20	V
Gate Current	I _G	10	mA

Q2


CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CBO}	60	V
Collector-Emitter Voltage	V _{CEO}	50	V
Emitter-Base Voltage	V _{EB0}	5	V
Collector Current	I _C	150	mA
Base Current	I _B	30	mA

COMMON RATINGS


CHARACTERISTIC	SYMBOL	RATING	UNIT
Power Dissipation	P*	200	mW
Junction Temperature	T _j	125	°C
Storage Temperature Range	T _{stg}	-55~125	°C

* Total Rating


PIN ASSIGNMENT (TOP VIEW)



Marking



Unit in mm




● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

● The information contained herein is subject to change without notice.

961001EAA2



ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Q1

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current	I_{GSS}	$V_{GS} = -15V, V_{DS} = 0$	—	—	-1.0	nA
Gate-Drain Breakdown Voltage	$V_{(BR)GDS}$	$V_{DS} = 0, I_G = -100\mu A$	-20	—	—	V
Drain Current	I_{DSS} (Note)	$V_{DS} = 5V, V_{GS} = 0$	6	—	32	mA
Gate-Source Cut-off Voltage	$V_{GS(OFF)}$	$V_{DS} = 5V, I_D = 10\mu A$	—	—	-2.5	V
Forward Transfer Admittance	$ Y_{fs} $	$V_{DS} = 5V, V_{GS} = 0, f = 1kHz$	15	25	—	mS
Input Capacitance	C_{iss}	$V_{DS} = 5V, V_{GS} = 0, f = 1MHz$	—	7.5	10	pF
Reverse Transfer Capacitance	C_{rss}	$V_{DG} = 5V, I_D = 0, f = 1MHz$	—	2	3	pF

Note : I_{DSS} Classification

GR : 6~12mA, BL : 10~20mA, V : 16~32mA

(G)

(L)







(V)



()... I_{DSS} Rank Marking

Q2




CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB} = 60V, I_E = 0$	—	—	0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$	—	—	0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = 6V, I_C = 2mA$	120	—	400	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 100mA, I_B = 10mA$	—	0.1	0.25	V
Transition Frequency	f_T	$V_{CE} = 10V, I_C = 1mA$	60	—	—	MHz
Collector Output Capacitance	C_{ob}	$V_{CB} = 10V, I_E = 0, f = 1MHz$	—	2.0	3.5	pF

* Q1 CHARACTERISTICS





* Q2 CHARACTERISTIC



* Q1, Q2 COMMON CHARACTERISTICS

