




**PI3B16209
PI3B162209 (25Ω)**

3.3V, 18-Bit Bus Exchange Switch

Product Features

- Near-zero propagation delay
- 5Ω switches connect inputs to outputs
- Fast Switching speed - 5ns (max.)
- Operating Range: 3.0V to 3.6V
- Industrial operating temperature: -40°C to +85°C
- Packages available:
 - 48-pin 240-mil wide thin plastic TSSOP (A)
 - 48-pin 300-mil wide plastic SSOP (V)

Logic Block Diagram



Truth Table

| Function | S2 | S1 | S0 | A1 | A2 |
|--------------------|----|----|----|----|----|
| Disconnect | L | L | L | Z | Z |
| A1 to B1 | L | L | H | B1 | Z |
| A1 to B2 | L | H | L | B2 | Z |
| A2 to B1 | L | H | H | Z | B1 |
| A2 to B2 | H | L | L | Z | B2 |
| Disconnect | H | L | H | Z | Z |
| A1 to B1, A2 to B2 | H | H | L | B1 | B2 |
| A1 to B2, A2 to B1 | H | H | H | B2 | B1 |

Note:

- H = High Voltage Level
- L = Low Voltage Level
- Z = High Impedance


Product Description

Pericom Semiconductor's PI3B series of logic circuits are produced in the Company's advanced 0.35 micron CMOS technology.

The PI3B16209 and PI3B162209 are 3.3 volt, 18-bit bus exchange switches designed with a low ON resistance (5Ω) allowing inputs to be connected directly to outputs. The devices operate as an 18-bit bus switch or as a 9-bit exchanger, providing data exchange between the four signal ports via the data select pins (S0-S2).

The PI5C162209 device has a built-in 25-ohm series resistor to reduce noise resulting from reflections, thus eliminating the need for an external terminating resistor.

Product Pin Configuration



Product Pin Description

| Pin Name | I/O | Description |
|----------|-----|---------------|
| S0-S2 | I | Select Inputs |
| xAx | I/O | Bus A |
| xBx | I/O | Bus B |



Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

| | |
|--|-----------------|
| Storage Temperature | -65°C to +150°C |
| Ambient Temperature with Power Applied | -0°C to +85°C |
| Supply Voltage Range | -0.5V to +4.6V |
| DC Input Voltage | -0.5V to +4.6V |
| DC Output Current | 120 mA |
| Power Dissipation | 0.5W |

Note:

Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

DC Electrical Characteristics (Over the Operating Range, TA = -40°C to +85°C, VCC = 3.0V to 3.6V)

| Parameters | Description | Test Conditions ⁽¹⁾ | Min. | Typ ⁽²⁾ | Max. | Units | |
|------------------|-------------------------------------|---|--------|--------------------|------|-------|---|
| V _{IH} | Input HIGH Voltage | Guaranteed Logic HIGH Level | 2.0 | — | — | V | |
| V _{IL} | Input LOW Voltage | Guaranteed Logic LOW Level | -0.5 | — | 0.8 | V | |
| I _{IH} | Input HIGH Current | V _{CC} = Max., V _{IN} = V _{CC} | — | — | ±1 | µA | |
| I _{IL} | Input LOW Current | V _{CC} = Max., V _{IN} = GND | — | — | ±1 | µA | |
| I _{OZH} | High Impedance Output Current | 0 ≤ A, B ≤ V _{CC} | — | — | ±1 | µA | |
| V _{IK} | Clamp Diode Voltage | V _{CC} = Min., I _{IN} = -18mA | — | -0.7 | -1.2 | V | |
| R _{ON} | Switch On Resistance ⁽³⁾ | V _{CC} = Min., V _{IN} = 0.0V, | 16209 | — | 5 | 8 | Ω |
| | | I _{ON} = 48mA | 162209 | 20 | 28 | 40 | |
| | | V _{CC} = Min., V _{IN} = 2.4V, | 16209 | — | 10 | 15 | Ω |
| | | I _{ON} = 15mA | 162209 | 20 | 35 | 48 | |

Capacitance (TA = 25°C, f = 1 MHz)

| Parameters ⁽⁴⁾ | Description | Test Conditions | Typ | Units |
|---------------------------|-----------------------------|----------------------|-----|-------|
| C _{IN} | Input Capacitance | V _{IN} = 0V | 3 | pF |
| C _{OFF} | A/B Capacitance, Switch Off | V _{IN} = 0V | 14 | pF |
| C _{ON} | A/B Capacitance, Switch On | V _{IN} = 0V | 30 | pF |

Notes:

1. For Max. or Min. conditions, use appropriate value specified under Electrical Characteristics for the applicable device type.
2. Typical values are at V_{CC} = 3.3V, T_A = 25°C ambient and maximum loading.
3. Measured by the voltage drop between A and B pin at indicated current through the switch. ON resistance is determined by the lower of the voltages on the two (A,B) pins.
4. This parameter is determined by device characterization but is not production tested.



Power Supply Characteristics

| Parameters | Description | Test Conditions ⁽¹⁾ | | Min. | Typ ⁽²⁾ | Max. | Units |
|------------------|---|--|--|------|--------------------|------|------------|
| | | | | | | | |
| I _{CC} | Quiescent Power Supply Current | V _{CC} = Max. | V _{IN} = GND or V _{CC} | | | 10 | μA |
| ΔI _{CC} | Supply Current per Input @ TTL HIGH | V _{CC} = Max. | V _{IN} = 3.0V ⁽³⁾ | | | 750 | μA |
| I _{CCD} | Supply Current per Input per MHz ⁽⁴⁾ | V _{CC} = Max. A and B Pins Open \overline{BE} = GND Control Input Toggling 50% Duty Cycle | | | | 0.25 | mA/ MHz |

Notes:

1. For Max. or Min. conditions, use appropriate value specified under Electrical Characteristics for the applicable device.
2. Typical values are at V_{CC} = 3.3V, +25°C ambient.
3. Per TTL driven input (control input only); A and B pins do not contribute to I_{CC}.
4. This current applies to the control inputs only and represent the current required to switch internal capacitance at the specified frequency. The A and B inputs generate no significant AC or DC currents as they transition. This parameter is not tested, but is guaranteed by design.

Switching Characteristics over Operating Range

| Parameters | Description | Conditions ⁽¹⁾ | Com. | | Units |
|------------------|---|---|--------|------|-------|
| | | | Min. | Max. | |
| t _{PLH} | Propagation Delay ^(2,3) | C _I = 50pF R _I = 500Ω | 16209 | 0.25 | ns |
| t _{PHL} | A _X to B _X , B _X to A _X | | 162209 | 1.25 | |
| t _{PZH} | Bus Enable Time | C _I = 50pF, R _L = 500Ω, R = 500Ω | 1 | 4.5 | |
| t _{PZL} | \overline{BE} to A _X or B _X | | | | |
| t _{PHZ} | Bus Disable Time | | 1 | 5 | |
| t _{PLZ} | \overline{BE} to A _X or B _X | | | | |

Notes:

1. See test circuit and waveforms.
2. This parameter is guaranteed but not tested on Propagation Delays.
3. The bus switch contributes no propagational delay other than the RC delay of the ON resistance of the switch and the load capacitance. The time constant for the switch alone is of the order of 0.25 ns for 50 pF load. Since this time constant is much smaller than the rise/fall times of typical driving signals, it adds very little propagational delay to the system. Propagational delay of the bus switch when used in a system is determined by the driving circuit on the driving side of the switch and its interaction with the load on the driven side.