



**PI7C8148B
2-PORT PCI-to-PCI BRIDGE
PLX PCI6152 COMPARISON**

FEATURE COMPARISON: PI7C8148B vs. PLX PCI6152

Features:

Feature	Pericom PI7C8148B	PLX PCI6152
<u>Interfaces</u> <ul style="list-style-type: none"> ▪ Complies with the following specifications: <i>PCI Local Bus Specification</i> <i>PCI-to-PCI Bridge Architecture Specification</i> ▪ 3.3V and 5V signaling environments ▪ 66MHz capable ▪ Asynchronous Mode support ▪ Concurrent primary and secondary bus operations 	Revision 2.2 Revision 1.1 yes yes yes yes	Revision 2.1 Revision 1.1 no (3.3V w/5V tolerance) yes no yes
<u>Memory Buffer Architecture</u> <ul style="list-style-type: none"> ▪ <i>Dynamic Prefetching Control</i> 	yes	no
<u>Bus Arbitration</u> <ul style="list-style-type: none"> ▪ Programmable internal arbiter for the secondary bus with support for up to 4 external masters 	yes	yes
<u>IEEE 1149.1 JTAG port</u> <ul style="list-style-type: none"> ▪ Available boundary scan testing 	no	no
<u>Compact PCI Hot Swap</u> <ul style="list-style-type: none"> ▪ Hot Swap Friendly Support 	yes	yes
<u>Packaging</u> <ul style="list-style-type: none"> ▪ 160-pin PBGA ▪ Extended commercial temp range: 0°C to 85°C 	yes yes	yes no (0°C to 70°C)

Pin differences (160-pin PBGA):

pin number	Pericom PI7C8148B	PLX PCI6152
N7	SCAN_EN	NAND_O
P7	SCAN_TM#	GOZ_L

SCAN_TM# (P7) should be pulled HIGH for normal operation (same as the PLX solution).
SCAN_EN (N7) becomes an output when SCAN_TM# is pulled HIGH.

Register differences:

	Pericom PI7C8148B	PLX PCI6152
Vendor ID	12D8h	3388h
Device ID	8140h	0021h



PERFORMANCE COMPARISON: PI7C8148B vs. PLX PCI6152

The performance data was measured using an in-house evaluation board slotted into an off-the-shelf motherboard. Fast Ethernet (100Mbit LAN) Cards reside in each of the 4 PCI slots on the secondary bus of the evaluation board. In each comparison, the hardware and software remain constant. The only item changed is the bridge on the evaluation board. Two different sets of hardware were used, and the description of each fixture is listed. In each test setup, a PCI exerciser program is used to generate traffic or write packets from the PCI Fast Ethernet card to memory and then read back from memory to the PCI Fast Ethernet card.

TEST CASE 1

Motherboard: SuperMicro P3TDLE
 Chipset: ServerWorks ServerSet III LE
 Processor: Intel PIII 800
 Memory: 512MB
 Video: S3 TrioV64/DX
 Other PCI Devices: No other PCI devices active

A Fast Ethernet card running full duplex is slotted in each of the 4 PCI slots on the evaluation board.

Results: Transfer rate measured in Megabits per second

Card Number	Pericom PI7C8148B	PLX PCI6152
LAN Card 1	42.61 – 46.99 Mb/s	19.84 – 22.07 Mb/s
LAN Card 2	84.33 – 89.14 Mb/s	66.17 – 70.66 Mb/s
LAN Card 3	46.19 – 48.12 Mb/s	18.70 – 22.14 Mb/s
LAN Card 4	84.81 – 89.01 Mb/s	67.14 – 70.40 Mb/s

TEST CASE 2

Motherboard: MSI GNB Max
 Chipset: Intel E7205
 Processor: Intel P4 2.4GHz
 Memory: 256MB
 Video: nVidia GeForce 2 MX-400
 Other PCI Devices: No other PCI devices active

A Fast Ethernet card running full duplex is slotted in each of the 4 PCI slots on the evaluation board.

Results: Transfer rate measured in Megabits per second

Card Number	Pericom PI7C8148B	PLX PCI6152
LAN Card 1	27.16 – 31.30 Mb/s	21.50 – 28.55 Mb/s
LAN Card 2	26.70 – 32.78 Mb/s	23.02 – 28.29 Mb/s
LAN Card 3	27.54 – 32.18 Mb/s	22.05 – 27.61 Mb/s
LAN Card 4	27.63 – 32.13 Mb/s	23.09 – 27.05 Mb/s