

Internet Office UPS System

All-in-one SOHO solution



Cisco
Compatible

Cisco Systems
Technology
Developer
Partner

Model #: INTERNETOFFICE700

- ▶ 6 outlets (3 UPS/surge, 3 surge-only)
- ▶ Single-line tel/DSL surge protection
- ▶ USB port and FREE software (Web download) facilitate unattended shutdown
- ▶ \$150,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's INTERNETOFFICE700 standby UPS system offers surge suppression and long-lasting battery support for personal computers, internetworking equipment and other sensitive electronics. Internal UPS circuits support entry-level PC systems for up to 45 minutes during power failures and brownouts so that connected equipment can be shut down without data loss. Offers complete desktop power protection in an attractive gray tower configuration. Includes 3 battery-supported outlets for computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support. USB port enables optional unattended system shutdown without data loss in the case of extended power failure; USB cable included. PowerAlert software available via FREE download from www.tripplite.com. Built-in RJ11 phone suppression jacks protect modem, fax machine, cordless phone or other peripheral with a standard single-line tel/DSL phone connection. Built-in audible alarm and 3 front panel LEDs indicate line power status, battery power status and battery low/replace status. 700VA/425W power handling ability supports entry-level PCs, network workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Offers 5 min. battery runtime with a full load of 700VA and 17 min. with a half load of 350VA. Supports user battery replacement via built-in access panel. 2-year warranty. \$150,000 connected equipment insurance (USA & Canada only).

KEY BUYING POINTS

- INTERNETOFFICE700 standby UPS system offers UPS battery support, plus complete AC and tel/DSL line surge suppression
- Supports entry-level PC systems for up to 45 min. during brownouts and power failures to enable a safe system shutdown
- Supports a max load of 700VA/425W for 5 min.
- Supports a half load of 350VA/215W for 17 min.
- Supplies battery-derived AC output during brownouts starting at 99V, user adjustment allows fine tuning of brownout response to any setting from 83V to 99V
- Attractive gray tower configuration
- Includes 3 battery-supported outlets plus 3 additional surge suppression-only outlets, and 6-ft. AC line cord (all NEMA 5-15)
- USB port enables unattended shutdown without data loss during extended power failures; includes USB cable
- Built-in USB port supports on battery, low battery and power restored messaging
- USB interface supports timed inverter shutoff after unattended shutdown
- PowerAlert software available via FREE download from www.tripplite.com
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them, and rebooting completely locked computers by automatically switching UPS power off and back on again
- Built-in phone suppression jacks protect modem, fax machine or other peripheral with a dialup or DSL line phone connection (2 wire, 1 line, 260-volt clamping)
- Built-in audible alarm and 3 front panel LEDs indicate line power, battery power and battery low/replace status
- 700VA/425W power handling ability supports a variety of computer, internetworking, telecom and consumer electronics equipment
- Supports hot-swap battery replacement via built-in access panel
- Compatible with 120V/60Hz applications for USA, Canada, Mexico and more
- 2-year manufacturer's warranty
- \$150,000 connected equipment insurance (USA & Canada only)

TYPICAL APPLICATIONS

- Entry-level PCs, networked workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems.

OPTIONS & ACCESSORIES

- USB Hubs-accessories: [U202-004-R](#), [U205-004-R](#), [U022-010](#)
- Dataline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Wallmount Bracket: [UPSWM](#)
- Circuit Tester: [CT120](#)
- Watchdog software: [WATCHDOGSW](#)
- Extended warranties: 3 Year [WEXT3-INTERNET](#), 5 Year [WEXT5-INTERNET](#)

PACKAGE INCLUDES

- INTERNETOFFICE700 Standby UPS System
- USB and phone cable
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:	Small tower standby UPS protects PCs, network workstations and other sensitive electronics from blackouts, surges and line noise. Maintains AC output during blackouts and brownouts starting at 99V. Includes USB monitoring port with cabling, TEL / DSL surge suppression, surge only outlets and LED indicators. PowerAlert software available FREE via Web download.
Voltage compatibility:	120V AC
Frequency compatibility:	60Hz

OUTPUT

Output volt amp capacity (VA):	700
Output watt capacity (watts):	425
Output nominal voltage:	120V AC
Output voltage regulation:	BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation:	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type:	6 NEMA 5-15R

INPUT

Maximum input amps:	12A / 1440 watts
Input connection type:	NEMA 5-15P
Input cord length:	6 ft., 14 gauge
Recommended electrical service:	15A 120V

BATTERY

Full load runtime:	5 minutes (700VA)
Half load runtime:	17 minutes (350VA)
DC system voltage:	12V DC
Typical battery lifespan:	3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

Replacement Battery Cartridge: RBC51

LEDS ALARMS & SWITCHES

Front panel LEDs: 3 front panel LEDs indicate line power status, battery power status and battery low/replace status

Alarms: Audible alarm with 15-second delay sounds to indicate loss of utility power. Alarm can be silenced by pressing front panel alarm cancel button. Once silenced, alarm will re-sound when approximately 2 minutes runtime remain.

Switches: Includes 2 front panel switches—one main on/off power switch and one dual function "alarm cancel" / "self test" button

SURGE / NOISE SUPPRESSION

AC surge suppression: 480 joules

AC suppression response time: Instantaneous

Dataline suppression: Tel/DSL

EMI / RFI AC noise suppression: Yes

PHYSICAL

Shipping weight (lbs): 21

Shipping weight (kg): 9.5

Unit weight (lbs): 19

Unit weight (kg): 8.6

Unit Dimensions (HWD/in): 10.75 x 5.25 x 7.25

Unit Dimensions (HWD/cm): 27.3 x 13.3 x 18.4

Material of construction: PVC

Form factors supported: Tower

Cooling method: Convection

Battery Access: Battery access door allows user replacement of UPS batteries. Hot-swappable battery replacement supported.

ENVIRONMENTAL

Operating Temperature: +32 to +104 degrees Fahrenheit
0 to +40 degrees Celsius

Storage Temperature: +5 to +122 degrees Fahrenheit
-15 to +50 degrees Celsius

Relative Humidity: 0 to 95%, non-condensing

COMMUNICATIONS

Network monitoring port: USB

Software and cabling included: USB cabling included, PowerAlert software available for free download at www.tripplite.com

WatchDog compatibility: Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode: 2-4 milliseconds

Low voltage transfer to battery power: Switches to battery power as line voltage decreases to 99 volts or less. Resets to line power mode as line voltage increases to 104V or higher. Back panel potentiometer allows users to adjust brownout response to any voltage between 83 and the 99 volt factory preset.

High voltage transfer to battery power: Yes

CERTIFICATIONS

Certifications: Tested to UL1778 (USA), Tested to CSA (Canada), FCC Class B (emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications), SASO (Saudi Arabia)

WARRANTY

Optional coverage: 3-5 year warranties, plus next day and on-site warranty coverage available. Contact Tripp Lite for additional information.

Product warranty: 2-year product warranty

Connected equipment insurance (USA and Canada Only): \$150,000 connected equipment insurance (USA & Canada only)

SPECIAL FEATURES

Cold Start: Yes, inverter can be "cold started" to enable temporary AC output during a power failure

Appearance: Attractive gray tower UPS

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.