

Internet Office UPS System

Affordable full system protection for PCs and workstations



Cisco
Compatible

Cisco Systems Technology
Developer Partner

Model #: INTERNET350U

- ▶ Ultra-compact standby UPS offers complete protection for PC and workstations
- ▶ 6 widely spaced outlets (3 UPS/surge, 3 surge-only)
- ▶ USB port with HID protocol support, cabling and included PowerAlert monitoring software
- ▶ Single line TEL/DSL modem suppression
- ▶ \$100,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

DESCRIPTION

Tripp Lite's INTERNET350U standby UPS offers complete protection for PCs, workstations and other sensitive electronics in an attractive ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery supported AC output during brownouts and blackout conditions. 6 widely spaced output receptacles accommodate large transformer plugs without blocking outlets. 3 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power. 3 additional outlets with surge suppression-only are ideal for printers and other accessories not requiring battery support. Single line telephone suppression jacks protect a single directly connected modem, fax machine, cordless phone or other peripheral on a single standard dialup or DSL phone line connection. HID compliant USB port with PowerAlert monitoring software and cabling enables safe unattended system shutdown in the case of extended power failure. HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 350VA / 180 watt power handling ability supports entry-level PCs for up to 12 minutes during power failures. 2 year warranty. \$100,000 connected equipment Insurance (USA & Canada Only).

KEY BUYING POINTS

- INTERNET350U standby UPS offers complete protection from blackouts, brownouts and surges on both AC and TEL/DSL line connections
- 6 widely spaced outlets accommodate large transformer plugs without blocking outlets
- 3 battery supported outlets protect computer, monitor and vital system peripherals, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts and brownouts
- 350VA / 180 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 12 minutes during blackout conditions
- Built-in single line TEL/DSL line surge suppression protects modems, fax machines or cordless phones on a single phone line connection
- USB port, PowerAlert software and cabling offer safe unattended shutdown without data loss during extended outages
- HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.
- Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
- Space saving, ultra-compact housing fits almost anywhere

TYPICAL APPLICATIONS

- Basic PCs for home / home-office use, network workstations, audio/video equipment, home entertainment systems and other sensitive electronic devices.

OPTIONS & ACCESSORIES

- Watchdog software: [WATCHDOGSW](#)
- USB Hubs: [U222-004-R](#), [U202-004-R](#), [U203-004-R](#), [U205-004-R](#)
- USB Extension Cables: [U004-006](#), [U004-006-R](#), [U004-010](#), [U004-010-R](#), [U005-010I](#)
- Dataline protectors: [DNET1](#) [DTEL2](#), [DCATV](#)
- Circuit Tester: [CT120](#)
- Extended warranties: 3 Year [WEXT3-INTERNET](#), 5 Year [WEXT5-INTERNET](#)

PACKAGE INCLUDES

- INTERNET350U UPS System
- PowerAlert Software & USB cable
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview: Ultra-compact standby UPS protects PCs, network workstations and other sensitive electronic equipment from blackouts, surges and line noise. Maintains AC output during blackouts and brownouts starting at 98V. Includes HID compliant USB monitoring port with cabling, TEL / DSL line surge suppression, surge only outlets and LED indicators. PowerAlert software included.

Voltage compatibility: 120VAC

Frequency compatibility: 60Hz

OUTPUT

Output volt amp capacity (VA): 350

Output watt capacity (watts): 180

Output nominal voltage: 120VAC

Output voltage regulation: BATTERY MODE: PWM sine wave output 115V +/-5%

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz

Outlet quantity / type: 6 NEMA 5-15R

INPUT

Maximum input amps: 12A / 1440 watts

Input connection type: NEMA 5-15P space saving right-angle plug

Input cord length: 6 ft., 16 gauge

Recommended electrical service: 15A 120V

BATTERY

Full load runtime: 2.5 minutes (350VA)

Half load runtime: 8 minutes (175VA)

DC system voltage: 12 VDC

Typical battery lifespan: 3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

LEDS ALARMS & SWITCHES

Front panel LEDs: 2 LEDs indicate line power, battery power status

Alarms: Audible alarm beeps at regular intervals to indicate battery backup operation. Alarm also

	sounds during self-test operation.
Switches:	Combination power off / on / self-test push button switch
SURGE / NOISE SUPPRESSION	
AC surge suppression:	380 joules
AC suppression response time:	Instantaneous
Dataline suppression:	Tel/DSL
EMI / RFI AC noise suppression:	Yes, >40dB @ 1 MHz
PHYSICAL	
Shipping weight (lbs):	10
Shipping weight (kg):	4.5
Unit weight (lbs):	7.7
Unit weight (kg):	3.5
Unit Dimensions (HWD/in):	3 x 10.5 x 5
Unit Dimensions (HWD/cm):	7.6 x 26.7 x 12.7
Shipping Dimensions (HWD/in):	4.5 x 12.5 x 7.75
Shipping Dimensions (HWD/cm):	11.4 x 31.8 x 19.7
Material of construction:	ABS
Form factors supported:	Ultra-compact
Battery Access:	Hot-swappable batteries are accessible via battery door
ENVIRONMENTAL	
Operating Temperature:	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing
Line mode BTU/hr. (Max.):	15.7
Battery mode BTU/hr. (Max.):	53.2
COMMUNICATIONS	
Network monitoring port:	HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.
Software and cabling included:	Includes USB cable and PowerAlert UPS monitoring software
WatchDog compatibility:	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	Switches to battery power as line voltage decreases to 98 volts or less. Resets back to line power mode as line voltage increases to 103V or higher.
High voltage transfer to battery power:	Switches to battery power as line voltage increases to 147V or higher. Resets back to line power as line voltage decreases to 143V or less.
CERTIFICATIONS	
Certifications:	Tested to UL1778 (USA), Tested to CSA (Canada), Class B (Emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)
WARRANTY	
Optional coverage:	Optional 3 and 5 year on site or factory warranties available for select opportunities, contact Tripp Lite for more information

Product warranty:	2 years
Connected equipment insurance (USA and Canada Only):	\$100,000 connected equipment insurance (USA and Canada only)
SPECIAL FEATURES	
Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive black ultra-compact housing

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.