

International **IR** Rectifier

Data Sheet No. PD60196

IRIS4009(K)

INTEGRATED SWITCHER


Features

- Primary current mode control, and secondary voltage mode control
- Vcc Over-voltage protection (latched)
- Over-current & over-temperature protection
- Quasi resonant, variable frequency operation
- 5 pin TO-220 and TO-262
- 8.0Ω Rds(on) max/ 650V MOSFET
- Fully Characterized Avalanche Energy


Description

The IRIS4009(K) is a dual mode voltage and current controller combined with a MOSFET in a single package. The IRIS4009(K) is designed for use in universal and single input AC/DC and DC/DC switching power supplies and is capable of powers up to 30W for a universal line input. The device can operate in either a quasi-resonant or Pulse Ratio Control (PRC) mode, and thereby variable frequency operation.

Packages



Typical Connection Diagram



IRIS4009(K)

International
IR Rectifier

Absolute Maximum Ratings


Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to terminals stated, all currents are defined positive into any lead. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions.

Symbol	Definition	Terminals	Max. Ratings	Units	Note
I _{Dpeak}	Peak drain current	3-1	3.9	A	Single pulse
I _{Dmax}	Maximum switching current	3-1	1.5		V ₂₋₃ = 0.78V T _c =25°C
E _{AS}	Single pulse avalanche energy	3-1	100	mJ	V _{dd} =50V, L=20mH, G=12V, I _{pk} =1.5A
V _{CC}	Power supply voltage	4-3	35	V	
V _{TH}	OCP/FB terminal voltage	5-2	6		
PD1	Power dissipation for MOSFET	3-1	62.5	W	With infinite heatsink
			1.1		Without heatsink
PD2	Power dissipation for control part (MIC)	4-2	0.8		Specified by V _{IN} x I _{IN}
R _{thJC}	Thermal resistance, junction to case	—	2.0	°C/W	
T _J	Junction temperature	—	-40-125	°C	
T _S	Storage temperature	—	-40-125		
T _f	Internal frame temperature in operation	—	-20-125		Refer to recommended operating temperature
T _{OP}	Ambient operating temperature	—	-20-125		
T _L	Lead temp. (soldering, 10 seconds)	—	300		

Recommended Operating Conditions

Time for input of quasi resonant signals.

For the Quasi resonant signal inputted to the V_{DCP/FB} terminal at the time of quasi resonant operation, the signal should be wider than T_{th(2)}



Electrical Characteristics (for Control IC)

V_{CC} = 18V, (T_A = 25°C) unless otherwise specified.

Symbol	Definition	Min.	Typ.	Max.	Units	Test Conditions
V _{CCUV+}	V _{CC} supply undervoltage positive going threshold	14.4	16	17.6	V	
V _{CCUV-}	V _{CC} supply undervoltage negative going threshold	9	10	11		
I _{QCCUV}	UVLO mode quiescent current	—	—	100	µA	V _{CC} < V _{CCUV+}
I _{QCC}	Quiescent operating V _{CC} supply current	—	—	30	mA	
T _{OFF/(MAX)}	Maximum OFF time	40	—	60	µsec	
T _{TH(2)}	Minimum input pulse width for quasi resonant signals	—	—	1.0		
T _{OFF/(MIN)}	Minimum OFF time	—	—	1.5		
V _{TH(1)}	OCP/FB terminal threshold voltage 1	0.68	0.73	0.78	V	
V _{TH(2)}	OCP/FB terminal threshold voltage 2	1.3	1.45	1.6		
I _{OCP/FB}	OCP/FB terminal sink current	1.1	1.35	1.7	mA	
V _{CC(OVP)}	V _{CC} overvoltage protection limit	20.5	22.5	24.5	V	
I _{CC(LA)}	Latch circuit holding current	—	—	400	µA	
V _{CC(LaOFF)}	Latch circuit reset voltage	6.6	—	8.4	V	
T _{J(TSD)}	Thermal shutdown activation temperature	140	—	—	°C	

Electrical Characteristics (for MOSFET)


(T_A = 25°C) unless otherwise specified.


Symbol	Definition	Min.	Typ.	Max.	Units	Test Conditions
V _{DSS}	Drain-to-source breakdown voltage	650	—	—	V	
I _{DSS}	Drain leakage current	—	—	300	µA	V _{DS} =520V, V _{CC} =0V T _j =125°C
R _{D(S(ON))}	On-resistance	—	—	8.0	Ω	V ₃₋₁ =10V, I _D =0.85A
t _r	Rise time (10% to 90%)	—	—	120	ns	
T _{Hj-C}	Thermal resistance	—	—	2.0	°C/W	Between junction and case

IRIS4009(K)

International
IR Rectifier

Block Diagram




Lead Assignments		Pin #	Symbol	Description
		1	S	MOSFET Source terminal
		2	Ground	Ground terminal
		3	D	MOSFET Drain terminal
		4	Vcc	Control circuit supply voltage
		5	OCP/FB	Overcurrent detection, and Voltage mode control feedback signal

Other Functions

O.V.P. – Overvoltage Protection Circuit
T.S.D. – Thermal Shutdown Circuit


Case outline



IRIS4009(K)

International
IR Rectifier

Case outline



International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas Street, El Segundo, California 90245 Tel: (310) 252-7105
Data and specifications subject to change without notice. 12/3/2001