


# SEMIX 353GB126HD



SEMIX<sup>®</sup> 3

## Trench IGBT Modules

### SEMIX 353GB126HD

Preliminary Data

#### Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$  with positive temperature coefficient
- High short circuit capability

#### Typical Applications







- AC inverter drives
- UPS
- Electronic welders

Absolute Maximum Ratings		$T_c = 25^\circ\text{C}$ , unless otherwise specified		
Symbol	Conditions	Values		Units
<b>IGBT</b>				
$V_{CES}$		1200		V
$I_C$	$T_c = 25 (80)^\circ\text{C}$	360 (260)		A
$I_{CRM}$	$t_p = 1 \text{ ms}$	450		A
$V_{GES}$		$\pm 20$		V
$T_{vj}, (T_{stg})$	$T_{OPERATION} \leq T_{stg}$	- 40 ... + 150 (125)		$^\circ\text{C}$
$V_{isol}$	AC, 1 min.	4000		V
<b>Inverse diode</b>				
$I_F$	$T_c = 25 (125)^\circ\text{C}$	320 (220)		A
$I_{FRM}$	$t_p = 1 \text{ ms}$	450		A
$I_{FSM}$	$t_p = 10 \text{ ms}; \text{sin.}; T_j = 25^\circ\text{C}$	1700		A







Characteristics		$T_c = 25^\circ\text{C}$ , unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
<b>IGBT</b>					
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 9 \text{ mA}$	5	5,8	6,5	V
$I_{CES}$	$V_{GE} = 0, V_{CE} = V_{CES}, T_j = 25 ( )^\circ\text{C}$			0,3	mA
$V_{CE(TO)}$	$T_j = 25 (125)^\circ\text{C}$		1 (0,9)	1,2 (1,1)	V
$r_{CE}$	$V_{GE} = 15 \text{ V}, T_j = 25 (125)^\circ\text{C}$		3,1 (4,9)	4 (5,8)	m $\Omega$
$V_{CE(sat)}$	$I_{Cnom} = 225 \text{ A}, V_{GE} = 15 \text{ V}, T_j = 25 (125)^\circ\text{C}, \text{chip level}$		1,7 (2)	2,1 (2,4)	V
$C_{ies}$	under following conditions		16		nF
$C_{oes}$	$V_{GE} = 0, V_{CE} = 25 \text{ V}, f = 1 \text{ MHz}$		0,9		nF
$C_{res}$			0,7		nF
$L_{CE}$			20		nH
$R_{CC+EE'}$	terminal-chip, $T_c = 25 (125)^\circ\text{C}$		0,7 (1)		m $\Omega$
$t_{d(on)}/t_r$	$V_{CC} = 600 \text{ V}, I_{Cnom} = 225 \text{ A}$		265 / 55		ns
$t_{d(off)}/t_f$	$V_{GE} = \pm 15 \text{ V}$		585 / 120		ns
$E_{on} (E_{off})$	$R_{Gon} = R_{Goff} = 2 \Omega, T_j = 125^\circ\text{C}$		25 (31)		mJ
<b>Inverse diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 225 \text{ A}; V_{GE} = 0 \text{ V}; T_j = 25 (125)^\circ\text{C}, \text{chip level}$		1,6 (1,6)	1,8 (1,8)	V
$V_{(TO)}$	$T_j = 25 (125)^\circ\text{C}$		1 (0,8)	1,1 (0,9)	V
$r_T$	$T_j = 25 (125)^\circ\text{C}$		2,7 (3,6)	3,1 (4)	m $\Omega$
$I_{RRM}$	$I_{Fnom} = 225 \text{ A}; T_j = 25 (125)^\circ\text{C}$		(330)		A
$Q_{rr}$	$di/dt = 5600 \text{ A}/\mu\text{s}$		(68,5)		$\mu\text{C}$
$E_{rr}$	$V_{GE} = -15 \text{ V}$		(29)		mJ
<b>Thermal characteristics</b>					
$R_{th(j-c)}$	per IGBT			0,1	K/W
$R_{th(j-c)D}$	per Inverse Diode			0,176	K/W
$R_{th(j-c)FD}$	per FWD				K/W
$R_{th(c-s)}$	per module		0,04		K/W
<b>Temperature sensor</b>					
$R_{25}$	$T_c = 25^\circ\text{C}$		5 $\pm$ 5%		k $\Omega$
$B_{25/85}$	$R_2 = R_1 \exp[B(1/T_2 - 1/T_1)]; T[K]; B$		3420		K
<b>Mechanical data</b>					
$M_s/M_t$	to heatsink (M5) / for terminals (M6)	3/2,5		5 / 5	Nm
w			289		g






# SEMIX 353GB126HD



# SEMIX 353GB126HD



# SEMiX 353GB126HD



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.