




Advanced Technical Information

HiPerFAST™ IGBT IXGN 200N60B

$$V_{CES} = 600 \text{ V}$$


$$I_{C25} = 200 \text{ A}$$

$$V_{CE(sat)} = 2.1 \text{ V}$$



| Symbol | Test Conditions | Maximum Ratings | |
|---------------------|---|-----------------------------------|------------------|
| V_{CES} | $T_J = 25^\circ\text{C}$ to 150°C | 600 | V |
| V_{CGR} | $T_J = 25^\circ\text{C}$ to 150°C ; $R_{GE} = 1 \text{ M}\Omega$ | 600 | V |
| V_{GES} | Continuous | ± 20 | V |
| V_{GEM} | Transient | ± 30 | V |
| I_{C25} | $T_C = 25^\circ\text{C}$ | 200 | A |
| I_{C90} | $T_C = 90^\circ\text{C}$ | 120 | A |
| I_{CM} | $T_C = 25^\circ\text{C}$, 1 ms | 400 | A |
| SSOA (RBSOA) | $V_{GE} = 15 \text{ V}$, $T_{VJ} = 125^\circ\text{C}$, $R_G = 2.4 \Omega$ Clamped inductive load, $L = 30 \mu\text{H}$ | $I_{CM} = 200$ @ $0.8 V_{CES}$ | A |
| P_C | $T_C = 25^\circ\text{C}$ | 600 | W |
| T_J | | -55 ... +150 | $^\circ\text{C}$ |
| T_{JM} | | 150 | $^\circ\text{C}$ |
| T_{stg} | | -55 ... +150 | $^\circ\text{C}$ |
| V_{ISOL} | 50/60 Hz | t = 1 min | 2500 V~ |
| | $I_{ISOL} \leq 1 \text{ mA}$ | t = 1 s | 3000 V~ |
| M_d | Mounting torque | 1.5/13 | Nm/lb.in. |
| | Terminal connection torque (M4) | 1.5/13 | Nm/lb.in. |
| Weight | | 30 | g |

SOT-227B, miniBLOC



G = Gate, C = Collector, E = Emitter
 ① either emitter terminal can be used as Main or Kelvin Emitter

Features

- International standard package miniBLOC
- Aluminium nitride isolation
 - high power dissipation
- Isolation voltage 3000 V~
- Very high current, fast switching IGBT
- Low $V_{CE(sat)}$
 - for minimum on-state conduction losses
- MOS Gate turn-on
 - drive simplicity
- Low collector-to-case capacitance (< 50 pF)
- Low package inductance (< 5 nH)
 - easy to drive and to protect

Applications

- AC motor speed control
- DC servo and robot drives
- DC choppers
- Uninterruptible power supplies (UPS)
- Switch-mode and resonant-mode power supplies

Advantages


- Easy to mount with 2 screws
- Space savings
- High power density

| Symbol | Test Conditions | Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified) | | |
|---------------|--|---|------|----------------------|
| | | min. | typ. | max. |
| BV_{CES} | $I_C = 1 \text{ mA}$, $V_{GE} = 0 \text{ V}$ | 600 | | V |
| $V_{GE(th)}$ | $I_C = 1 \text{ mA}$, $V_{CE} = V_{GE}$ | 2.5 | | 5.5 V |
| I_{CES} | $V_{CE} = V_{CES}$ $V_{GE} = 0 \text{ V}$ | $T_J = 25^\circ\text{C}$ | | 200 μA |
| | | $T_J = 125^\circ\text{C}$ | | 2 mA |
| I_{GES} | $V_{CE} = 0 \text{ V}$, $V_{GE} = \pm 20 \text{ V}$ | | | $\pm 400 \text{ nA}$ |
| $V_{CE(sat)}$ | $I_C = I_{C90}$, $V_{GE} = 15 \text{ V}$ | | | 2.1 V |



| Symbol | Test Conditions | Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified) | | |
|--|--|---|-------|-----------------|
| | | min. | typ. | max. |
| g_{fs} | $I_C = 60\text{ A}; V_{CE} = 10\text{ V}$, Pulse test, $t \leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$ | 50 | 75 | S |
| C_{ies} C_{oes} C_{res} | $V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 1\text{ MHz}$ | | 11000 | pF |
| | | | 680 | pF |
| | | | 190 | pF |
| Q_g Q_{ge} Q_{gc} | $I_C = I_{C90}, V_{GE} = 15\text{ V}, V_{CE} = 0.5 V_{CES}$ | | 350 | nC |
| | | | 72 | nC |
| | | | 131 | nC |
| $t_{d(on)}$ t_{ri} E_{on} $t_{d(off)}$ t_{ri} E_{off} | Inductive load, $T_J = 25^\circ\text{C}$ $I_C = 100\text{ A}, V_{GE} = 15\text{ V}$ $V_{CE} = 0.8 V_{CES}, R_G = R_{off} = 2.4\ \Omega$ Remarks: Switching times may increase for $V_{CE}(\text{Clamp}) > 0.8 \cdot V_{CES}$, higher T_J or increased R_G | | 60 | ns |
| | | | 45 | ns |
| | | | 2.4 | mJ |
| | | | 200 | 360 ns |
| | | | 160 | 280 ns |
| | | | 5.5 | 9.6 mJ |
| $t_{d(on)}$ t_{ri} E_{on} $t_{d(off)}$ t_{ri} E_{off} | Inductive load, $T_J = 125^\circ\text{C}$ $I_C = 100\text{ A}, V_{GE} = 15\text{ V}$ $V_{CE} = 0.8 V_{CES}, R_G = R_{off} = 2.4\ \Omega$ Remarks: Switching times may increase for $V_{CE}(\text{Clamp}) > 0.8 \cdot V_{CES}$, higher T_J or increased R_G | | 60 | ns |
| | | | 60 | ns |
| | | | 4.8 | mJ |
| | | | 290 | ns |
| | | | 250 | ns |
| | | | 8.7 | mJ |
| R_{thJC} R_{thCK} | | | 0.05 | 0.21 K/W K/W |

miniBLOC, SOT-227 B



M4 screws (4x) supplied

| Dim. | Millimeter | | Inches | |
|------|------------|-------|--------|-------|
| | Min. | Max. | Min. | Max. |
| A | 31.50 | 31.88 | 1.240 | 1.255 |
| B | 7.80 | 8.20 | 0.307 | 0.323 |
| C | 4.09 | 4.29 | 0.161 | 0.169 |
| D | 4.09 | 4.29 | 0.161 | 0.169 |
| E | 4.09 | 4.29 | 0.161 | 0.169 |
| F | 14.91 | 15.11 | 0.587 | 0.595 |
| G | 30.12 | 30.30 | 1.186 | 1.193 |
| H | 38.00 | 38.23 | 1.496 | 1.505 |
| J | 11.68 | 12.22 | 0.460 | 0.481 |
| K | 8.92 | 9.60 | 0.351 | 0.378 |
| L | 0.76 | 0.84 | 0.030 | 0.033 |
| M | 12.60 | 12.85 | 0.496 | 0.506 |
| N | 25.15 | 25.42 | 0.990 | 1.001 |
| O | 1.98 | 2.13 | 0.078 | 0.084 |
| P | 4.95 | 5.97 | 0.195 | 0.235 |
| Q | 26.54 | 26.90 | 1.045 | 1.059 |
| R | 3.94 | 4.42 | 0.155 | 0.174 |
| S | 4.72 | 4.85 | 0.186 | 0.191 |
| T | 24.59 | 25.07 | 0.968 | 0.987 |
| U | -0.05 | 0.1 | -0.002 | 0.004 |