

Photocoupler

KODENSHI

K5620 • K5621

These Photocouplers consist of a Gallium Arsenide Infrared Emitting Diode and a Silicon NPN PhotoDarlington transistor in a 6-pin package.

FEATURES


- Collector-Emitter Voltage : Min.35V
- Current Transfer Ratio : Typ.500% (at $I_F=1\text{mA}$, $V_{CE}=2\text{V}$)
- Electrical Isolation Voltage : AC5000Vrms
- UL Recognized File No. E107486

APPLICATIONS

- Interface between two circuits of different potential
- Telephone Line Receiver
- Automatic Vending Machine
- Power Supply Regulators

DIMENSION

(Unit : mm)



MAXIMUM RATINGS

(Ta=25°C)

Parameter	Symbol	Rating	Unit
Input	Forward Current	I_F	60
	Reverse Voltage	V_R	5
	Peak Forward Current ^{*1}	I_{FP}	1
	Power Dissipation	P_D	150
	Junction Temperature	T_J	125
Output	Collector-Emitter Breakdown Voltage	BV_{CEO}	35
	Emitter-Collector Breakdown Voltage	BV_{ECO}	6
	Collector-Base Breakdown Voltage**	BV_{CBO}	35
	Collector Current	I_C	50
	Collector Power Dissipation	P_C	150
Input to Output Isolation Voltage ^{*2}		V_{iso}	AC5000
Storage Temperature		T_{stg}	-55~+125
Operating Temperature		T_{opr}	-30~+100
Lead Soldering Temperature ^{*3}		T_{sol}	260
Total Power Dissipation		P_{tot}	200

** Except for K5620

^{*1} Input current with 100μs pulse width, 1% duty cycle^{*2} Measured at RH=40~60% for 1min^{*3} 1/16 inch form case for 10sec

K5620 • K5621

ELECTRO-OPTICAL CHARACTERISTICS

(Ta=25°C , unless otherwise noted)


Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit.
Input	Forward Voltage	V _F	I _F =10mA	-	1.15	1.30	V
	Reverse Current	I _R	V _R =5V	-	-	10	μA
	Capacitance	C _T	V=0, f=1MHz	-	30	-	pF
Output	Collector-Emitter Breakdown Voltage	BV _{CEO}	I _C =1mA	35	-	-	V
	Emitter-Collector Breakdown Voltage	BV _{ECO}	I _E =0.1mA	6	-	-	V
	Collector-Base Breakdown Voltage **	BV _{CBO}	I _C =0.1mA	35	-	-	V
	Collector Dark Current	I _{CEO}	I _F =0, V _{CE} =10V	-	-	100	nA
	Capacitance	C _{CE}	V _{CE} =0, f=1MHz	-	10	-	pF
Coupled	Current Transfer Ratio *4	CTR	I _F =1mA, V _{CE} =2V		500	-	%
	Collector-Emitter Saturation Voltage	V _{CE(SAT)}	I _F =1mA, I _C =2mA	-	0.85	1.0	V
	Input-Output Capacitance	C _{IO}	V=0, f=1MHz	-	1	-	pF
	Input-Output Isolation Resistance	R _{IO}	RH=40~60%, V=500V	-	10 ¹¹	-	Ω
	Rise Time	t _r	V _{CE} =10V, R _L =100Ω	-	100	-	μs
	Fall Time	t _f	I _C =2mA	-	100	-	μs

** Except for K5620


*4. CTR=(I_C/I_F) X 100 (%)

K5620 • K5621


Forward Current vs. Ambient Temperature




Collector Power Dissipation vs. Ambient Temperature




Forward Current vs. Forward Voltage




Collector Current vs. Collector-Emitter Voltage



Dark Current vs. Ambient Temperature



Collector Current vs. Forward Current



Switching Time Test Circuit

