查询KB3541NT供应商 捷多邦，专业PCB打样工厂，24小时加急出货

Kingbright

PHOTOCOUPLER

KB3541NT

Features

1.AC inputs
2.High current transfer ratio
3.Opaque type, mini-flat package
4.Subminiature type (The volume is smaller than that of our conventional DIP type by as far as 30%)
5.Isolation voltage between input and output Viso:3750Vrms
6.Employs double transfer mold technology
7.Recognized by UL and CUL, file NO.E225308.
8.Package:1000Pcs/Reel.
9.RoHS Compliant.

Applications

1.Hybrid substrates that require high density mounting
2.Programmable controllers

***PACKAGE DIMENSIONS (UNIT:mm)**
SMD Type



Internal connection diagram



① Anode/Cathode ③ Emitter
② Cathode/Anode ④ Collector





UNIT : MM[INCH]
TOLERANCE : ±0.5[±0.02] UNLESS OTHERWISE NOTED.

找PDF 维库一下 pdf.dzsc.com

*Absolute Maximum Ratings (Ta=25℃)

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	±50	mA
	Power dissipation	P	70	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	IC	80	mA
	Collector power dissipation	P_C	150	mW
Total power dissipation		Ptot	170	mW
*1 Isolation voltage		Viso	3750	Vrms
Operating temperature		Topr	-30 to +100	°C
Storage temperature		Tstg	-40 to +125	°C
*2 Soldering temperature		Tsol	260	°C

*1 40 to 60%RH, AC for1 minute.
*2 For 10 seconds.

*Electro-optical Characteristics

Parameter			Symbol	Conditions	Min.	Typ.	Max.	Unit
Input	Forward voltage		V_F	I_F=± 20mA	-	1.2	1.4	V
	Peak forward voltage		V_{FM}	I_{FM}=0.5A	-	-	3.0	V
Output	Collector dark current		I_{CEO}	Vce=20V I_F=0	-	-	10^{-6}	A
	Collector-emitter breakdown voltage		BV_{CEO}	I_C=0.1mA I_F=0	35	-	-	V
	Emitter-collector breakdown voltage		BV_{ECO}	I_E=10uA I_F=0	6	-		V
Transfer charact-eristics	Current transfer ration		CTR	I_F=± 1mA Vce=5V	450	1600	7400	%
	Collector-emitter saturation voltage		V_{CE} (sat)	I_F=± 20mA I_C=1mA	-	0.8	1.0	V
	Response time	Rise time	tr	Vce=2V I_C=2mA R_L=100Ω	-	60	300	uS
		Fall time	tr			53	250	uS

Fig. 1 Current Transfer Ratio vs. Forward Current



Fig. 2 Forward Current vs. Forward voltage



Fig. 3 Collector Current vs. Collector-emitter Voltage



Fig. 4 Relative Current Transfer Ratio vs. Ambient Temperature



Fig. 5 Collector-emitter Saturation Voltage vs. Ambient Temperature



Fig. 6 Response Time vs. Load Resistance



Fig. 7 Collector-emitter Saturation Voltage vs. Forward Current



Fig. 8 Collector Dark Current vs. Ambient Temperature



Test Circuit for Response Time



* NOTES ON HANDLING

1.Recommended soldering conditions (Dip soldering)

(1) Dip soldering

Temperature	260 or below (molten solder temperature)
Time	Less than 10 seconds.
Cycle	One cycle allowed to be dipped in solder including plastic nold portion.
Flux	Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt % is recommended.)

(2) Cautions

Fluxes

Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.

2.Cautions regarding noise

Be aware that power is suddenly into the component any surge current may cause damage happen, even if the voltage is within the absolute maximum ratings.

NOTES ON HANDLING

1.Recommended soldering conditions

(1).Infrared reflow soldering

- Peak reflow temperature 235 ° C or below(package surface temperature)
- Time of temperature higher than 210 ° C 30 seconds or less
- Number or reflows Three
- Flux Rosin flux containing small amount of chlorine(The flux with a maximum chlorine content of 0.2Wt % is recommended.)

Recommended Temperature Profile of infrared Reflow



CAUTION

Within this device there exists GaAs (Gallium Arsenide) material which is a harmful substance if ingested. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them.

RESTRICTIONS ON PRODUCT USE

- The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version. Not all devices / types available in every country.
- We are mention about our product quality stablity, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing KINGBRIGHT products, to observe standards of safety, and to a avoid situations in which a malfunction or failure of a KINGBRIGHT product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that KINGBRIGHT products are used within specified operating ranges as set forth in the most recent products specifications.

Outline and Dimension(Tape)
(Units : mm)



Tape Direction



Outline and Dimension(Reel)



Packing:1000pcs/reel