



**DC COMPONENTS CO., LTD.**  
RECTIFIER SPECIALISTS

**KBJ4A  
THRU  
KBJ4M**

**TECHNICAL SPECIFICATIONS OF SINGLE-PHASE SILICON BRIDGE RECTIFIER**  
VOLTAGE RANGE - 50 to 1000 Volts      CURRENT - 4.0 Amperes

**FEATURES**


- \* Ideal for printed circuit board
- \* Surge overload rating: 120 Amperes peak

**MECHANICAL DATA**

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: MIL-STD-202E, Method 208 guaranteed
- \* Polarity: Symbols molded or marked on body
- \* Mounting position: Any
- \* Weight: 4.6 grams

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



	SYMBOL	KBJ4A	KBJ4B	KBJ4D	KBJ4G	KBJ4J	KBJ4K	KBJ4M	UNITS
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V <sub>bc</sub>	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Output Current at T <sub>c</sub> = 100 °C	I <sub>o</sub>				4.0				Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>				120				Amps
Maximum Forward Voltage Drop per element at 3.0A DC	V <sub>F</sub>				1.0				Volts
Maximum DC Reverse Current at Rated	I <sub>R</sub>				10				uAmps
DC Blocking Voltage per element					500				
I <sup>2</sup> t Rating for Fusing (t<8.3ms)	I <sup>2</sup> t				93				A <sup>2</sup> Sec
Typical Junction Capacitance ( Note1)	C <sub>J</sub>				40				pF
Typical Thermal Resistance (Note 2)	R <sub>θJA</sub>				19				°C/W
Operating Temperature Range	T <sub>J</sub>				-55 to + 150				°C
Storage Temperature Range	T <sub>STG</sub>				-55 to + 150				°C

NOTES : 1. Measured at 1 MHz and applied reverse voltage of 4.0 volts  
2. Thermal Resistance from Junction to Case per element Unit mounted on 300x300x1.6mm Aluminum plate heat-sink.



## RATING AND CHARACTERISTIC CURVES (KBJ4A THRU KBJ4M)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS

