


cosmo

High Voltage, Solid State Relay-MOSFET Output **KCP1008**

UL 1577/ UL 508 (File No.E108430), FI EN60950 (File No.F113698)

Features



1. Normally Open, Single Pole Single Throw
2. Control 100VAC or DC Voltage
3. Switch 150mA Loads
4. LED control Current, 2mA
5. Low ON-Resistance
6. dv/dt, >500V/ms
7. Isolation Test Voltage, 1500VACrms



Absolute Maximum Ratings

(Ta=25°C)

Emitter (Input)	Detector (Output)
Reverse Voltage..... 5.0V	Output Breakdown Voltage..... ±100V
Continuous Forward Current..... 50mA	Continuous Load Current..... ±150mA
Peak Forward Current.....1A	Power Dissipation.....500mW
Power Dissipation..... 100mW	
Derate Linearly from 25°C..... 1.3mW/°C	
General Characteristics	
Isolation Test Voltage..... 1500VACrms	Storage Temperature Range... -40°C to +150°C
Isolation Resistance	Operating Temperature Range... -40°C to +85°C
Vio=500V, Ta=25°C..... ≥10 ¹⁰ Ω	Junction Temperature.....100°C
Total Power Dissipation..... 500mW	Soldering Temperature,
Derate Linearly from 25°C.....2.5mW/°C	2mm from case, 10 sec..... 260°C



Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Emitter (Input)						
Forward Voltage	V _F	I _F = 10mA		1.2	1.5	V
Operation Input Current	I _{FORN}	V _L = ±20V, I _L = 100mA, t = 10ms			2	mA
Recovery Input Current	I _{FOFF}	V _L = ±20V, I _L ≤ 5uA	0.2			mA
Detector (Output)						
Output Breakdown Voltage	V _B	I _B = 50uA	100			V
Output Off-State Leakage	I _{TOFF}	V _T = 100V, I _F = 0mA		0.2	1	uA
I/O Capacitance	C _{ISO}	I _F = 0, f = 1MHz		6		p F
ON Resistance	R _{ON}	I _L = 100mA, I _F = 10mA		6	8	Ω
Turn-On Time	T _{ON}	I _F = 10mA, V _L = ±20V		0.3	2.0	ms
Turn-Off Time	T _{OFF}	t = 10ms, I _L = ±100mA		0.3	1.0	ms

Schematic and Wiring Diagrams

Type	Schematic	Output configuration	Load	Connection	Wiring Diagrams
KCP1008		1a	AC/DC	—	



Data Curve

