

KSR2009

PNP EPITAXIAL SILICON TRANSISTOR


SWITCHING APPLICATION (Bias Resistor Built In)

- Switching Circuit, Inverter, Interface circuit Driver circuit
- Built in bias Resistor ($R=4.7K\Omega$)
- Complement to KSR1009

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ C$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CB0}	-40	V
Collector-Emitter Voltage	V_{CE0}	-40	V
Emitter-Base Voltage	V_{EB0}	-5	V
Collector Current	I_C	-100	mA
Collector Dissipation	P_C	300	mW
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{stg}	-55 ~ 150	$^\circ C$

TO-92




1. Emitter 2. Collector 3. Base

3

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ C$)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Collector-Base Breakdown Voltage	BV_{CB0}	$I_C = -100\mu A, I_E = 0$	-40			V
Collector-Emitter Breakdown Voltage	BV_{CE0}	$I_C = -1mA, I_B = 0$	-40			V
Collector Cutoff Current	I_{CB0}	$V_{CB} = -30V, I_E = 0$			-0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = -5V, I_C = -1mA$	100		600	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10mA, I_B = -1mA$			-0.3	V
Output Capacitance	C_{ob}	$V_{CB} = -10V, I_E = 0$ $f = 1MHz$		5.5		pF
Current Gain-Bandwidth Product	f_T	$V_{CE} = -10V, I_C = -5mA$		200		MHz
Input Resistor	R_i		3.2	4.7	6.2	K Ω

Equivalent Circuit



KSR2009

PNP EPITAXIAL SILICON TRANSISTOR

T-37-13

