

Line Conditioner

Automatic voltage regulation with surge protection



Model #: LC1200WM

- ▶ Automatically adjusts low or high voltage
- ▶ 1200 watts continuous
- ▶ 4 NEMA 5-15R outlets
- ▶ Wallmount cabinet keeps unit conveniently out of the way
- ▶ \$25,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's wall-mountable LC1200WM automatic voltage regulation system offers complete protection from brownouts, overvoltages and transient surges for computers, printers, telecommunications systems and more. Transformer-based voltage correction circuits maintain usable 120V nominal AC output during brownouts as low as 87V and overvoltages to 140V. Network grade equipment protection offers AC surge and noise suppression. Supports heavy loads up to 1200 watts. Rugged, all-metal case with keyhole mounting tabs allow secure 4-screw mounting on walls and other surfaces. Includes 4 NEMA5-15R outlets, 6-ft. line cord and lighted power switch. \$25,000 Ultimate Lifetime Insurance (USA & Canada Only).

KEY BUYING POINTS

- Maintains usable 120V nominal output during brownouts as low as 87V and overvoltages as high as 140V
- 1200 watts output power rating supports heavy 120V loads up to 10 amps
- All-metal case with keyhole mounting tabs for secure 4-screw mounting on walls and other surfaces
- Network grade surge suppression
- Complete EMI/RFI noise filtering
- Lighted red switch indicates power status
- 4 protected NEMA5-15R outlets
- 6-ft. AC power cord with standard NEMA5-15P input plug
- 2 year manufacturers product warranty
- \$25,000 Ultimate Lifetime connected equipment Insurance (USA & Canada Only)

TYPICAL APPLICATIONS

- Maintains usable output voltage during severe brownouts and overvoltages for printers, computers, telecommunications systems and more.

PACKAGE INCLUDES

- LC1200WM Line Conditioner
- Mounting hardware
- Instruction manual

COMPLETE SPECIFICATIONS

OUTPUT	
Output volt amp capacity (VA):	1200
Output nominal voltage:	120V / 60Hz

Outlet quantity / type:	4 NEMA5-15R
INPUT	
Input cord length (ft.):	6.00
Input cord length (m):	1.83
LEDS ALARMS & SWITCHES	
Front panel LEDs:	Lighted power switch shows incoming power status
SURGE / NOISE SUPPRESSION	
AC surge suppression:	1200 joules
EMI / RFI AC noise suppression:	80 dB
PHYSICAL	
Unit Dimensions (HWD/in):	5 x 5 x 7.25
Form factors supported:	Short tower format with keyhole slots for wall-mount applications
Material of construction:	Steel
Shipping weight (lbs):	16.00
Shipping weight (kg):	7.26
WARRANTY	
Product warranty:	2 years
Connected equipment insurance (USA and Canada Only):	\$25,000

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.