

Round-Top View Type


φ 2.6 mm Series

Conventional Part No.	Global Part No.	Lighting Color
LN221RPX	LNG221RKR	Red
LN321GPX	LNG321GKG	Green
LN421YPX	LNG421YKX	Amber

■ Absolute Maximum Ratings ($T_a = 25^{\circ}\text{C}$)

Lighting Color	$P_D(\text{mW})$	$I_F(\text{mA})$	$I_{FP}(\text{mA})^*$	$V_R(\text{V})$	$T_{opr}(\text{C}^{\circ})$	$T_{stg}(\text{C}^{\circ})$
Red	70	25	150	4	-25 ~ +85	-30 ~ +100
Green	90	30	150	4	-25 ~ +85	-30 ~ +100
Amber	90	30	150	4	-25 ~ +85	-30 ~ +100

I_{FP} 的条件は $duty$ 10%, Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec



■ Electro-Optical Characteristics ($T_a = 25^{\circ}\text{C}$)

Conventional Part No.	Lighting Color	Lens Color	I_O		I_F	V_F		λ_P	$\Delta\lambda$	I_F	I_R	
			Typ	Min		Typ	Max				Max	V_R
LN221RPX	Red	Red Diffused	1.0	0.5	15	2.2	2.8	700	100	20	5	4
LN321GPX	Green	Green Diffused	1.2	0.5	20	2.2	2.8	565	30	20	10	4
LN421YPX	Amber	Amber Diffused	2.0	1.0	20	2.2	2.8	590	30	20	10	4
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

