



SHARP BREAKDOWN, LOW LEAKAGE LVA REGULATOR DIODES LVA43A - LVA100A

- Sharper breakdown
- Lower leakage current characteristics in the 4 – 10 volt range

PART NUMBER	NOMINAL VOLTAGE Vz @ Iz (Vdc)	TEST CURRENT Izt (mA)	MAX ZENER IMPEDANCE Zzt @ Iz (OHMS)	MAX REVERSE LEAKAGE CURRENT Ir (μ Adc)	MAX NOISE DENSITY @ 250 μ A
LVA43A	4.3	20	18	4.0	4
LVA47A	4.7	10	15	4.0	4
LVA51A	5.1	5	15	0.1	4
LVA56A	5.6	1	40	0.05	4
LVA62A	6.2	1	50	0.05	4
LVA68A	6.8	1	50	0.05	4
LVA75A	7.5	1	100	0.01	4
LVA82A	8.2	1	100	0.01	4
LVA91A	9.1	1	100	0.01	4
LVA100A	10.0	1	100	0.01	4

Package Style	DO-7
Forward Voltage (Vf)	1.5 Vdc
Noise Density (Nd)	4.0 μ V / $\sqrt{\text{Hz}}$
Power Dissipation (Pd)	400 mW
Operating Temperature (Topr)	-65 to + 175° C
Storage Temperature (Tstg)	-65 to + 200° C
Voltage Tolerance:	±10%
Standard Device	±5%
Suffix A	±2%
Suffix B	

Noise Density measured from 1000 to 3000 Hz.