


SWITCHING REGULATOR CONTROL IC FOR FLYBACK**■ GENERAL DESCRIPTION**


The NJM2369 is a high speed switching regulator control IC which can operate at low voltage.

It uses a totempole output circuit, so that it can drive an external power MOS-FET directly.

It is suitable for applications of flyback type switching regulation of up to 10W.

■ PACKAGE OUTLINE

NJM2369D



NJM2369M




NJM2369E



NJM2369V

■ FEATURES

- Operating Voltage (3.6~32V)
- Wide Oscillator Range (5~350 kHz)
- Soft-Start function.
- Under Voltage Lockouts (U.V.L.O.)
- Bipolar Technology
- Package Outline DIP8, DMP8, EMP8, SSOP8

■ BLOCK DIAGRAM**PIN FUNCTION**

1. IN-
2. F. B
3. GND
4. OUT
5. V⁺
6. CS
7. CT
8. REF

NJM2369

■ ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

PARAMETER	SYMBOL	MAXIMUM RATINGS		UNIT
Input Voltage	V^+	36		V
Reference Output Current	I_{OR}	10		mA
Power Dissipation	P_D	(DIP8) 700 (DMP8) 300 (EMP8) 300 (SSOP8) 250		mW
Operating Temperature Range	T_{OPR}	-40~+85		°C
Storage Temperature Range	T_{STG}	-50~+125		°C

■ RECOMMENDED OPERATING CONDITIONS ($V^+ = 6\text{ V}$, $T_a = 25^\circ\text{C}$)

PARAMETER	SYMBOL	RATINGS	MIN.	MAX.	UNIT
Operating Voltage	V^+		3.6	32	V
Feed Back Resistor	R_{NF}		100	—	kΩ
Oscillator Timing Capacitor	C_T		220	22000	pF
Oscillator Timing Resistor	R_T		10	100	kΩ
Oscillate	f_{osc}		5	350	kHz

■ ELECTRICAL CHARACTERISTICS

($V^+ = 6\text{ V}$, $R_T = 33\text{ k}\Omega$, $C_T = 1000\text{ pF}$, $T_a = 25^\circ\text{C}$)

REFERENCE VOLTAGE BLOCK

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_{REF}	$I_{OR}=1\text{ mA}$	2.45	2.50	2.55	V
Line Regulation	L_{INE}	$V^+=3.6\sim 32\text{ V}$, $I_{OR}=1\text{ mA}$	—	6.8	20.7	mV
Load Regulation	L_{OAD}	$I_{OR}=0.1\sim 5.0\text{ mA}$	—	5	30	mV

OSCILLATOR BLOCK

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Oscillate	f_{osc}	$C_T=1000\text{ pF}$, $R_T=33\text{ k}\Omega$	85	105	125	kHz
Oscillate Fluctuations1 (Line Fluctuations)	f_{dv}	$V^+=3.6\sim 32\text{ V}$	—	1	—	%
Oscillate Fluctuations2 (Temp Fluctuations)	f_{dt}	$T_a=-40\sim +85^\circ\text{C}$	—	5	—	%

■ ELECTRICAL CHARACTERISTICS

($V^+ = 6 \text{ V}$, $R_T = 33 \text{ k}\Omega$, $C_T = 1000 \text{ pF}$, $T_a = 25^\circ\text{C}$)
ERROR AMPLIFIER BLOCK

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Reference Voltage	V_B		0.51	0.52	0.53	V
Input Bias Current	I_B		—	5	100	nA
Open Loop Gain	A_v		—	90	—	dB
Gain Band width Product	G_B		—	0.6	—	MHz
Maximum Output Voltage (F.B Pin)	V_{OM+}	$R_{NF}=100\text{k}\Omega$	$V_{REF}=0.2$	—	—	V
	V_{OM-}	$R_{NF}=100\text{k}\Omega$	—	—	200	mV
Output Source Current (F.B Pin)	I_{OM+}	$V_{om}=1\text{V}$	40	85	200	μA

PWM COMPARATE BLOCK

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Input Bias Voltage (F.B Pin)	V_{TH0}	duty-cycle=0%	—	0.55	0.65	V
Input Threshold Voltage (F.B Pin)	V_{TH50}	duty-cycle=50%	—	0.87	—	V
Maximum Duty Cycle	α_M	F.B Pin=1.2V	55	64	85	%

SOFT START CIRCUIT BLOCK

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Input Bias Current (CS Pin)	I_{BGS}		—	250	650	nA
Input Threshold Voltage (CS Pin)	V_{THCS0}	duty-cycle=0%	—	0.25	0.35	V
Input Threshold Voltage (CS Pin)	V_{THCS50}	duty-cycle=50%	—	0.52	—	V

SHORT CIRCUIT PROTECTION

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Input Threshold Voltage (F.B Pin)	V_{THPC}		1.20	1.50	1.80	V
Charge Current (CS Pin)	I_{CHG}	CS Pin=0V, F.B Pin=2V	10	30	50	μA
Latch mode Threshold Voltage (CS Pin)	V_{THLA}		1.20	1.50	1.80	V

UNDER VOLTAGE LOCKOUT

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
ON Threshold Voltage	V_{THON}		—	2.70	—	V
OFF Threshold Voltage	V_{THOFF}		—	2.52	—	V
Hysteresis Voltage	V_{HYS}		60	180	—	mV

NJM2369

ELECTRICAL CHARACTERISTICS

($V^+ = 6 \text{ V}$, $R_T = 33 \text{ k}\Omega$, $C_T = 1000 \text{ pF}$, $T_a = 25^\circ\text{C}$)


OUTPUT



PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
H-Output Voltage(OUT Pin)	V_{OH}	$R_L=10\text{k}\Omega$	3.50	4.00	—	V
L-Output Voltage(OUT Pin)	V_{OL}	Output Sink Current=20mA	—	0.25	0.65	V
Output Source Current (OUT Pin)	I_{SOURCE}	OUT Pin=0V	—	35	—	mA

GENERAL CHARACTERISTIC

PARAMETER	SYMBOL	RATINGS	MIN.	TYP.	MAX.	UNIT
Quiescent Current	I_{CCLA}	Latch	—	1.6	2.2	mA
Average Quiescent Current	I_{CCAV}	$R_L=\infty$, duty-cycle=50%	—	5.2	10.0	mA


APPLICATION




■ TYPICAL CHARACTERISTICS

■ TYPICAL CHARACTERISTICS


H Output Voltage vs. Source Current
 $(V^+=6V, R_T=33k\Omega, C_T=1000pF,$
 $OUT\ Pin=0V, Ta=25^\circ C)$




L Output Voltage vs. Sink Current
 $(V^+=6V, R_T=33k\Omega, C_T=1000pF, Ta=25^\circ C)$




Oscillator Frequency vs. Timing Resistor
 $(V^+=6V, Ta=25^\circ C)$




Oscillator Frequency vs. Timing Capacitor
 $(V^+=6V, Ta=25^\circ C)$









Reference Voltage vs. Operating Voltage
 $(V^+=6V, Ta=25^\circ C)$



Operating Current vs. Operating Voltage
 $(Ta=25^\circ C)$





■ TYPICAL CHARACTERISTICS



NJM2369

■ TYPICAL CHARACTERISTICS



NJM2369

MEMO

[CAUTION]
The specifications on this databook are only given for information , without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.