查询M57706供应商 捷多邦，专业PCB打样工厂，24小时加急出货

M57706

145-175MHz, 12.5V, 8W, FM MOBILE RADIO

OUTLINE DRAWING

Dimensions in mm



BLOCK DIAGRAM



PIN :
①Pin : RF INPUT
②Vcc1 : 1st. DC SUPPLY
③Vcc2 : 2nd. DC SUPPLY
④Po : RF OUTPUT
⑤GND : FIN

ABSOLUTE MAXIMUM RATINGS (Tc = 25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
Vcc	Supply voltage		17	V
Icc	Total current		5	A
Pin(max)	Input power	ZG = ZL = 50 Ω	0.4	W
Po(max)	Output power	ZG = ZL = 50 Ω	12	W
Tc(OP)	Operation case temperature		− 30 to 110	℃
Tstg	Storage temperature		− 40 to 110	℃

Note. Above parameters are guaranteed independently.

ELECTRICAL CHARACTERISTICS (Tc = 25℃ unless otherwise noted)

Symbol	Parameter	Test conditions	Limits Min	Limits Max	Unit
f	Frequency range	Pin = 0.2W Vcc = 12.5V ZG = ZL = 50 Ω	145	175	MHz
Po	Output power		8		W
ηT	Total efficiency		35		%
2fo	2nd. harmonic			− 15	dBc
3fo	3rd. harmonic			− 25	dBc
ρin	Input VSWR			4	−
−	Load VSWR tolerance	Vcc = 15.2V, Po = 12W (Pin : controlled) Load VSWR=20:1(All phase), 2sec. ZG = 50Ω	No degradation or destroy		−

Note. Above parameters, ratings, limits and conditions are subject to change.

找PDF 维库一下 pdf.dzsc.com