





Characteristics			Typical	Guaranteed	
	- 12-111	- WW A		+25°C	-54° to +85°C
SSB Conversion Loss & SSI					
$f_R = f_L = f_L = f_L$	FE II				
$f_R = f_L = f_L = f_L$	II D				
$\begin{array}{ccc} f_R = & f_L = \\ f_R = & f_L = \end{array}$	$f_{\Gamma} =$				
Isolation (min.)	11-				
L to R					- 450
$f_L =$					7.00
$f_L =$			140		Acres 1
$f_L =$			and the		C.COM
L to I			The Colonial Inches		
$f_L =$			THE NAME OF		
$f_L =$					
$f_L =$					
R to I					
$f_R =$					
$f_R =$	- Com				
1 dB Conversion Compressi	on				
f _L @					
f _L @					
Input IP3					
$f_{R1} =$	$ m f_{R2} =$				7.00
$f_L =$			140		LAD TO SA
f _	f _		4.45		C.COM
$egin{aligned} f_{ extsf{R} extsf{I}} = \ f_{ extsf{L}} = \end{aligned}$	$ m f_{R2}$ =		The Columbia		
ıL —			LOS NEEDS		
$f_{RI} =$	$f_{R2} =$				
$f_{\tau} =$	*R2 —				

Absolute Maximum Ratings
Operating Temperature
Storage Tem Storage Temperature Peak Input Power Peak Input Current

Outline Drawing(s)

$\mathcal{U}^{(i)}$					
Package	Figure	Model			
1	1				



Typical Performance at 25°C