


SHINDENGEN

Power Switching Regulators

MA2000 Series

MA2450

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings		Unit
			P Class	N Class	
Storage Temperature	Tstg		-30~125	-30~125	°C
Operating Temperature	Top	Case Temperature	-20~125	-20~125	°C
Junction Temperature	Tj		150	150	°C
Peak Input Voltage	Vin	②+,④-,Fig.1 is Measurement Circuit of Peak Input Voltage Vin and Collector Cutoff Current I _{CEX} .	500	500	V
Input Current	Iin	Pulse Pulse Width 150 μs MAX, Dutv1/2, Sawtooth Wave, Peak Value, ②+,④-	10	10	A
Maximum Operating Frequency	f(max)		200	200	kHz
Maximum Power Dissipation	P _D	Ta=25°C	3	3	W
		Heatsink Tc=100°C	20	20	W
Dielectric Strength	Vdis	Terminals To Case AC 1 min	2	2	kV
Insulation Resistance		Terminals To Case 500VDC	100	100	MΩ
Fold Back Control Voltage	V _{CONT(max)}	Fold Control Resistance=0Ω Duty 1/2, ④,⑦	±8	±8	V
Fold Back Control Current	I _{CONT(max)}	④-,⑥+	100	100	mA

●Electrical Characteristics (Tc=25°C)

Item	Symbol	Conditions	Ratings		Unit
			P Class	N Class	
Q1	Collector Cutoff Current	I _{CEX}	V _{CE} =500V, Fig.1 is Measurement Circuit of Peak Input Voltage Vin and Collector Cutoff Current I _{CEX} , ②+,④-		mA
	DC Current Gain	h _{FE}	V _{CE} = 5V, I _C = 5A, ②+,④-,⑤I _B		-
	Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C =5.0A, I _B =1.0A, ②+,④-,⑤I _B		V
	Thermal Resistance	θ _{jc}	Junction to Case		°C/W
D1	Reverse Current	I _R	V _R =450V,①+,②-		μA
	Forward Voltage	V _F	I _F =0.6A,①-,②+		V
Driving Saturation Voltage	V _{D(sat)}	I _C =1.5A, I _B =0.3A, ⑤+,④-	MIN 1.7	MIN 1.7	V
			MAX 2.3	MAX 2.3	



● Standard Operating Condition・Design Standard For Application Circuit

Item	Conditions	Ratings		Unit
		P Class	N Class	
Input Rated Voltage		AC90~132	AC90~132	V
Output Nominal Wattage		100	100	W
Output Nominal Voltage		15	15	V
Output Nominal Current		6.6	6.6	A

● Standard Operating Condition・Standard Operating Characteristics (Ta=25°C)

Item	Conditions	Ratings		Unit		
		P Class	N Class			
Minimum Input Full Load Output Voltage	Vin=90V, IO=6.6A	15.0±0.75	15.0±0.75	V	Fig 2, ① Refer	
Maximum Input Light Load Output Voltage	Vin=132V, IO=0.66A	15.0±0.75	15.0±0.75	V	Fig 2, ② Refer	
AC Input Voltage	IO=6.6A	MAX 85	MAX 85	V		
Over Current Protection	Foldback Current	Vin=132V, VO=12V	MAX 10	MAX 10	A	Fig 2, ③ Refer
	Short Circuit	Vin=132V, RO=0.5Ω	Nodamage To Any Device, Automatic Recovery.		-	Fig 2, ④ Refer
Output Ripple Noise	Vin=90~132V, IO=0.66~6.6A	MAX 150	MAX 150	mV P-P		

Figure in ○=Terminal Sign




Fig1. Measurement Circuit






Fig2. Output Voltage/Current

MA2450 Transient Thermal Impedance




MA2450

Forward Bias SOA




MA2450

Collector Current Derating



MA2450

Reverse Bias SOA



MA2450

$h_{FE} - I_C$

