


MA3830

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-30~125	°C
Operating Temperature	Top		-20~125	°C
Junction Temperature	Tj		150	°C
Peak Input Voltage	Vin	②+,④-,Fig.1 is Measurement Circuit of Peak Input Voltage Vin and Collector Cutoff Current I _{CEX} .	850	V
Input Current	Iin	DC ②+,④-	6	A
		Pulse ②+,④- Pulse Width 150 μs MAX, Duty 1/2, Sawtooth Wave, Peak Value.	12	A
Maximum Power Dissipation	P _D	Ta=25°C	3	W
	P _D	Heatsink Tc=100°C	22	W
Dielectric Strength	Vdis	Terminals To Case AC 1 min	2	kV
Insulation Resistance		Terminals To Case 500VDC	100	MΩ
Max Voltage ④ to ⑦	V④•⑦	④+,⑦-	6	V
Max Current ⑥ to ④	I⑥•④	⑥+,④- (Peak) Duty Max 3/5	100	mA
Max Current ⑤ to ④	I⑤•④	⑤+,④- (Q ₂ Collector Current)	500	mA

●Electrical Characteristics (Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit	
Q1	Collector Cutoff Current	I _{CEX}	V _{CE} =850V, Fig.1 is Measurement Circuit of Peak Input Voltage Vin and Collector Cutoff Current I _{CEX} , ②+,④-	MAX 100	μA
	DC Current Gain	h _{FE}	V _{CE} =5V, I _C =3.0A, ②+,④-,⑤I _B	11~22	
	Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C =3.0A, I _B =0.6A, ②+,④-,⑤I _B	MAX 1.0	V
				MIN 1.7	V
	Driving Saturation Voltage	V _{D(sat)}	I _C =1.5A, I _B =0.3A, ②+,④-,⑤I _B	MAX 2.3	V
Thermal Resistance	θ _{jc}	Junction to Case	MAX 2.2	°C/W	

●Standard Operating Condition*Design Standard For Application Circuit

Item	Conditions	Ratings	Unit
Input Rated Voltage		AC175~276	V
Output Nominal Wattage		100	W
Output Nominal Voltage		24	V
Output Nominal Current		4.2	A

●Standard Operating Condition*Standard Operating Characteristics (Ta=25°C)

Item	Conditions	Ratings	Unit	
AC Input Voltage	$I_0=4.2A, 20.5V \leq V_0 \leq 24.6V$	MAX 175	V	
Minimum Input Full Load Output Voltage	$V_{in}=180V, I_0=4.2A$	24.0 ± 0.6	V	Fig 2, ① Refer
Maximum Input Light Load Output Voltage	$V_{in}=276V, I_0=0.0A$	24.0 ± 0.6	V	Fig 2, ② Refer
Over Current Protection	Foldback Current	$V_{in}=276V, V_0=20V$	MAX 6.0	Fig 2, ③ Refer
	Short Circuit	$V_{in}=276V, R_0=0.5 \Omega$	Nodamage To Any Device, Automatic Recovery.	Fig 2, ④ Refer

Figure in ○=Terminal Sign




Fig1. Measurement Circuit






Fig2. Output Voltage/Current

MA3830 Transient Thermal Impedance




MA3830

Forward Bias SOA




MA3830

Collector Current Derating




MA3830

Reverse Bias SOA



MA3830

$h_{FE} - I_C$



Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com