



**MICROCIRCUIT DATA SHEET**

**MN54AC258-X REV 1B0**

Original Creation Date: 07/01/96

Last Update Date: 03/31/97

Last Major Revision Date: 07/01/96

**Quad 2 Input Multiplexer With TRI - STATE Outputs**

**General Description**

The AC258 is a quad 2-input multiplexer with 3-state outputs. Four bits of data from two sources can be selected using a Common Data Select Input. The four outputs present the selected data in the complement (inverted) form. The outputs may be switched to a high impedance state with a logic HIGH on the common Output Enable ( $\overline{OE}$ ) input, allowing the outputs to interface directly with bus-oriented systems.

**Industry Part Number**

54AC258

**Prime Die**

Z258

**NS Part Numbers**

54AC258DMQB

54AC258FMQB

54AC258LMQB

**Processing**

MIL-STD-883, Method 5004

**Quality Conformance Inspection**

MIL-STD-883, Method 5005

**Subgrp Description Temp (°C)**

|    |                     |      |
|----|---------------------|------|
| 1  | Static tests at     | +25  |
| 2  | Static tests at     | +125 |
| 3  | Static tests at     | -55  |
| 4  | Dynamic tests at    | +25  |
| 5  | Dynamic tests at    | +125 |
| 6  | Dynamic tests at    | -55  |
| 7  | Functional tests at | +25  |
| 8A | Functional tests at | +125 |
| 8B | Functional tests at | -55  |
| 9  | Switching tests at  | +25  |
| 10 | Switching tests at  | +125 |
| 11 | Switching tests at  | -55  |



**Features**

- $I_{cc}$  and  $I_{oz}$  reduced by 50%
- Multiplexer expansion by tying outputs together
- Inverting TRI-STATE outputs
- Outputs source/sink 24 mA
- Standard Military Drawing (SMD)
- AC258: 5962-91604

**(Absolute Maximum Ratings)**

(Note 1)

|   |                    |
|---|--------------------|
| Supply Voltage (Vcc)                                  | -0.5V to +7.0V     |
| DC Input Diode Current (Iik)                          |                    |
| Vi = -0.5V  | -20 mA             |
| Vi = Vcc +0.5V  | +20 mA             |
| DC Input Voltage (Vi)                                 | -0.5V to Vcc +0.5V |
| DC Output Diode Current (Iok)                         |                    |
| Vo = -0.5V  | -20 mA             |
| Vo = Vcc +0.5V  | +20 mA             |
| DC Output Voltage (Vo)                                | -0.5V to Vcc +0.5V |
| DC Output Source or Sink Current (Io)                 | ±50 mA             |
| DC Vcc or Ground Current Per Output Pin (Icc or Ignd) | ±50 mA             |
| Storage Temperature (Tstg)                            | -65 C to 150 C     |
| Junction Temperature (Tj)                             |                    |
| CDIP  | 175 C              |

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specification should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

**Recommended Operating Conditions**

|   |                 |
|---|-----------------|
| Supply Voltage (Vcc)                      | 2.0V to 6.0V    |
| Input Voltage (Vi)                        | 0V to Vcc       |
| Output Voltage (Vo)                       | 0V to Vcc       |
| Operating Temperature (Ta)                | -55 C to +125 C |
| Minimum Input Edge Rate (Delta V/Delta t) |                 |
| AC Devices                                |                 |
| Vin from 30% to 70% of Vcc                |                 |
| Vcc @ 3.0V, 4.5V, 5.5V                    | 125 mV/ns       |

## Electrical Characteristics

### DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 3.0V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

| SYMBOL                                      | PARAMETER                   | CONDITIONS                                   | NOTES   | PIN-NAME | MIN  | MAX     | UNIT | SUB-GROUPS |
|---|-----------------------------|--|---------|----------|------|---------|------|------------|
| IIH   | High Level Input Current    | VCC=5.5V, VM=5.5V, VINL=0.0V                 | 1, 2    | INPUTS   |      | 0.1     | uA   | 1          |
|   |                             |  | 1, 2    | INPUTS   |      | 1.0     | uA   | 2, 3       |
| IIL   | Low Level Input Current     | VCC=5.5V, VM=0.0V, VINH=5.5V                 | 1, 2    | INPUTS   |      | -0.1    | uA   | 1          |
|   |                             |  | 1, 2    | INPUTS   |      | -1.0    | uA   | 2, 3       |
| VOL   | Low level output voltage    | VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=12.0mA     | 1, 2    | OUTPUTS  |      | .36     | V    | 1          |
|   |                             |  | 1, 2    | OUTPUTS  |      | .50     | V    | 2, 3       |
|   |                             | VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=50.0uA     | 1, 2    | OUTPUTS  |      | .10     | V    | 1, 2, 3    |
|   |                             |  | 1, 2    | OUTPUTS  |      | .10     | V    | 1, 2, 3    |
|   |                             | VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=24.0mA   | 1, 2    | OUTPUTS  |      | .36     | V    | 1          |
|   |                             |  | 1, 2    | OUTPUTS  |      | .50     | V    | 2, 3       |
|   |                             | VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=50.0uA   | 1, 2    | OUTPUTS  |      | .10     | V    | 1, 2, 3    |
|   |                             |  | 1, 2    | OUTPUTS  |      | .36     | V    | 1          |
| VCC=4.5V, VIH=3.15V, VIL=1.35V, IOL=24.0mA  | 1, 2                        | OUTPUTS                                      |         | .36      | V    | 1       |      |            |
|   | 1, 2                        | OUTPUTS                                      |         | .50      | V    | 2, 3    |      |            |
| VIOL  | Dynamic output current LOW  | VCC=5.5V, VINH=3.85V, VIL=1.65V, IOL=50.0mA, | 1, 2, 5 | OUTPUTS  |      | 1.65    | V    | 1, 2, 3    |
| VOH   | High level output voltage   | VCC=3.0V, VIH=2.1V, VIL=0.9V, IOH=-50.0uA    | 1, 2    | OUTPUTS  | 2.90 |         | V    | 1, 2, 3    |
|   |                             |  | 1, 2    | OUTPUTS  | 2.56 |         | V    | 1          |
|   |                             | VCC=3.0V, VIH=2.1V, VIL=0.9V, IOH=-12.0mA    | 1, 2    | OUTPUTS  | 2.40 |         | V    | 2, 3       |
|   |                             |  | 1, 2    | OUTPUTS  | 4.86 |         | V    | 1          |
|   |                             | VCC=5.5V, VIH=3.85V, VIL=1.65V, IOH=-24.0mA  | 1, 2    | OUTPUTS  | 4.70 |         | V    | 2, 3       |
|   |                             |  | 1, 2    | OUTPUTS  | 3.86 |         | V    | 1          |
|   |                             | VCC=4.5V, VIH=3.15V, VIL=1.35V, IOH=-24.0mA  | 1, 2    | OUTPUTS  | 3.70 |         | V    | 2, 3       |
|   |                             |  | 1, 2    | OUTPUTS  | 4.40 |         | V    | 1, 2, 3    |
| VCC=4.5V, VIH=3.15V, VIL=1.35V, IOH=-50.0uA | 1, 2                        | OUTPUTS                                      | 4.40    |          | V    | 1, 2, 3 |      |            |
|   | 1, 2                        | OUTPUTS                                      | 5.40    |          | V    | 1, 2, 3 |      |            |
| VCC=5.5V, VIH=3.85V, VIL=1.65V, IOH=-50.0uA | 1, 2                        | OUTPUTS                                      | 5.40    |          | V    | 1, 2, 3 |      |            |
|   | 1, 2                        | OUTPUTS                                      | 5.40    |          | V    | 1, 2, 3 |      |            |
| VIOH  | Dynamic output current HIGH | VCC=5.5V, VIH=5.5V, VIL=1.65V, IOH = -50mA   | 1, 2, 5 | OUTPUTS  | 3.85 |         | V    | 1, 2, 3    |

## Electrical Characteristics

### DC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 DC: VCC 3.0V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

| SYMBOL | PARAMETER                              | CONDITIONS                              | NOTES | PIN-NAME | MIN | MAX   | UNIT | SUB-GROUPS |
|--------|--|---|-------|----------|-----|-------|------|------------|
| IOZH   | Maximum TRI-STATE Leakage Current High | VCC=3.0V, VM=3.0V, VINL=0.0V, VIH=2.1V  | 1, 2  | OUTPUTS  |     | 0.25  | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | 5.00  | uA   | 2, 3       |
|        |  | VCC=4.5V, VM=4.5V, VINL=0.0V, VIH=3.15V | 1, 2  | OUTPUTS  |     | 0.25  | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | 5.00  | uA   | 2, 3       |
|        |  | VCC=5.5V, VM=5.5V, VINL=0.0V, VIH=3.85V | 1, 2  | OUTPUTS  |     | 0.25  | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | 5.00  | uA   | 2, 3       |
| IOZL   | Maximum TRI-STATE Leakage Current Low  | VCC=3.0V, VM=0.0V, VINH=3.0V, VIH=2.1V  | 1, 2  | OUTPUTS  |     | -0.25 | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | -5.00 | uA   | 2, 3       |
|        |  | VCC=4.5V, VM=0.0V, VINH=4.5V, VIH=3.15V | 1, 2  | OUTPUTS  |     | -0.25 | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | -5.00 | uA   | 2, 3       |
|        |  | VCC=5.5V, VM=0.0V, VINH=5.5V, VIH=3.85V | 1, 2  | OUTPUTS  |     | -0.25 | uA   | 1          |
|        |  |   | 1, 2  | OUTPUTS  |     | -5.00 | uA   | 2, 3       |
| ICCH   | Supply Current Outputs HIGH            | VCC=5.5V, VINH=5.5V, VINL=0.0V          | 1, 2  | VCC      |     | 4.0   | uA   | 1          |
|        |  |   | 1, 2  | VCC      |     | 80    | uA   | 2, 3       |
| ICCL   | Supply Current Outputs LOW             | VCC=5.5V, VINL=0.0V                     | 1, 2  | VCC      |     | 4.0   | uA   | 1          |
|        |  |   | 1, 2  | VCC      |     | 80    | uA   | 2, 3       |
| IC CZ  | Supply Current Outputs Tri-State       | VCC=5.5V, VINH=5.5V, VINL=0.0V          | 1, 2  | VCC      |     | 4.0   | uA   | 1          |
|        |  |   | 1, 2  | VCC      |     | 80    | uA   | 2, 3       |

### AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

|         |                   |          |         |          |     |      |    |        |
|---------|-------------------|----------|---------|----------|-----|------|----|--------|
| tpLH(1) | Propagation Delay | VCC=4.5V | 3, 4, 6 | Sn to Zn | 1.5 | 9.50 | ns | 9      |
|         |                   |          | 3, 4, 6 | Sn to Zn | 1.5 | 11.5 | ns | 10, 11 |
| tpHL(1) | Propagation Delay | VCC=4.5V | 3, 4, 6 | Sn to Zn | 1.5 | 9.00 | ns | 9      |
|         |                   |          | 3, 4, 6 | Sn to Zn | 1.5 | 10.5 | ns | 10, 11 |

## Electrical Characteristics

### AC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

| SYMBOL  | PARAMETER           | CONDITIONS | NOTES   | PIN-NAME                           | MIN | MAX  | UNIT | SUB-GROUPS |
|---------|---------------------|------------|---------|------------------------------------|-----|------|------|------------|
| tpLH(2) | Propagation Delay   | VCC=4.5V   | 3, 4, 6 | In to $\overline{Zn}$              | 1.5 | 7.5  | ns   | 9          |
|         |                     |            | 3, 4, 6 | In to $\overline{Zn}$              | 1.5 | 9.5  | ns   | 10, 11     |
| tpHL(2) | Propagation Delay   | VCC=4.5V   | 3, 4, 6 | In to $\overline{Zn}$              | 1.5 | 6.5  | ns   | 9          |
|         |                     |            | 3, 4, 6 | In to $\overline{Zn}$              | 1.5 | 7.5  | ns   | 10, 11     |
| tpZH(1) | Output Enable Time  | VCC=4.5V   | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 7.50 | ns   | 9          |
|         |                     |            | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 9.0  | ns   | 10, 11     |
| tpZL(1) | Output Enable Time  | VCC=4.5V   | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 7.0  | ns   | 9          |
|         |                     |            | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 8.5  | ns   | 10, 11     |
| tpHZ(1) | Output Disable Time | VCC=4.5V   | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 8.50 | ns   | 9          |
|         |                     |            | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 9.50 | ns   | 10, 11     |
| tpLZ(1) | Output Disable Time | VCC=4.5V   | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 7.0  | ns   | 9          |
|         |                     |            | 3, 4, 6 | $\overline{OE}$ to $\overline{Zn}$ | 1.5 | 8.5  | ns   | 10, 11     |
| tpLH(3) | Propagation Delay   | VCC=3.0V   | 3, 4    | Sn to $\overline{Zn}$              | 1.0 | 12.0 | ns   | 9          |
|         |                     |            | 3, 4    | Sn to $\overline{Zn}$              | 1.0 | 15.0 | ns   | 10, 11     |
| tpHL(3) | Propagation Delay   | VCC=3.0V   | 3, 4    | Sn to $\overline{Zn}$              | 1.0 | 11.5 | ns   | 9          |
|         |                     |            | 3, 4    | Sn to $\overline{Zn}$              | 1.0 | 14.0 | ns   | 10, 11     |
| tpLH(4) | Propagation Delay   | VCC=3.0V   | 3, 4    | In to $\overline{Zn}$              | 1.0 | 9.50 | ns   | 9          |
|         |                     |            | 3, 4    | In to $\overline{Zn}$              | 1.0 | 12.0 | ns   | 10, 11     |
| tpHL(4) | Propagation Delay   | VCC=3.0V   | 3, 4    | In to $\overline{Zn}$              | 1.0 | 8.50 | ns   | 9          |
|         |                     |            | 3, 4    | In to $\overline{Zn}$              | 1.0 | 10.5 | ns   | 10, 11     |

## Electrical Characteristics

### AC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

| SYMBOL  | PARAMETER           | CONDITIONS | NOTES | PIN-NAME                           | MIN | MAX  | UNIT | SUB-GROUPS |
|---------|---------------------|------------|-------|------------------------------------|-----|------|------|------------|
| tpZH(2) | Output Enable Time  | VCC=3.0V   | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 9.50 | ns   | 9          |
|         |                     |            | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 11.5 | ns   | 10, 11     |
| tpZL(2) | Output Enable Time  | VCC=3.0V   | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 9.00 | ns   | 9          |
|         |                     |            | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 10.5 | ns   | 10, 11     |
| tpHZ(2) | Output Disable Time | VCC=3.0V   | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 10.0 | ns   | 9          |
|         |                     |            | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 11.5 | ns   | 10, 11     |
| tpLZ(2) | Output Disable Time | VCC=3.0V   | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 9.00 | ns   | 9          |
|         |                     |            | 3, 4  | $\overline{OE}$ to $\overline{Zn}$ | 1.0 | 10.5 | ns   | 10, 11     |

Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.

Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C, TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.

Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY, SUBGROUP A9.

Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.

Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBAND LIMITS SET FOR +25C, 2MSEC DURATION MAX.

Note 6: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.