查询MSA-0785供应商

捷多邦，专业PCB打样工厂，24小时加急出货

HEWLETT® PACKARD

Cascadable Silicon Bipolar MMIC Amplifier

Technical Data

MSA-0785

Features

- **Cascadable 50 Ω Gain Block**
- **Low Operating Voltage:** 4.0 V Typical V_d
- **3 dB Bandwidth:** DC to 2.0 GHz
- **12.5 dB Typical Gain at 1.0 GHz**
- **Unconditionally Stable (k>1)**
- **Low Cost Plastic Package**

Description

The MSA-0785 is a high performance silicon bipolar Monolithic Microwave Integrated Circuit (MMIC) housed in a low cost plastic package. This MMIC is designed for use as a general purpose 50 Ω gain block. Typical applications include narrow and broad band IF and RF amplifiers in commercial and industrial applications.

The MSA-series is fabricated using HP's 10 GHz f_T, 25 GHz f_{MAX}, silicon bipolar MMIC process which uses nitride self-alignment, ion implantation, and gold metallization to achieve excellent performance, uniformity and reliability. The use of an external bias resistor for temperature and current stability also allows bias flexibility.

85 Plastic Package



Typical Biasing Configuration



找PDF 维库一下 pdf.dzsc.com

MSA-0785 Absolute Maximum Ratings

Parameter	Absolute Maximum[1]
Device Current	60 mA
Power Dissipation[2,3]	275 mW
RF Input Power	+13 dBm
Junction Temperature	150°C
Storage Temperature	–65 to 150°C

Thermal Resistance[2,4]:
θ_{jc} = 110°C/W

Notes:
1. Permanent damage may occur if any of these limits are exceeded.
2. T_{CASE} = 25°C.
3. Derate at 9.1 mW/°C for T_C > 120°C.
4. See MEASUREMENTS section "Thermal Resistance" for more information.

Electrical Specifications[1], T_A = 25°C

Symbol	Parameters and Test Conditions: I_d = 22 mA, Z_O = 50 Ω		Units	Min.	Typ.	Max.
G_P	Power Gain ($\|S_{21}\|^2$)	f = 0.1 GHz f = 1.0 GHz	dB	 10.5	13.5 12.5	
ΔG_P	Gain Flatness	f = 0.1 to 1.3 GHz	dB		± 0.7	
$f_{3\,dB}$	3 dB Bandwidth		GHz		2.0	
VSWR	Input VSWR	f = 0.1 to 2.5 GHz			1.4:1	
	Output VSWR	f = 0.1 to 2.5 GHz			1.5:1	
NF	50 Ω Noise Figure	f = 1.0 GHz	dB		5.0	
$P_{1\,dB}$	Output Power at 1 dB Gain Compression	f = 1.0 GHz	dBm		5.5	
IP_3	Third Order Intercept Point	f = 1.0 GHz	dBm		19.0	
t_D	Group Delay	f = 1.0 GHz	psec		140	
V_d	Device Voltage		V	3.2	4.0	4.8
dV/dT	Device Voltage Temperature Coefficient		mV/°C		–7.0	

Note:
1. The recommended operating current range for this device is 15 to 40 mA. Typical performance as a function of current is on the following page.

MSA-0785 Typical Scattering Parameters (Z_O = 50 Ω, T_A = 25°C, I_d = 22 mA)

Freq. GHz	S_{11}		S_{21}			S_{12}			S_{22}	
	Mag	Ang	dB	Mag	Ang	dB	Mag	Ang	Mag	Ang
0.1	.05	166	13.5	4.73	174	–18.4	.120	1	.14	–11
0.2	.05	151	13.4	4.70	169	–18.3	.122	3	.14	–21
0.4	.04	115	13.3	4.63	158	–18.3	.121	6	.14	–40
0.6	.04	65	13.1	4.53	148	–18.0	.125	7	.16	–58
0.8	.05	26	12.9	4.41	138	–17.8	.139	9	.17	–71
1.0	.06	–5	12.6	4.25	127	–17.6	.132	10	.18	–84
1.5	.08	–51	11.6	3.82	104	–16.5	.149	12	.18	–109
2.0	.11	–99	10.5	3.33	82	–15.9	.161	11	.17	–126
2.5	.14	–127	9.3	2.91	68	–15.2	.174	13	.16	–134
3.0	.20	–154	7.9	2.48	52	–14.8	.183	7	.16	–139
3.5	.25	–173	6.7	2.16	37	–14.7	.184	5	.16	–132
4.0	.29	171	5.5	1.88	23	–14.8	.182	1	.18	–130
5.0	.35	139	3.5	1.50	–1	–14.3	.193	–6	.21	–133
6.0	.46	100	1.7	1.22	–26	–14.5	.189	–14	.20	–169

A model for this device is available in the DEVICE MODELS section.

Typical Performance, T_A = 25°C

(unless otherwise noted)



Figure 1. Typical Power Gain vs. Frequency, I_d = 22 mA.



Figure 2. Device Current vs. Voltage.



Figure 3. Power Power Gain vs. Current.



Figure 4. Output Power at 1 dB Gain Compression, NF and Power Gain vs. Case Temperature, f = 1.0 GHz, I_d=22mA.



Figure 5. Output Power at 1 dB Gain Compression vs. Frequency.



Figure 6. Noise Figure vs. Frequency.

85 Plastic Package Dimensions