

INTERNATIONAL RECTIFIER



1N1183, 1N3765, 1N1183A, 1N2128A SERIES

35, 40 and 60 Amp Power Silicon Rectifier Diodes

Major Ratings and Characteristics



	1N1183	1N3765	1N1183A	1N2128A	Units
$I_F(AV)$	35*	35*	40*	60*	A
@ Max. T_C	140*	140*	150*	140*	°C
I_{FSM} @ 50 Hz	480	380	765	860	A
@ 60 Hz	500*	400*	800*	900*	
I_T @ 50 Hz	1140	730	2900	3700	
@ 60 Hz	1040	670	2650	3400	A ² s
I^2/t	16 100	10 300	41 000	52 500	A ² /s
V_{RRM} Range	50* to 800*	700* to 1000*	50* to 600*	50* to 600*	V

*JEDEC registered values.

Description and Features

- Low leakage current series
- Good surge current capability up to 1000 amps
- Can be supplied to meet stringent military, aerospace and other high-reliability requirements.

CASE STYLE AND DIMENSIONS



Conforms to JEDEC Outline DO-203AB (DO-5)
Dimensions in Millimeters and (Inches)

VOLTAGE RATINGS

Part Number ①			V_{RRM} - Max. Repetitive Peak Reverse Voltage (V)	V_R - Max. Direct Reverse Voltage (V)
			$T_C = -65^\circ\text{C to } 200^\circ\text{C} ②$	$T_C = -65^\circ\text{C to } 200^\circ\text{C} ②$
1N1183	1N1183A	1N2128A	50*	50*
1N1184	1N1184A	1N2129A	100*	100*
1N1185	1N1185A	1N2130A	150*	150*
1N1186	1N1186A	1N2131A	200*	200*
1N1187	1N1187A	1N2133A	300*	300*
1N1188	1N1188A	1N2135A	400*	400*
1N1189	1N1189A	1N2137A	500*	500*
1N1190	1N1190A	1N2138A	600*	600*
1N3765			700*	700*
1N3766			800*	800*
1N3767			900*	900*
1N3768			1000*	1000*

ELECTRICAL SPECIFICATIONS

	1N1183	1N3765	1N1183A	1N2128A	Units	Conditions
$I_{F(AV)}$ Max. average forward current @ Max. T_C	35*	35*	40*	60*	A	1-phase operation, 180° conduction
	140*	140*	150*	140*	$^\circ\text{C}$	
I_{FSM} Max. peak one-cycle non-repetitive surge current	480	380	765	880	A	Half cycle 50 Hz sine wave or 5 ms rectangular pulse
	500*	400*	800*	900*		Following any rated load condition and with rated V_{RRM} applied.
	570	455	910	1000	A	Half cycle 60 Hz sine wave or 5 ms rectangular pulse
	595	475	950	1050		Following any rated load condition and with $\frac{1}{2}$ V_{RRM} applied following surge = 0
i^2t Max. i^2t for fusing	1140	730	2900	3700	A^2s	$t = 10\text{ms}$ With rated V_{RRM} applied following surge, initial $T_J = T_J \text{ max.}$
	1040	670	2650	3400		$t = 8.3\text{ms}$
	1610	1030	4150	5250		$t = 10\text{ms}$ With $V_{RRM} = 0$ following surge, initial $T_J = T_J \text{ max.}$
	1470	940	3750	4750		$t = 8.3\text{ms}$
$i^2\sqrt{t}$ Max. $i^2\sqrt{t}$ for individual device fusing ③	16 100	10 300	41 500	52 500	$\text{A}^2\sqrt{\text{s}}$	$t = 0.1$ to 10ms , $V_{RRM} = 0$ following surge.
V_{FM} Max. peak forward voltage @ I_{FM}	1.7*	1.8*	1.3*	1.3*	V	$T_J = 25^\circ\text{C}$
	110	110	126	188	A	
$I_{R(AV)}$ Max. average reverse current	—	5.0*	—	—	mA	Max. rated $I_{F(AV)}$ and T_C , $V_{RRM} = 700\text{V}$
	—	4.0*	—	—		800V
	—	3.0*	—	—		900V
	—	2.0*	—	—		1000V
	10*	—	2.5*	10*	mA	Max. rated $I_{F(AV)}$, V_{RRM} and T_C

① Basic part number indicates cathode-to-case. For anode-to-case, add "R" to part number, i.e., 1N1188R, 1N3766R, 1N1186RA, 1N2135RA

② For 1N1183 series and 1N3765 series $T_C = -65$ to 190°C .③ i^2t for $t_{AX} = i_X^2 \sqrt{t_X} \cdot \sqrt{t_{AX}}$

* JEDEC registered values.

/ rated load
with rated
d.

/ rated load
with 1/2
d following

wing

3,




Fig. 1 - Maximum Allowable Case Temperature Vs. Average Forward Current, 1N1183 and 1N3765 Series




Fig. 2 - Typical Loss Vs. Average Current Waveform




Fig. 3 - Typical High Level Forward Power Loss Vs. Average Forward Current (Sinusoidal Current Waveform), 1N1183 and 1N3765 Series




Fig. 4 - Typical Forward Power Loss Vs. Instantaneous Forward Current, 1N1183 and 1N3765 Series




Fig. 5 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses, 1N1183 and 1N3765 Series




Fig. 6 - Average Forward Current Vs. Maximum Allowable Case Temperature, 1N1183A Series




Fig. 8 - Maximum High Level Forward Power Loss Vs. Average Forward Current, 1N1183A Series.




Fig. 7 - Maximum Low Level Forward Power Loss Vs. Average Forward Current, 1N1183A Series




Fig. 9 - Maximum Forward Voltage Vs. Forward Current, 1N1183A Series




Fig. 10 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses, 1N1183A Series




Fig. 11 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses, 1N2128A Series




Fig. 12 - Maximum Allowable Case Temperature Vs. Average Forward Current, 1N2128A Series




Fig. 13 - Maximum Low Level Forward Power Loss Vs. Average Forward Current, 1N2128A Series




Fig. 14 - Maximum High Level Forward Power Loss Vs. Average Forward Current, 1N2128A Series




Fig. 15 - Maximum Forward Voltage Vs. Forward Current, 1N2128A Series

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com