



February 1997
Revised June 2000

NC7ST04 TinyLogic™ HST Inverter


General Description

The NC7ST04 is a single high performance CMOS Inverter, with TTL-compatible inputs. Advanced Silicon Gate CMOS fabrication assures high speed and low power circuit operation. ESD protection diodes inherently guard both input and output with respect to the V_{CC} and GND rails. High gain circuitry offers high noise immunity and reduced sensitivity to input edge rate. The TTL-compatible input facilitates TTL to NMOS/CMOS interfacing. Device performance is similar to MM74HCT but with $\frac{1}{2}$ the output current drive of HC/HCT.


Ordering Code:

Order Number	Package Number	Product Code Top Mark	Package Description	Supplied As
NC7ST04M5	MA05B	8S04	5-Lead SOT23, JEDEC MO-178, 1.6mm	250 Units on Tape and Reel
NC7ST04M5X	MA05B	8S04	5-Lead SOT23, JEDEC MO-178, 1.6mm	3k Units on Tape and Reel
NC7ST04P5	MAA05A	T04	5-Lead SC70, EIAJ SC-88a, 1.25mm Wide	250 Units on Tape and Reel
NC7ST04P5X	MAA05A	T04	5-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3k Units on Tape and Reel

Logic Symbol



Connection Diagram



Pin Descriptions

Pin Names	Description
A	Input
Y	Output
NC	No Connect

Function Table

Y = \bar{A}	
Input	Output
A	Y
L	H
H	L

H = HIGH Logic Level
L = LOW Logic Level

TinyLogic™ is a trademark of Fairchild Semiconductor Corporation.

NC7ST04 TinyLogic™ HST Inverter


Absolute Maximum Ratings ^(Note 1)						Recommended Operating Conditions ^(Note 2)		
Supply Voltage (V_{CC})			-0.5V to +7.0V			Supply Voltage	4.5V–5.5V	
DC Input Diode Current (I_{IK})						Input Voltage (V_{IN})	0V– V_{CC}	
$V_{IN} < -0.5V$			-20 mA			Output Voltage (V_{OUT})	0V– V_{CC}	
$V_{IN} \geq V_{CC} + 0.5V$			+20 mA			Operating Temperature (T_A)	-40°C to +85°C	
DC Input Voltage (V_{IN})			-0.5V to $V_{CC} + 0.5V$			Input Rise and Fall Time (t_r, t_f)		
DC Output Diode Current (I_{OK})						$V_{CC} = 5.0V$	0–500 ns	
$V_{OUT} < -0.5V$			-20 mA			Thermal Resistance (θ_{JA})		
$V_{OUT} > V_{CC} + 0.5V$			+20 mA			SOT23-5	300°C/W	
Output Voltage (V_{OUT})			-0.5V to $V_{CC} + 0.5V$			SC70-5	425°C/W	
DC Output Source or Sink Current (I_{OUT})								
DC V_{CC} or Ground Current per Supply Pin (I_{CC} or I_{GND})			± 25 mA					
Storage Temperature (T_{STG})			-65°C to +150°C					
Junction Temperature (T_J)			150°C					
DC V_{CC} or Ground Current per (Soldering, 10 seconds)			260°C					
Power Dissipation (P_D) @ +85°C								
SOT23-5			200 mW					
SC70-5			150 mW					
DC Electrical Characteristics								
Symbol	Parameter	V_{CC} (V)	$T_A = +25^\circ\text{C}$		$T_A = -40^\circ\text{C to } +85^\circ\text{C}$		Units	Conditions
			Min	Typ	Max	Min		
V_{IH}	HIGH Level Input Voltage	4.5–5.5	2.0		2.0	V		
V_{IL}	LOW Level Input Voltage	4.5–5.5		0.8	0.8	V		
V_{OH}	HIGH Level Output Voltage	4.5	4.4	4.5		V	$I_{OH} = -20 \mu\text{A}, V_{IN} = V_{IL}$,	
		4.5	4.18	4.35	4.13	V	$I_{OH} = -2 \text{ mA}$	
V_{OL}	LOW Level Output Voltage	4.5	0	0.1	0.1	V	$I_{OL} = 20 \mu\text{A}, V_{IN} = V_{IH}$,	
		4.5		0.10	0.26	V	$I_{OL} = 2 \text{ mA}$	
I_{IN}	Input Leakage Current	5.5		± 0.1	± 1.0	μA	$0 \leq V_{IN} \leq 5.5\text{V}$	
I_{CC}	Quiescent Supply Current	5.5		1.0	10.0	μA	$V_{IN} = V_{CC}$ or GND	
I_{CCT}	I_{CC} per Input	5.5		2.0	2.9	mA	Input $V_{IN} = 0.5\text{V}$ or 2.4V	

AC Electrical Characteristics

Symbol	Parameter	V _{CC} (V)	T _A = +25°C			T _A = -40°C to +85°C		Units	Conditions	Fig. No.
			Min	Typ	Max	Min	Max			
t _{PLH} , t _{PHL}	Propagation Delay	5.0	3.5	12				ns	C _L = 15 pF	Figures 1, 3
			6.0	17					C _L = 50 pF	
		4.5	6.2	16		20		ns		
			11.4	27		31				
		5.5	4.3	14		18		ns		
			11.1	26		30				
t _{TLH} , t _{THL}	Output Transition Time	5.0	4	10				ns	C _L = 15 pF	Figures 1, 3
		4.5	11	25		31			C _L = 50 pF	
		5.5	10	21		26				
C _{IN}	Input Capacitance	Open	2	10				pF		
C _{PD}	Power Dissipation Capacitance	5.0	6					pF	(Note 3)	Figure 2

Note 3: C_{PD} is defined as the value of the internal equivalent capacitance which is derived from dynamic operating current consumption (I_{CCD}) at no output loading and operating at 50% duty cycle. (See Figure 2.) C_{PD} is related to I_{CCD} dynamic operating current by the expression:
 $I_{CCD} = (C_{PD}) (V_{CC}) (f_{IN}) + (I_{CCstatic})$.


AC Loading and Waveforms



C_L includes load and stray capacitance

Input PRR = 1.0 MHz, t_w = 500 ns

FIGURE 1. AC Test Circuit



Input = AC Waveform; PRR = Variable; Duty Cycle = 50%

FIGURE 2. I_{CCD} Test Circuit





FIGURE 3. AC Waveforms

Tape and Reel Specification

TAPE FORMAT

Package Designator	Tape Section	Number Cavities	Cavity Status	Cover Tape Status
M5, P5	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	250	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed
M5X, P5X	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed


TAPE DIMENSIONS inches (millimeters)



Package	Tape Size	DIM A	DIM B	DIM F	DIM Ko	DIM P1	DIM W
SC70-5	8 mm	0.093 (2.35)	0.096 (2.45)	0.138 ± 0.004 (3.5 ± 0.10)	0.053 ± 0.004 (1.35 ± 0.10)	0.157 (4)	0.315 ± 0.004 (8 ± 0.1)
SOT23-5	8 mm	0.130 (3.3)	0.130 (3.3)	0.138 ± 0.002 (3.5 ± 0.05)	0.055 ± 0.004 (1.4 ± 0.11)	0.157 (4)	0.315 ± 0.012 (8 ± 0.3)

Tape and Reel Specification (Continued)


REEL DIMENSIONS inches (millimeters)





Tape Size	A	B	C	D	N	W1	W2	W3
8 mm	7.0 (177.8)	0.059 (1.50)	0.512 (13.00)	0.795 (20.20)	2.165 (55.00)	0.331 + 0.059/-0.000 (8.40 + 1.50/-0.00)	0.567 (14.40)	W1 + 0.078/-0.039 (W1 + 2.00/-1.00)

NC7ST04

Physical Dimensions inches (millimeters) unless otherwise noted



LAND PATTERN RECOMMENDATION




NOTES: UNLESS OTHERWISE SPECIFIED
A) THIS PACKAGE CONFORMS TO JEDEC
MO-178, ISSUE B, VARIATION AA,
DATED JANUARY 1999.
B) ALL DIMENSIONS ARE IN MILLIMETERS.

MA05BRevC

DETAIL A

5-Lead SOT23, JEDEC MO-178, 1.6mm
Package Number MA05B

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)**NOTES:**

- A. CONFORMS TO EIAJ REGISTERED OUTLINE DRAWING SC88A.
- B. DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH.
- C. DIMENSIONS ARE IN MILLIMETERS.

MAA05ARevC

**5-Lead SC70, EIAJ SC-88a, 1.25mm Wide
Package Number MAA05A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com