


SPDT SWITCH GaAs MMIC

■GENERAL DESCRIPTION

NJG1507R is a GaAs SPDT switch IC which exhibits low loss and high isolation, and ideally suitable for T/R switch of the digital wireless phone.

This switch is operated in the wide frequency range from 50MHz to 3.0GHz at low operating voltage from +2.5V with small VSP8 package.

■PACKAGE OUTLINE




NJG1507R

■FEATURES

- Single and low positive supply voltage
- Low insertion loss
- Transmission power
- High isolation
- Low control current
- Package

+2.5~+5.5V
 0.5dB typ. @ $f=2\text{GHz}$, $P_{in}=22\text{dBm}$
 27dBm max. @ $f=2\text{GHz}$, $V_{CTR}=3.0\text{V}$
 33dB typ. @ $f=2\text{GHz}$, $P_{in}=22\text{dBm}$
 5uA typ. @ $f=0.05\text{~}2.5\text{GHz}$, $P_{in}=22\text{dBm}$
 VSP8 (Mount Size: 4.0x2.9x1.2mm)

■PIN CONFIGURATION



■TRUTH TABLE

$H = V_{CTR(H)}$, $L = V_{CTR(L)}$

V_{CTR1}	H	L	L	H
V_{CTR2}	L	H	L	H
P1-PC	OFF	ON	Loss =15dB P_1 Return Loss =-3dB	Loss =16dB P_1 Return Loss =-2dB
P2-PC	ON	OFF	Loss =15dB P_2 Return Loss =-3dB	Loss =16dB P_2 Return Loss =-2dB

Note) The values of "Loss" and "Return Loss" are typical values at 2.0GHz.

NJG1507R

■ABSOLUTE MAXIMUM RATINGS

($T_a=25^\circ\text{C}$, $Z_s=Z_l=50\Omega$)

PARAMETER	SYMBOL	RATINGS	UNITS
Input power	P_{in}	33	dBm
Control voltage	V_{CTR}	6.0	V
Power dissipation	P_D	320	mW
Operating Temp.	T_{opr}	-30~+85	°C
Storage Temp.	T_{stg}	-40~+150	°C



■ELECTRICAL CHARACTERISTICS

($V_{CTR(L)}=0\text{V}$, $V_{CTR(H)}=2.7\text{V}$, $Z_s=Z_o=50\Omega$, $T_a=25^\circ\text{C}$)



PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Control voltage (L)	$V_{CTR(L)}$	$f=0.05\text{~}2.5\text{GHz}$, $P_{in}=22\text{dBm}$	-0.2	0	0.2	V
Control voltage (H)	$V_{CTR(H)}$	$f=0.05\text{~}2.5\text{GHz}$, $P_{in}=22\text{dBm}$	2.5	2.7	5.5	V
Control current	I_{CTR}	$f=0.05\text{~}2.5\text{GHz}$, $P_{in}=22\text{dBm}$	-	5.0	8.0	uA
Insertion loss1	LOSS1	$f=1.0\text{GHz}$, $P_{in}=22\text{dBm}$	-	0.4	0.7	dB
Insertion loss2	LOSS2	$f=2.0\text{GHz}$, $P_{in}=22\text{dBm}$	-	0.5	0.8	dB
Isolation 1 (PC-P1, PC-P2, P1-P2)	ISL1	$f=1.0\text{GHz}$, $P_{in}=22\text{dBm}$	25	31	-	dB
Isolation 2 (PC-P1, PC-P2, P1-P2)	ISL2	$f=2.0\text{GHz}$, $P_{in}=22\text{dBm}$	25	33	-	dB
Pin at 1dB compression point 1	$P_{-1\text{dB}}(1)$	$f=2.0\text{GHz}$	26	28	-	dBm
Pin at 1dB compression point 2	$P_{-1\text{dB}}(2)$	$V_{CTR(H)}=3.0\text{V}$, $f=2.0\text{GHz}$	27	30	-	dBm
VSWR	VSWR	$f=0.05\text{~}2.5\text{GHz}$, ON STATE	-	1.2	1.5	
Switching time	T_{SW}	$f=0.05\text{~}2.5\text{GHz}$	-	15	-	ns

■TYPICAL CHARACTERISTICS



(PC-P1) Insertion loss vs. Frequency
($V_{CTR}=0V/2.7V$, $P_{in}=22dBm$)





(PC-P2) Insertion loss vs. Frequency
($V_{CTR}=0V/2.7V$, $P_{in}=22dBm$)



(PC-P1) Isolation vs. Frequency
($V_{CTR}=0V/2.7V$, $P_{in}=22dBm$)



(PC-P2) Isolation vs. Frequency
($V_{CTR}=0V/2.7V$, $P_{in}=22dBm$)





NJG1507R

■TYPICAL CHARACTERISTICS



P1-PC(ON) V.S.W.R vs. Frequency

($V_{CTR}=0V/2.7V$, $P_{in}=0dBm$)





PC-P2(ON) V.S.W.R vs. Frequency

($V_{CTR}=0V/2.7V$, $P_{in}=0dBm$)









PC-P1(ON) V.S.W.R vs. Frequency

($V_{CTR}=0V/2.7V$, $P_{in}=0dBm$)







■TYPICAL CHARACTERISTICS



NJG1507R

■TYPICAL CHARACTERISTICS



NJG1507R

■ TYPICAL CHARACTERISTICS


600kHz ACP (Ta=25°C)

DQPSK Modulation Signal (without D.U.T)

$f_{ip} = 1.9\text{GHz}$ $P_{ip} = 22\text{dBm}$

MODULATION : 384Kbps RNYQ $\alpha=0.5$ $1/4 \pi$ DQPSK

ATTEN 20d8
RL 10.05d8




D. U.T Output Signal

Insertion PORT : PC \rightarrow P1

$f_{in} = 1.9\text{GHz}$ $P_{in} = 22\text{dBm}$ $V_{CTR} = 0/2.7\text{V}$

MODULATION : 384Kbps RNYQ $\alpha=0.5$ $1/4 \pi$ DQPSK

*ATTEN 20dB
RL 10.0dBm



NJG1507R

■ TYPICAL CHARACTERISTICS

900kHz ACP (Ta=25°C)

Insertion PORT : PC → P1


$$f_c = 1.9 \text{ GHz} \quad P_t = 22 \text{ dBm} \quad V_{\text{CTB}} = 0/2.7 \text{ V}$$

MODULATION : 384Kbps RNYQ $\alpha=0.5$ $1/4 \pi$ DQPSK

→ATTEN 10dB

RL = 7dBm

10dB/




Harmonics (Ta=25°C)

$f_{in}=1.9\text{GHz}$ $P_{in}=22\text{dBm}$ $V_{CTR(H)}=2.7\text{V}$

ATTEN 30dB



RF 10. 5dS₃



■TYPICAL CHARACTERISTICS

P1 PORT IMPEDANCE (OFF STATE)



REF 1.0 Units
 5 200.0 mUnits/
 ∇ 292.59 Ω -71.453 Ω



MARKER	f(MHz)	Mag.	Ang. ($^{\circ}$)
1	50	0.952	-15.9
2	800	0.780	-171.0
3	1500	0.740	117.0
4	2000	0.726	75.8
5	3000	0.698	1.2

P2 PORT IMPEDANCE (OFF STATE)

REF 1.0 Units
 5 200.0 mUnits/
 ∇ 280.78 Ω 15.5 Ω



MARKER	f(MHz)	Mag.	Ang. ($^{\circ}$)
1	50	0.952	-15.9
2	800	0.780	-171.0
3	1500	0.740	117.0
4	2000	0.726	75.8
5	3000	0.698	1.2

START 0.0500000000 GHz
 STOP 3.0000000000 GHz

NJG1507R


■TYPICAL CHARACTERISTICS

Scattering Parameters: S11 (OFF STATE)
($V_{CTR}=0/2.7V$, 50Ω System)

f(MHz)	P1 PORT		P2 PORT	
	Mag.	Ang.($^{\circ}$)	Mag.	Ang.($^{\circ}$)
50	0.951	-15.8	0.952	-15.9
100	0.941	-30.9	0.938	-31.0
200	0.911	-59.2	0.911	-59.2
300	0.879	-84.9	0.877	-84.6
400	0.849	-107.4	0.850	-106.7
500	0.823	-127.2	0.824	-126.0
600	0.803	-144.6	0.805	-142.8
700	0.787	-160.1	0.791	-157.6
800	0.777	-174.1	0.780	-171.0
900	0.768	173.1	0.770	176.8
1000	0.761	161.2	0.763	165.5
1100	0.750	149.6	0.749	154.2
1200	0.751	139.8	0.749	144.7
1300	0.748	129.7	0.745	135.1
1400	0.748	120.1	0.744	125.9
1500	0.745	110.9	0.740	117.0
1600	0.746	102.1	0.737	108.5
1700	0.743	93.6	0.732	100.3
1800	0.742	85.1	0.732	91.9
1900	0.740	76.9	0.728	83.7
2000	0.739	68.9	0.726	75.8
2100	0.740	61.3	0.725	68.3
2200	0.739	53.3	0.723	60.5
2300	0.735	45.8	0.718	52.7
2400	0.735	38.4	0.717	45.2
2500	0.736	30.8	0.714	37.7
2600	0.732	23.8	0.711	30.5
2700	0.734	17.0	0.708	23.4
2800	0.729	9.5	0.706	15.8
2900	0.727	2.5	0.703	8.6
3000	0.721	-4.6	0.698	1.2

NJG1507R


■APPLICATION CIRCUIT 1: Single control signal operation by using C-MOS inverter.



[1]Please connect bypass capacitors to the supply terminals of the C-MOS inverter.


[2]In order to stabilize input impedance of inverter, please pull down using 510KΩ resister from the input terminal of the C-MOS inverter to the ground plane.

■APPLICATION CIRCUIT 2: Single control signal operation by using a transistor.




NJG1507R

■TEST CIRCUIT



■RECOMMENDED PCB DESIGN



PCB SIZE=19.5x14.0mm

PCB: FR-4, $t=0.2\text{mm}$

CAPACITOR: size 1005

STRIPLINE WIDTH=0.5mm

C1~C3: 56pF

C4, C5: 10pF


R1: 510KΩ

◆: Please short between Pin4 and ground plane directly as close as possible.

Precautions

- [1] External capacitors should be connected to the input and output RF terminals (P1, P2, PC) to block the DC current. The above example is a circuit at 1.9GHz. Please select the capacitor value suitable for actual frequency from 10pF to 1000pF.
- [2] Decoupling capacitors should be connected to the control terminals (V_{CTR1} , V_{CTR2}) as close as possible. The values of these capacitors should be selected from 5pF to 100pF range. Please consider that these values are very effective to switching time (Larger capacitor gives longer switching time).
- [3] In order to keep good isolation characteristics, the ground terminals (3, 4, 6pin) should be connected to the ground pattern with wider width as close as possible, and through-hole in the ground plane should also be placed as close as possible.

■PACKAGE OUTLINE (VSP8)



Lead material : Copper
 Lead surface finish : Solder plating
 Molding material : Epoxy resin
 UNIT : mm
 Weight : 22mg

Cautions on using this product

This product contains Gallium-Arsenide (GaAs) which is a harmful material.
 • Do NOT eat or put into mouth.
 • Do NOT dispose in fire or break up this product.
 • Do NOT chemically make gas or powder with this product.
 • To waste this product, please obey the relating law of your country.

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

This product may be damaged with electric static discharge (ESD) or spike voltage. Please handle with care to avoid these damages.