



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1104 Integrated Circuit Wide and Narrow Band Amp, FM/IF Limiter

Applications:


- For FM IF Amplifier
- For TV SIF Amplifier

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}	15V
Output Voltage, V_{OUT}	24V
Input Voltage (Between Pin1 and Pin2), V_{IN}	$\pm 15V$
Power Dissipation, P_D	400mW
Derate Above 25°C	3mW/ $^\circ\text{C}$
Operating Temperature Range ($V_{CC} = 12V$), T_{opr}	-30 to $+75^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55 to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current	I_{CC}	$V_{CC} = 12V$	5.3	9.5	14.0	mA
		$V_{CC} = 9V$	–	6.5	–	mA
Power Dissipation	P_D	$V_{CC} = 12V$	–	114	–	mW
		$V_{CC} = 9V$	–	59	–	mW
Voltage Gain	G_V	$V_{CC} = 12V, R_g = 50\Omega, R_L = 1k\Omega$	–	26.5	–	dB
Input Impedance		$V_{CC} = 12V, f = 10.7\text{MHz}$				
Parallel Input Resistance	r_{ip}		–	35	–	k Ω
Parallel Input Capacitance	C_{ip}		–	8.0	–	pF
Output Impedance						
Parallel Output Resistance	r_{op}	–	80	–	k Ω	
Parallel Output Capacitance	C_{op}	–	3.0	–	pF	
Forward Transfer Admittance	y_f	–	30	–	mmhos	
Reverse Transfer Admittance	y_r	–	2.0	–	μmhos	



Pin Connection Diagram
(Front View)

