



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE1162 Integrated Circuit TV Sound IF Amp & FM Detector

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

| | |
|-----------------------------------------------------------------------|-------------------------------------|
| Supply Voltage, V_{CC} | Note 1 |
| Supply Current (I_S), I_{CC} | 50mA |
| Total Power Dissipation ($T_A \leq +70^\circ\text{C}$), P_T | 445mW |
| Operating Temperature Range, T_{opr} | -20° to $+70^\circ\text{C}$ |
| Storage Temperature Range, T_{stg} | -40° to $+150^\circ\text{C}$ |

Note 1. Pin5 can be connected to any positive voltage by using a resistor (R_S):

- Ex. $V_{CC} = 24\text{V}$, $R_S = 390\Omega$, $I_S = 30\text{mA}$
- $V_{CC} = 140\text{V}$, $R_S = 3.9\text{k}\Omega$, $I_S = 30\text{mA}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 24\text{V}$, $R_S = 390\Omega$ unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|------------------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------|------|------|------|---------------------|
| Total Circuit Current | I_{tot} | $V_{CC} = 9\text{V}$, Pin1 – Pin2, Pin9 – Pin10 Shorted | 10 | 16 | 24 | mA |
| Zener Voltage | V_{5-3} | Pin1 – Pin2, Pin9 – Pin10 Shorted | 10.3 | 11.2 | 12.2 | V |
| Input Limiting Voltage (-3dB) | $V_{i(lim)}$ | $f_o = 4.5\text{MHz}$, $f_m = 400\text{Hz}$, $\Delta f = \pm 25\text{kHz}$, $V_i = 100\text{mV}_{rms}$ | – | 250 | 400 | μV_{rms} |
| AM Rejection Ratio | AMR | AM = 400Hz, 30% | 40 | 50 | – | dB |
| Output Impedance | $R_{O(IF)}$ | $f_o = 4.5\text{MHz}$, Pin9 – Pin3 Shorted | – | 3.25 | – | $\text{k}\Omega$ |
| Output Capacitance | $C_{O(IF)}$ | | – | 10 | – | pF |
| Demodulation Output | $V_{O(AF)}$ | $f_o = 4.5\text{MHz}$, $f_m = 400\text{Hz}$, $\Delta f = \pm 25\text{kHz}$, $V_i = 100\text{mV}_{rms}$ | 0.5 | 0.75 | 1.1 | V_{rms} |
| Demodulation Signal Distortion | THD | $R_6 = 0$ | – | 0.9 | 2.0 | % |
| Output Resistance | $R_{O(7)}$ | $f = 400\text{Hz}$, $V_i = 100\text{mV}_{rms}$ | – | 7.5 | – | $\text{k}\Omega$ |
| | $R_{O(8)}$ | | – | 300 | – | Ω |
| Attenuation Circuit Max. Attenuation | ATT | $R_6 = \infty$ | 60 | 80 | – | dB |
| Sound Amp Distortion | THD | $f = 400\text{Hz}$ | – | 1.5 | – | % |
| Non-Distortional Max. Output | $V_{O(max)}$ | $V_O = 2V_{rms}$ | – | 2.0 | – | V_{rms} |
| Voltage Gain | $G_{V(AF)}$ | THD = 5% | 2.0 | 2.5 | – | V_{rms} |
| | | $V_i = 100\text{mV}_{rms}$ | 17.5 | 20.0 | 23.0 | dB |



Pin Connection Diagram

