



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE1290 Integrated Circuit AM Tuner for Car Radio

Features:


- Complete 1-Chip AM Tuner
- Good High-Input Characteristics Provided with Automatic Dynamic Range Mag. Control at RF State (THD = 1% Typ. at 130dB μ)
- High AGC FOM (63dB Typ)
- Good Usable Sensitivity (23dB μ Typ.)
- Low Distortion (0.4% Typ. at 74dB μ)
- Good Beat Characteristics (3fi beat = 40dB at 108dB μ Input, at fi = 262.5kHz)
- Large Two-Signal Selectivity (55dB Typ. at Desired 54dB μ)
- Cut-Off Pop Noise at Detuning
- Standard Power Supply Voltage Area is 10.8V through 15.6V (13.2V typ) and Local Oscillation Stopping Voltage is Less Than 6V.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC} 16V
Power Dissipation ($T_A = +60^\circ\text{C}$), P_T 550mW
Operating Temperature Range, T_{opr} -30° to $+70^\circ\text{C}$
Storage Temperature Range, T_{stg} -55° to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 13.2\text{V}$, $f_c = 1000\text{kHz}$, $f_m = 400\text{Hz}$, Output Power of Power Stage 0.5W, $R_L = 4\Omega$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Current Drain	I_{CC}	$V_{CC} = 13.2\text{V}$ at zero signal	—	15	—	mA
Signal-to-Noise Ratio	S/N	Input = 34dB μ , 30% MOD.	25.5	30	—	dB
AGC FOM		Output Base at 74dB μ input, Test at the 10dB output down, 30% MOD.	51	63	—	dB
Total Harmonic Distortion	THD	Input = 11dB μ , 30% MOD.	—	0.4	5	%
Sensitivity		Input at S/N = 20dB, 30% MOD.	—	23	—	dB μ



Pin Connection Diagram

