



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE1498 Integrated Circuit Dual Peak Power Meter Driver

Features:

- Dynamic Range: 40dB Typ
- Wide Range Meter for the 1/4 Root Compression
- Single and Dual Power Supply Operation
- Built-In Zener Diode Providing Stable Operation to Variations in Supply Voltage
(Zener Voltage: ±8.5V)
- Two Built-In Channels – Excellent for Matching Characteristics for Stereo

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Current, I_{CC}	20mA
Power Dissipation, P_D	700mW
Derate Above 25°C	7mW/ $^\circ\text{C}$

Operating Temperature Range, T_{opr} -25° to $+75^\circ\text{C}$

Electrical Characteristics: ($V_{CC} - V_{EE} \pm 25\text{V}$, $T_A = +25^\circ\text{C}$, $f = 1\text{kHz}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	I_{CCQ}	$I_{IN} = 0$, $V_9 = 7\text{V}$, $V_5 = -7\text{V}$	—	2.1	3.0	mA
Quiescent Output Current	I_{OQ}	Input Short	—	—	1	μA
Channel Balance	CH.B	$I_{IN} = -100\mu\text{A}$	—	—	1.4	dB
Input Resistance	R_{IN}		—	2	—	$\text{k}\Omega$
Channel Separation	$I_{OUT(sep)}$	$I_{IN} = 1\text{mA}$	—	-60	—	dB
Output Current	I_{OUT}	$I_{IN} = -100\mu\text{A}$	1.6	2.1	2.6	mA
Min Input Current	$I_{IN(\text{Min})}$		—	7	—	μA
Max Input Current	$I_{IN(\text{Max})}$		—	—	2	mA
Hold Terminal Voltage	V_H	Input Short, Note 1	25	—	150	mV

Note 1. The hold terminal voltage is classified into two ranks as follows:

V_H –1: 25 to 65mV

V_H –2: 45 to 150mV

Pin Connection Diagram
(Front View)

9	V _{CC}
8	Rt Ch Output
7	Rt Ch Hold
6	Rt Ch Input
5	V _{EE}
4	Lt Ch Input
3	Lt Ch Hold
2	Lt Ch Output
1	GND

